

Package ‘QLearning’

October 12, 2022

Type Package

Title Reinforcement Learning using the Q Learning Algorithm

Version 0.1.1

Author Liam Bressler

Maintainer Liam Bressler <liam.bressler@yale.edu>

Description Implements Q-Learning, a model-free form of reinforcement learning, described in work by Strehl, Li, Wiewiora, Langford & Littman (2006) <doi:10.1145/1143844.1143955>.

License GNU General Public License

LazyData TRUE

RoxygenNote 6.0.1

NeedsCompilation no

Repository CRAN

Date/Publication 2017-09-21 07:59:42 UTC

R topics documented:

qlearn	1
qlearningaction	3
qlearningupdate	5

Index	7
--------------	----------

qlearn	<i>qlearn</i>
--------	---------------

Description

Input a *game* that has variables *statevars* (which the player can keep track of). The player can perform any of *possibleactions*. The output matrix will give the expected value of each action (column) in each state (row).

Usage

```
qlern(game, statevars, possibleactions, playername="P1",
      numiter=1000, prevstrategy=NULL, ...)
```

Arguments

game	Name of the game to be played/learned.
statevars	A vector of the states to be monitored inside <i>game</i> . These are the conditions under which we the player has to make his decision.
possibleactions	A vector of the names of the possible actions inside <i>game</i> . This should be a list of every possible action that can be taken, regardless of state.
playername	The name of the variable that holds the name for the player's action inside <i>game</i> . See Details .
numiter	Number of iterations of <i>game</i> . Defaults to 50.
prevstrategy	Reward matrix returned by a previous <i>qlern</i> function; serves as a starting point. Defaults to a blank reward matrix.
...	Additional arguments to be passed to <i>game</i> .

Details

At some point in game, there must be a line of the format

```
playername <- 'Choose'
```

where *playername* is substituted with the parameter "*playername*". This line should be at the point where the user wants to have the player choose an action. Since *playername* defaults to "P1", it sufficient to put the line:

```
P1 <- 'Choose'
```

somewhere in the function.

Value

A matrix describing the expected reward values of performing a certain action (columns) in a certain state (rows).

Note

Contact at liam.bressler@yale.edu

Author(s)

Liam Bressler

References

<http://labressler.github.io/analytics>

Examples

```

cardgame <- function()
{
  playercards <- sample(1:8,4) #distribute the cards, we're player one
  ourcard <- playercards[1] #our card
  playertotals <- rep(-1,4) #including the antes
  playersinpot <- vector()
  for (player in 2:4) #other 3 players go first
  {
    if (playercards[player]>=2)
    {
      playertotals[player] <- (-3)
      playersinpot <- append(playersinpot,player)
    }
  }
  #the next line is where we want to choose our action
  player1 <- 'Choose'
  if (player1=="Call")
  {
    playertotals[1] <- (-3)
    playersinpot <- append(playersinpot,1)
  }
  potsize <- -1*(sum(playertotals)) #the amount in the pot is how much the players put in
  playercards[!(1:4 %in% playersinpot)] <- 0 #get rid of everyone who folded
  winner <- which.max(playercards) #winner is the person with the highest card who didn't fold
  playertotals[winner] <- playertotals[winner]+potsize
  return(playertotals[1]) #return how much we won
}

strat <- qlearn(game="cardgame",statevars="ourcard",possibleactions=c("Call","Fold"),
  playername="player1",numiter=25000) #make sure each function and variable name is a string

strat

```

qlearningaction

qlearningaction

Description

This repository implements **Q-Learning**, a model-free form of reinforcement learning in R.

Usage

```
qlearningaction(q, currentstate, exploration=.5)
```

Arguments

<code>q</code>	Input state/action matrix.
<code>currentstate</code>	Current state of the game. Does not have to match any of the state for q .
<code>exploration</code>	The probability of choosing a random state, rather than the one with the highest EV. Default 0.5.

Details

For internal use for *qlearn*.

Value

An action to take, taken from the possible actions of q .

Note

Contact at liam.bressler@yale.edu

Author(s)

Liam Bressler

References

<http://labressler.github.io/analytics>

Examples

```
cardgame <- function()
{
  playercards <- sample(1:8,4) #distribute the cards, we're player one
  ourcard <- playercards[1] #our card
  playertotals <- rep(-1,4) #including the antes
  playersinpot <- vector()
  for (player in 2:4) #other 3 players go first
  {
    if (playercards[player]>=2)
    {
      playertotals[player] <- (-3)
      playersinpot <- append(playersinpot,player)
    }
  }
  #the next line is where we want to choose our action
  player1 <- 'Choose'
  if (player1=="Call")
  {
    playertotals[1] <- (-3)
    playersinpot <- append(playersinpot,1)
  }
  potsize <- -1*(sum(playertotals)) #the amount in the pot is how much the players put in
```

```

    playercards[!(1:4 %in% playersinpot)] <- 0 #get rid of everyone who folded
    winner <- which.max(playercards) #winner is the person with the highest card who didn't fold
    playertotals[winner] <- playertotals[winner]+potsize
    return(playertotals[1]) #return how much we won
  }

  strat <- qlearn(game="cardgame",statevars="ourcard",possibleactions=c("Call","Fold"),
    playername="player1",numiter=25000) #make sure each function and variable name is a string

  qlearningaction(strat,3,exploration=.75)
  #Pick an action to perform when we have the 3 card, with high exploration

```

qlearningupdate

qlearningupdate

Description

This repository implements **Q-Learning**, a model-free form of reinforcement learning in R.

Usage

```

qlearningupdate(q, currentstate, currentaction, currentreward, nextstate=NULL,
  rewardcount=.5, gamma=.25)

```

Arguments

q	Input state/action matrix.
currentstate	Current state of the game. Does not have to match any of the state for <i>q</i> .
currentaction	Action to take.
currentreward	Reward for <i>currentaction</i> in current iteration.
nextstate	State that the game is in after taking <i>currentaction</i> .
rewardcount	Regularization constant for reward.
gamma	Learning rate constant for Q-Learning.

Details

For internal use for *qlearn*.

Value

An updated state/action matrix.

Note

Contact at liam.bressler@yale.edu

Author(s)

Liam Bressler

References<http://labressler.github.io/analytics>**Examples**

```

cardgame <- function()
{
  playercards <- sample(1:8,4) #distribute the cards, we're player one
  ourcard <- playercards[1] #our card
  playertotals <- rep(-1,4) #including the antes
  playersinpot <- vector()
  for (player in 2:4) #other 3 players go first
  {
    if (playercards[player]>=2)
    {
      playertotals[player] <- (-3)
      playersinpot <- append(playersinpot,player)
    }
  }
  #the next line is where we want to choose our action
  player1 <- 'Choose'
  if (player1=="Call")
  {
    playertotals[1] <- (-3)
    playersinpot <- append(playersinpot,1)
  }
  potsize <- -1*(sum(playertotals)) #the amount in the pot is how much the players put in
  playercards[!(1:4 %in% playersinpot)] <- 0 #get rid of everyone who folded
  winner <- which.max(playercards) #winner is the person with the highest card who didn't fold
  playertotals[winner] <- playertotals[winner]+potsize
  return(playertotals[1]) #return how much we won
}

strat <- qlearn(game="cardgame",statevars="ourcard",possibleactions=c("Call","Fold"),
  playername="player1",numiter=25000) #make sure each function and variable name is a string

strat <- qlearningupdate(strat,currentstate=7,currentaction="Call",currentreward=5)
#Update the matrix after an example when we call with the 7 card as our state, winning 5 chips

```

Index

* **machinelearning**

qlearn, 1

qlearningaction, 3

qlearningupdate, 5

* **optimize**

qlearn, 1

qlearningaction, 3

qlearningupdate, 5

* **reinforcementlearning**

qlearn, 1

qlearningaction, 3

qlearningupdate, 5

qlearn, 1

qlearningaction, 3

qlearningupdate, 5