

# Package ‘baf’

June 4, 2024

**Title** Block Assignment Files

**Version** 0.0.1

**Description** Download and read US Census Bureau data relationship files. Provides support for cleaning and using block assignment files since 2010, as described in <https://www.census.gov/geographies/reference-files/time-series/geo/block-assignment-files.html>. Also includes support for working with block equivalency files, used for years outside of decennial census years.

**License** MIT + file LICENSE

**Encoding** UTF-8

**RoxygenNote** 7.3.1

**Imports** cli, curl, dplyr, fs, glue, readr

**URL** <http://christophertkenny.com/baf/>,  
<https://github.com/christopherkenny/baf>

**Suggests** testthat (>= 3.0.0)

**Config/testthat/edition** 3

**NeedsCompilation** no

**Author** Christopher T. Kenny [aut, cre]  
(<https://orcid.org/0000-0002-9386-6860>),  
Cory McCartan [ctb] (<https://orcid.org/0000-0002-6251-669X>)

**Maintainer** Christopher T. Kenny <[christopherkenny@fas.harvard.edu](mailto:christopherkenny@fas.harvard.edu)>

**Repository** CRAN

**Date/Publication** 2024-06-04 16:00:06 UTC

## Contents

baf . . . . .	2
baf_download . . . . .	2
baf_download_path . . . . .	3
clean_bafs . . . . .	4

<b>Index</b>	<b>5</b>
--------------	----------

---

baf	<i>Download Block Assignment Files (BAF) from the Census Bureau</i>
-----	---

---

### Description

Download Block Assignment Files (BAF) from the Census Bureau

### Usage

```
baf(
  state,
  year = 2020,
  geographies = NULL,
  cache_to = baf_download_path(),
  overwrite = FALSE
)
```

### Arguments

state	state to download data for.
year	year to download data for. Default is 2020.
geographies	geography types to download. Default is NULL, which gets all available geographies.
cache_to	directory name to save the downloaded data. Default is baf_download_path().
overwrite	Should the data be re-downloaded? Default is FALSE.

### Value

a list of [tibbles](#) for each geography type

### Examples

```
baf('DE', 2020)
```

---

baf_download	<i>Download a file</i>
--------------	------------------------

---

### Description

Download a file

### Usage

```
baf_download(url, path, overwrite = FALSE, quiet = FALSE)
```

**Arguments**

- `url` a URL
- `path` a file path
- `overwrite` should the file at path be overwritten if it already exists? Default is FALSE.
- `quiet` should output and progress bar be suppressed?

**Value**

a path to the downloaded file, invisibly

**Examples**

```
tf <- tempfile(fileext = '.zip')
ex <- 'https://www2.census.gov/geo/docs/maps-data/data/baf2020/BlockAssign_ST01_AL.zip'
baf_download(url = ex, path = tf)
```

---

`baf_download_path` *Get download location for baf files*

---

**Description**

Get download location for baf files

**Usage**

```
baf_download_path()
```

**Value**

a path

**Examples**

```
baf_download_path()
```

---

clean_bafs	<i>Clean Block Assignment Files</i>
------------	-------------------------------------

---

**Description**

Clean Block Assignment Files

**Usage**

```
clean_bafs(bafs, state = NULL)
```

**Arguments**

bafs	list of block assignment files, named by type
state	if provided, adds the first two digits of the state FIPS to each code

**Value**

a tibble with two columns

- GEOID: block GEOIDs
- target: output GEOIDs for the target geography

**Examples**

```
baf('WA') |> clean_bafs('WA')
```

# Index

baf, [2](#)  
baf\_download, [2](#)  
baf\_download\_path, [3](#)  
  
clean\_bafs, [4](#)  
  
tibble, [2](#)