

Package ‘minimalistGODB’

March 18, 2025

Version 1.0

Date 2025-02-27

Title Build a Minimalist Gene Ontology (GO) Database (GODB)

Maintainer Barry Zeeberg <barryz2013@gmail.com>

Author Barry Zeeberg [aut, cre]

Depends R (>= 4.2.0)

LazyData true

LazyDataCompression xz

Description Normally building a GODB is fairly complicated, involving downloading multiple database files and using these to build e.g. a 'mySQL' database. Accessing this database is also complicated, involving an intimate knowledge of the database in order to construct reliable queries. Here we have a more modest goal, generating GOGO3, which is a stripped down version of the GODB that is restricted to human genes as designated by the HUGO Gene Nomenclature Committee (HGNC) (see <<https://geneontology.org/>>). This can be built in a matter of seconds from 2 easily downloaded files (see <<https://current.geneontology.org/products/pages/downloads.html>> and <<https://geneontology.org/docs/download-ontology/>>), and it can be queried by e.g. `w<-which(GOGO3[,`HGNC`] %in% hgncList)` where GOGO3 is a matrix representing the minimalist GODB and hgncList is a list of gene identifiers. This database will be used in my upcoming package 'GoMiner' which is based on my previous publication (see Zeeberg, B.R., Feng, W., Wang, G. et al. (2003)<[doi:10.1186/gb-2003-4-4-r28](https://doi.org/10.1186/gb-2003-4-4-r28)>). Relevant .RData files are available from GitHub (<<https://github.com/barryzee/GO>>).

License GPL (>= 2)

Encoding UTF-8

VignetteBuilder knitr

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

RoxygenNote 7.3.2

Config/testthat/edition 3

NeedsCompilation no

Repository CRAN

Date/Publication 2025-03-18 15:20:07 UTC

Contents

buildGODatabase	2
GO	3
GOA	3
GOGOAsmall	4
joinGO	4
parseGOA	5
parseGOBASIC	6
subsetGOGOA	7

Index **8**

buildGODatabase	<i>buildGODatabase</i>
-----------------	------------------------

Description

driver to build GO database

Usage

```
buildGODatabase(goa, gobasic, dir = NULL, verbose = FALSE)
```

Arguments

goa	character string path name to downloaded goa_human.gaf
gobasic	character string path name to downloaded go-basic.obo
dir	character string path name to directory to hold subdirectory GODB_RDATA
verbose	Boolean if TRUE print out some diagnostic info

Details

download goa_human.gaf from <https://current.geneontology.org/products/pages/downloads.html> download go-basic.obo from <https://geneontology.org/docs/download-ontology/> parameter dir should be omitted or NULL except for the developer harvesting the updated .RData DBs

The output GOGOA was saved as an .RData file. This was too large for CRAN. It is available from <https://github.com/barryzee/GO>

Value

returns GO database with columns c("HGNC","GO","RELATION","NAME","ONTOLOGY")

Examples

```
## Not run:
# replace my path names for goa and gobasic with your own!!
# these were obtained from the download sites listed in 'details' section
goa<-"~/goa_human.gaf"
gobasic<-"~/go-basic.obo"
GOGO<-buildGODatabase(goa,gobasic,dir="~/",verbose=FALSE)
# > dim(GOGO)
# [1] 720139      5
# > GOGO[1:5,]
#      HGNC      GO      RELATION      NAME      ONTOLOGY
# [1,] "NUDT4B"    "GO:0003723" "enables"  "RNA binding"  "molecular_function"
# [2,] "NUDT4B"    "GO:0005515" "enables"  "protein binding"  "molecular_function"
# [3,] "NUDT4B"    "GO:0046872" "enables"  "metal ion binding"  "molecular_function"
# [4,] "NUDT4B"    "GO:0005829" "located_in"  "cytosol"      "cellular_component"
# [5,] "TRBV20R9-2" "GO:0002376" "involved_in" "immune system process" "biological_process"

## End(Not run)

# here is a small example that you can run
f1<-system.file("extdata","goa_human.small.gaf",package="minimalistGODB")
f2<-system.file("extdata","go-basic.small.obo",package="minimalistGODB")
GODBsmall<-buildGODatabase(f1,f2,verbose=FALSE)
```

GO *minimalistGODB data set*

Description

minimalistGODB data set generated by parseGOBASIC()

Usage

data(GO)

GOA *minimalistGODB data set*

Description

minimalistGODB data set generated by parseGOA()

Usage

data(GOA)

GOGOAsmall	<i>minimalistGODB data set</i>
------------	--------------------------------

Description

small version of minimalistGODB data set generated by buildGODatabase()

Usage

```
data(GOGOAsmall)
```

joinGO	<i>joinGO</i>
--------	---------------

Description

join the outputs of parseGOA and parseGOBASIC to add the GO category name and the ontology to GOA

Usage

```
joinGO(GOA, GO)
```

Arguments

GOA	output of parseGOA()
GO	output of parseGOBASIC()

Value

returns a matrix with columns c("HGNC","GO","RELATION","NAME","ONTOLOGY")

Examples

```
GOGOAsmall <- joinGO(GOA, GO)
# GOGOAsmall[1:5,]
# HGNC      GO          RELATION      NAME          ONTOLOGY
# [1,] "NUDT4B"      "GO:0003723" "enables"     "RNA binding"  "molecular_function"
# [2,] "NUDT4B"      "GO:0005515" "enables"     "protein binding"  "molecular_function"
# [3,] "NUDT4B"      "GO:0046872" "enables"     "metal ion binding"  "molecular_function"
# [4,] "NUDT4B"      "GO:0005829" "located_in"  "cytosol"        "cellular_component"
# v[5,] "TRBV200R9-2" "GO:0002376" "involved_in" "immune system process" "biological_process"
# GO_NAME
# [1,] "GO_0003723__RNA_binding"
# [2,] "GO_0005515__protein_binding"
# [3,] "GO_0046872__metal_ion_binding"
# [4,] "GO_0005829__cytosol"
```

```
# [5,] "GO_0002376__immune_system_process"

# querying GOGOA to compute gene enrichment of some GO categories
hgncList<-GOGOA[1:1000,"HGNC"]
ontology<-"biological_process"
w<-which(GOGOA[, "ONTOLOGY"] == ontology)
GOGOA<-GOGOA[w,]
w<-which(GOGOA[, "HGNC"] %in% hgncList)
t<-sort(table(GOGOA[w, "NAME"]),decreasing=TRUE)[1:10]
```

parseGOA

parseGOA

Description

parse goa_human.gaf

Usage

```
parseGOA(goa)
```

Arguments

goa character string path name to downloaded goa_human.gaf

Details

download goa_human.gaf from <https://current.geneontology.org/products/pages/downloads.html>

Value

returns matrix with columns c("HGNC","GO","RELATION")

Examples

```
## Not run:
# replace my path name for goa with your own!!
# this was obtained from the download sites listed in 'details' section
GOA<-parseGOA("~/goa_human.gaf")
# GOA[1:5,]
#    HGNC            GO            RELATION
# [1,] "NUDT4B"       "GO:0003723" "enables"
# [2,] "NUDT4B"       "GO:0005515" "enables"
# [3,] "NUDT4B"       "GO:0046872" "enables"
# [4,] "NUDT4B"       "GO:0005829" "located_in"
# [5,] "TRBV200R9-2" "GO:0002376" "involved_in"

## End(Not run)
# here is a small example that you can run
```

```
f<-system.file("extdata","goa_human.small.gaf",package="minimalistGODB")
GOAsmall<-parseGOA(f)
```

parseGOBASIC

parseGOBASIC

Description

parse go-basic.obo

Usage

```
parseGOBASIC(gobasic, verbose = FALSE)
```

Arguments

gobasic	character string path name to downloaded go-basic.obo
verbose	Boolean if TRUE print out some diagnostic info

Details

download go-basic.obo from <https://geneontology.org/docs/download-ontology/>

Value

returns a list whose components are c("m", "bp", "mf", "cc")

Examples

```
## Not run:
# replace my path name for gobasic with your own!!
# this was obtained from the download sites listed in 'details' section
GO<-parseGOBASIC("~/go-basic.obo",verbose=FALSE)
# GO$bp[1:5,]
#      GO          NAME          ONTOLOGY
# GO:0000001 "GO:0000001" "mitochondrion inheritance" "biological_process"
# GO:0000002 "GO:0000002" "mitochondrial genome maintenance" "biological_process"
# GO:0000011 "GO:0000011" "vacuole inheritance" "biological_process"
# GO:0000012 "GO:0000012" "single strand break repair" "biological_process"
# GO:0000017 "GO:0000017" "alpha-glucoside transport" "biological_process"

## End(Not run)

# here is a small example that you can run
f<-system.file("extdata","go-basic.small.obo",package="minimalistGODB")
GOsmall<-parseGOBASIC(f)
```

`subsetGOGOA` *subsetGOGOA*

Description

split GOGOA into 3 separate ontologies

Usage

```
subsetGOGOA(GOGOA)
```

Arguments

GOGOA return value of `minimalistGODB::joinGO()`

Value

returns a list containing subsets of GOGOA for each ontology, unique gene and cat lists, and stats

Examples

```
#load("data/GOGOAsmall.RData")
GOGOA3small<-subsetGOGOA(GOGOAsmall)
```

Index

buildGODatabase, [2](#)

GO, [3](#)

GOA, [3](#)

GOGOAsmall, [4](#)

joinGO, [4](#)

parseGOA, [5](#)

parseGOBASIC, [6](#)

subsetGOGOA, [7](#)