

Package ‘ows4R’

June 26, 2024

Version 0.4

Date 2024-06-26

Title Interface to OGC Web-Services (OWS)

Maintainer Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Depends R (>= 3.3.0)

Imports methods, R6, httr, openssl, keyring, XML (>= 3.96-1.1),
geometa (>= 0.7-1), sf, terra, parallel, crayon

Suggests testthat, knitr, markdown

Description Provides an Interface to Web-Services defined as standards by the Open Geospatial Consortium (OGC), including Web Feature Service (WFS) for vector data, Web Coverage Service (WCS), Catalogue Service (CSW) for ISO/OGC metadata, Web Processing Service (WPS) for data processes, and associated standards such as the common web-service specification (OWS) and OGC Filter Encoding. Partial support is provided for the Web Map Service (WMS). The purpose is to add support for additional OGC service standards such as Web Coverage Processing Service (WCPS), the Sensor Observation Service (SOS), or even new standard services emerging such OGC API or SensorThings.

License MIT + file LICENSE

URL <https://github.com/eblondel/ows4R>,
<https://eblondel.github.io/ows4R/>,
<https://www.ogc.org/standards/>

BugReports <https://github.com/eblondel/ows4R/issues>

LazyLoad yes

RoxygenNote 7.3.1

VignetteBuilder knitr

NeedsCompilation no

Author Emmanuel Blondel [aut, cre] (<<https://orcid.org/0000-0002-5870-5762>>),
Alexandre Bennici [ctb] (<<https://orcid.org/0000-0003-2160-3487>>),
Norbert Billet [ctb]

Repository CRAN

Date/Publication 2024-06-26 09:50:02 UTC

Contents

And	4
BBOX	5
BinaryComparisonOpType	6
BinaryLogicOpType	7
CASClient	9
CSWCapabilities	10
CSWClient	11
CSWConstraint	17
CSWDescribeRecord	18
CSWGetRecordById	20
CSWGetRecords	21
CSWHarvest	23
CSWQuery	25
CSWRecordProperty	27
CSWTransaction	29
getOWSNamespace	30
getOWSNamespace	31
Not	31
OGCAbstractObject	32
OGCExpression	36
OGCFilter	37
Or	39
ows4R	40
OWSBoundingBox	40
OWSCapabilities	42
OWSClient	45
OWSCodeType	48
OWSException	49
OWSGetCapabilities	50
OWSHttpRequest	52
OWSNamespace	55
OWSOperation	56
OWSOperationsMetadata	58
OWSRequest	59
OWSServiceIdentification	60
OWSServiceProvider	62
OWSUtils	64
OWSWG84BoundingBox	65
PropertyIsBetween	66
PropertyIsEqualTo	67
PropertyIsGreaterThan	68
PropertyIsGreaterThanOrEqualTo	69

PropertyIsLessThan	70
PropertyIsLessThanOrEqualTo	71
PropertyIsLike	73
PropertyIsNotEqualTo	74
PropertyIsNull	75
registerOWSNamespace	76
setOWSNamespace	77
UnaryLogicOpType	77
WCSCapabilities	79
WCSClient	80
WCSCoverage	83
WCSCoverageDescription	85
WCSCoverageDomain	87
WCSCoverageFilenameHandler	89
WCSCoverageSpatialDomain	89
WCSCoverageSummary	91
WCSCoverageTemporalDomain	95
WCSDescribeCoverage	96
WCSGetCoverage	98
WCSGridCRS	100
WCSGSElevationDomain	101
WCSGSTimeDomain	102
WFSCapabilities	104
WFSClient	105
WFSDescribeFeatureType	108
WFSFeatureType	109
WFSFeatureTypeElement	113
WFSGetFeature	115
WMSCapabilities	116
WMSClient	118
WMSGetFeatureInfo	121
WMSLayer	123
WPSBoundingBoxData	127
WPSCapabilities	128
WPSClient	130
WPSComplexData	133
WPSComplexInputDescription	135
WPSComplexOutputDescription	136
WPSDescribeProcess	137
WPSDescriptionParameter	139
WPSException	140
WPSExecute	142
WPSExecuteResponse	144
WPSFormat	146
WPSInput	148
WPSInputDescription	149
WPSLiteralData	151
WPSLiteralInputDescription	152

WPSLiteralOutputDescription	154
WPSOutput	155
WPSOutputDescription	157
WSPParameter	158
WSPProcess	159
WSPProcessDescription	161
WPSResponseDocument	164
WPSStatus	165

Index	167
--------------	------------

And	<i>And</i>
-----	------------

Description

And

And

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an And operator

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OGCExpression](#) -> [ows4R::BinaryLogicOpType](#) -> And

Methods

Public methods:

- [And\\$new\(\)](#)
- [And\\$clone\(\)](#)

Method [new\(\)](#): Initializes an [And](#) expression

Usage:

[And\\$new\(...\)](#)

Arguments:

... list of objects of class [OGCExpression](#)

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

[And\\$clone\(deep = FALSE\)](#)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
expr1 <- PropertyIsEqualTo$new(PropertyName = "property1", Literal = "value1")
expr2 <- PropertyIsEqualTo$new(PropertyName = "property2", Literal = "value2")
and <- And$new(expr1,expr2)
and_xml <- and$encode() #see how it looks like in XML
```

BBOX

BBOX

Description

BBOX

BBOX

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an BBOX

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OGCExpression](#) -> BBOX

Public fields

PropertyName property name field for XML encoding

Envelope envelope as object of class [GMLEnvelope](#) from **geometa**

Methods**Public methods:**

- [BBOX\\$new\(\)](#)
- [BBOX\\$clone\(\)](#)

Method `new()`: Initializes a [BBOX](#) expression

Usage:

```
BBOX$new(bbox, srsName = NULL)
```

Arguments:

bbox an object of class `matrix`
 srsName srs name

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
BBOX$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
bbox <- OWSUtils$toBBOX(-180,-90,180,90)
expr <- BBOX$new(bbox)
expr_xml <- expr$encode() #see how it looks like in XML
```

BinaryComparisonOpType

BinaryComparisonOpType

Description

BinaryComparisonOpType

BinaryComparisonOpType

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an BinaryComparisonOpType

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OGCExpression](#) -> BinaryComparisonOpType

Public fields

PropertyName property name field for XML encoding

Literal literal field for XML encoding

attrs attributes for XML encoding

Methods**Public methods:**

- [BinaryComparisonOpType\\$new\(\)](#)
- [BinaryComparisonOpType\\$clone\(\)](#)

Method `new()`: Initializes an object extending [BinaryComparisonOpType](#)

Usage:

```
BinaryComparisonOpType$new(  
  element,  
  namespacePrefix,  
  propertyName,  
  literal,  
  matchCase = NA  
)
```

Arguments:

element element name
namespacePrefix XML namespace prefix
propertyName property name
literal literal
matchCase match case

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
BinaryComparisonOpType$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

abstract super class of all the property operation classes

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

BinaryLogicOpType

BinaryLogicOpType

Description

BinaryLogicOpType

BinaryLogicOpType

Format

R6Class object.

Value

Object of R6Class for modelling an BinaryLogicOpType

Super classes

ows4R::OGCAbstractObject -> ows4R::OGCEXpression -> BinaryLogicOpType

Public fields

operations a list OGC expressions

Methods**Public methods:**

- BinaryLogicOpType\$new()
- BinaryLogicOpType\$setExprVersion()
- BinaryLogicOpType\$clone()

Method new(): Initializes a BinaryLogicOpType expression

Usage:

```
BinaryLogicOpType$new(..., element, namespacePrefix, exprVersion = "1.1.0")
```

Arguments:

... list of objects of class OGCEXpression

element element

namespacePrefix namespacePrefix

exprVersion OGC expression version. Default is "1.1.0"

Method setExprVersion(): Sets expression version. The methods will control that expression versions are set for each of the operations specified in the expression.

Usage:

```
BinaryLogicOpType$setExprVersion(exprVersion)
```

Arguments:

exprVersion OGC expression version

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
BinaryLogicOpType$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

abstract super class of all the binary logical operation classes

CASClient

CASClient

Description

CASClient

CASClient

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing a Central Authentication Service (CAS).

Methods

Public methods:

- [CASClient\\$new\(\)](#)
- [CASClient\\$getUrl\(\)](#)
- [CASClient\\$login\(\)](#)
- [CASClient\\$logout\(\)](#)
- [CASClient\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [CASClient](#)

Usage:

`CASClient$new(url)`

Arguments:

url base URL of the Central Authentication Service (CAS)

Method [getUrl\(\)](#): Get CAS base URL

Usage:

`CASClient$getUrl()`

Returns: the base URL

Method [login\(\)](#): Logs in the CAS

Usage:

`CASClient$login(user, pwd)`

Arguments:

user user

pwd password

Returns: TRUE if logged in, FALSE otherwise

Method `logout()`: Logs out from the CAS

Usage:

`CASClient$logout()`

Returns: TRUE if logged out, FALSE otherwise

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`CASClient$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

CSWCapabilities

CSWCapabilities

Description

CSWCapabilities

CSWCapabilities

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing an OGC Catalogue Service for the Web (CSW) Get Capabilities document.

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSCapabilities](#) -> CSWCapabilities

Methods**Public methods:**

- [CSWCapabilities\\$new\(\)](#)
- [CSWCapabilities\\$clone\(\)](#)

Method `new()`: Initializes a [CSWCapabilities](#) object

Usage:

```
CSWCapabilities$new(url, version, client = NULL, logger = NULL, ...)
```

Arguments:

`url` url

`version` version

`client` object of class [CSWClient](#)

`logger` logger type NULL, "INFO" or "DEBUG"

... any other parameter to pass to [OWSGetCapabilities](#) service request

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CSWCapabilities$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used to read a [CSWCapabilities](#) document. The use of [CSWClient](#) is recommended instead to benefit from the full set of capabilities associated to a CSW server.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

CSWClient

CSWClient

Description

CSWClient

CSWClient

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing an OGC Catalogue Service for the Web.

Super classes

ows4R::OGCAbstractObject -> ows4R::OWSClient -> CSWClient

Methods**Public methods:**

- CSWClient\$new()
- CSWClient\$getCapabilities()
- CSWClient\$reloadCapabilities()
- CSWClient\$describeRecord()
- CSWClient\$getRecordById()
- CSWClient\$getRecords()
- CSWClient\$transaction()
- CSWClient\$insertRecord()
- CSWClient\$updateRecord()
- CSWClient\$deleteRecord()
- CSWClient\$deleteRecordById()
- CSWClient\$harvestRecord()
- CSWClient\$harvestNode()
- CSWClient\$clone()

Method new(): This method is used to instantiate a CSWClient with the url of the OGC service. Authentication is supported using basic auth (using user/pwd arguments), bearer token (using token argument), or custom (using headers argument). By default, the logger argument will be set to NULL (no logger). This argument accepts two possible values: INFO: to print only **ows4R** logs, DEBUG: to print more verbose logs

Usage:

```
CSWClient$new(
  url,
  serviceVersion = NULL,
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = c(),
  config = httr::config(),
  cas_url = NULL,
  logger = NULL
)
```

Arguments:

```
url url
serviceVersion CSW service version
user user
pwd password
token token
```

headers headers
config config
cas_url Central Authentication Service (CAS) URL
logger logger

Method getCapabilities(): Get CSW capabilities

Usage:

CSWClient\$getCapabilities()

Returns: an object of class [CSWCapabilities](#)

Method reloadCapabilities(): Reloads CSW capabilities

Usage:

CSWClient\$reloadCapabilities()

Method describeRecord(): Describe records. Retrieves the XML schema for CSW records. By default, returns the XML schema for the CSW records (<http://www.opengis.net/cat/csw/2.0.2>). For other schemas, specify the outputSchema required, e.g. <http://www.isotc211.org/2005/gmd> for ISO 19115/19139 schema

Usage:

CSWClient\$describeRecord(namespace, ...)

Arguments:

namespace namespace

... any other parameter to pass to the [CSWDescribeRecord](#) service request

Returns: the service record description

Method getRecordById(): Get a record by Id. By default, the record will be returned following the CSW schema (<http://www.opengis.net/cat/csw/2.0.2>). For other schemas, specify the outputSchema required, e.g. <http://www.isotc211.org/2005/gmd> for ISO 19115/19139 records. The parameter elementSetName should among values "full", "brief", "summary". The default "full" corresponds to the full metadata sheet returned. "brief" and "summary" will contain only a subset of the metadata content.

Usage:

CSWClient\$getRecordById(id, elementSetName = "full", ...)

Arguments:

id record id

elementSetName element set name. Default is "full"

... any other parameter to pass to [CSWGetRecordById](#) service request

Returns: the fetched record, NULL otherwise

Method getRecords(): Get records based on a query, object of class CSWQuery. The maximum number of records can be set either for the full query (maxRecords) or per request (maxRecordsPerRequest, default set to 10 records) considering this operation is paginated. By default, the record will be returned following the CSW schema (<http://www.opengis.net/cat/csw/2.0.2>). For other schemas, specify the outputSchema required, e.g. <http://www.isotc211.org/2005/gmd> for ISO 19115/19139 records.

Usage:

```
CSWClient$getRecords(
  query = CSWQuery$new(),
  maxRecords = NULL,
  maxRecordsPerRequest = 10L,
  ...
)
```

Arguments:

query an object of class [CSWQuery](#). By default, an empty query is set.
maxRecords max number of total records. Default is NULL meaning all records are returned.
maxRecordsPerRequest max number of records to return per request. Default set to 10.
 ... any other parameter to be passed to [CSWGetRecords](#) service request

Returns: the list of records. By default each record will be returned as Dublin Core list object. In case ISO 19115/19139 is set as outputSchema, each record will be object of class ISOMetadata from **geometa**.

Method `transaction()`: Generic transaction method. Used for inserting, updating or deleting metadata using the transactional CSW service. The type gives the type of transaction (Insert, Update, or Delete). The record

Usage:

```
CSWClient$transaction(
  type,
  record = NULL,
  recordProperty = NULL,
  constraint = NULL,
  ...
)
```

Arguments:

type of transaction either "Insert", "Update" or "Delete"
record the record subject of the transaction
recordProperty record property, object of class [CSWRecordProperty](#)
constraint constraint, object of class [CSWConstraint](#)
 ... any other parameter to pass to [CSWTransaction](#) service request

Returns: TRUE if transaction succeeded, FALSE otherwise

Method `insertRecord()`: Inserts a new record

Usage:

```
CSWClient$insertRecord(record, ...)
```

Arguments:

record record subject of the Insertion
 ... any other parameter to pass to the transaction

Returns: TRUE if insertion succeeded, FALSE otherwise

Method `updateRecord()`: Updates an existing record

Usage:

```
CSWClient$updateRecord(
  record = NULL,
  recordProperty = NULL,
  constraint = NULL,
  ...
)
```

Arguments:

record record subject of the Insertion
 recordProperty record property, object of class [CSWRecordProperty](#)
 constraint constraint, object of class [CSWConstraint](#)
 ... any other parameter to pass to the transaction

Returns: TRUE if update succeeded, FALSE otherwise

Method deleteRecord(): Deletes an existing (set of) record(s). A constraint (object of class [CSWConstraint](#)) can be specified to limit the deletion to some records.

Usage:

```
CSWClient$deleteRecord(record = NULL, constraint = NULL, ...)
```

Arguments:

record record subject of the Insertion
 constraint constraint, object of class [CSWConstraint](#)
 ... any other parameter to pass to the transaction

Returns: TRUE if deletion succeeded, FALSE otherwise

Method deleteRecordById(): Deletes an existing record by identifier (constraint used to identify the record based on its identifier).

Usage:

```
CSWClient$deleteRecordById(id)
```

Arguments:

id record id

Returns: TRUE if deletion succeeded, FALSE otherwise

Method harvestRecord(): Harvests a single record from a sourceUrl, given a resourceType (by default "http://www.isotc211.org/2005/gmd").

Usage:

```
CSWClient$harvestRecord(
  sourceUrl,
  resourceType = "http://www.isotc211.org/2005/gmd"
)
```

Arguments:

sourceUrl source URL
 resourceType resource type. Default is "http://www.isotc211.org/2005/gmd"

Returns: TRUE if harvesting succeeded, FALSE otherwise

Method harvestNode(): Harvests a CSW node (having its endpoint defined by an url). A query (object of class CSWQuery) can be specified if needed to restrain the harvesting to a subset. The resourceType defines the type of resources to be harvested (by default "http://www.isotc211.org/2005/gmd")

Usage:

```
CSWClient$harvestNode(
  url,
  query = CSWQuery$new(),
  resourceType = "http://www.isotc211.org/2005/gmd",
  sourceBaseUrl
)
```

Arguments:

url CSW node URL

query a CSW query, object of class [CSWQuery](#)

resourceType resource type. Default is "http://www.isotc211.org/2005/gmd"

sourceBaseUrl source base URL

Returns: an object of class list giving the number of records found and those actually harvested

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
CSWClient$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
## Not run:
#example based on CSW endpoint responding at http://localhost:8000/csw
csw <- CSWClient$new("http://localhost:8000/csw", serviceVersion = "2.0.2")

#get capabilities
caps <- csw$getCapabilities()

#get records
records <- csw$getRecords()

#get record by id
record <- csw$getRecordById("my-metadata-id")

#Advanced examples at https://github.com/eblondel/ows4R/wiki#csw

## End(Not run)
```

CSWConstraint	<i>CSWConstraint</i>
---------------	----------------------

Description

CSWConstraint

CSWConstraint

Format

R6Class object.

Value

Object of R6Class for modelling an CSW Constraint

Super class

ows4R::OGCAbstractObject -> CSWConstraint

Public fields

wrap internal property for object XML encoding

CqlText text to use as CQL filter

filter

Methods**Public methods:**

- [CSWConstraint\\$new\(\)](#)
- [CSWConstraint\\$setServiceVersion\(\)](#)
- [CSWConstraint\\$clone\(\)](#)

Method new(): Initializes a [CSWConstraint](#) object to be used to constrain CSW operations.*Usage:*

CSWConstraint\$new(cqlText = NULL, filter = NULL, serviceVersion = "2.0.2")

Arguments:

cqlText cqlText, object of class character

filter filter, object extending [OGCFilter](#)

serviceVersion CSW service version. Default is "2.0.2"

Method setServiceVersion(): Set service version. This methods ensures that underlying filter property is properly set with the right OGC filter version.*Usage:*

CSWConstraint\$setServiceVersion(serviceVersion)

Arguments:

serviceVersion service version

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
CSWConstraint$new(clone(deep = FALSE))
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
filter <- OGCFilter$new( PropertyIsEqualTo$new("apiso:Identifier", "12345") )
cons <- CSWConstraint$new(filter = filter)
cons_xml <- cons$encode() #how it looks like in XML
```

CSWDescribeRecord	<i>CSWDescribeRecord</i>
-------------------	--------------------------

Description

CSWDescribeRecord

CSWDescribeRecord

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a CSW DescribeRecord request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> CSWDescribeRecord

Methods**Public methods:**

- [CSWDescribeRecord\\$new\(\)](#)
- [CSWDescribeRecord\\$clone\(\)](#)

Method `new()`: Initializes a [CSWDescribeRecord](#) service request

Usage:

```
CSWDescribeRecord$new(
  capabilities,
  op,
  url,
  version,
  namespace = NULL,
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = c(),
  config = httr::config(),
  logger = NULL,
  ...
)
```

Arguments:

`capabilities` an object of class [CSWCapabilities](#)
`op` object of class [OWSOperation](#) as retrieved from `capabilities`
`url` url
`version` version
`namespace` namespace
`user` user
`pwd` password
`token` token
`headers` headers
`config` config
`logger` logger
`...` any parameter to pass to the service request

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CSWDescribeRecord$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a CSW DescribeRecord request

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

CSWGetRecordById

CSWGetRecordById

Description

CSWGetRecordById

CSWGetRecordById

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a CSW GetRecordById request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> CSWGetRecordById

Public fields

Id record Id property for request XML encoding

ElementSetName element set name property for XML encoding

Methods**Public methods:**

- [CSWGetRecordById\\$new\(\)](#)
- [CSWGetRecordById\\$clone\(\)](#)

Method `new()`: Initializes a [CSWGetRecordById](#) service request

Usage:

```
CSWGetRecordById$new(  
  capabilities,  
  op,  
  url,  
  serviceVersion = "2.0.2",  
  user = NULL,  
  pwd = NULL,  
  token = NULL,  
  headers = headers,  
  config = httr::config(),
```

```

        id,
        elementSetName = "full",
        logger = NULL,
        ...
    )

```

Arguments:

capabilities an object of class [CSWCapabilities](#)
op object of class [OWSOperation](#) as retrieved from capabilities
url url
serviceVersion serviceVersion. Default is "2.0.2"
user user
pwd password
token token
headers headers
config config
id record id
elementSetName element set name. Default is "full"
logger logger
... any parameter to pass to the service request

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
CSWGetRecordById$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a CSW GetRecordById request

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

CSWGetRecords

CSWGetRecords

Description

CSWGetRecords

CSWGetRecords

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a CSW GetRecords request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> CSWGetRecords

Public fields

Query query property for request XML encoding

Methods**Public methods:**

- [CSWGetRecords\\$new\(\)](#)
- [CSWGetRecords\\$clone\(\)](#)

Method new(): Initializes a [CSWGetRecordById](#) service request

Usage:

```
CSWGetRecords$new(
  capabilities,
  op,
  url,
  serviceVersion = "2.0.2",
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = list(),
  config = httr::config(),
  query = NULL,
  logger = NULL,
  ...
)
```

Arguments:

capabilities an object of class [CSWCapabilities](#)
 op object of class [OWSOperation](#) as retrieved from capabilities
 url url
 serviceVersion serviceVersion. Default is "2.0.2"
 user user
 pwd password
 token token
 headers headers
 config config
 query object of class [CSWQuery](#)
 logger logger

... any parameter to pass to the service request, such as `resultType`, `startPosition`, `maxRecords`, `outputFormat`, or `outputSchema`

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CSWGetRecords$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a CSW GetRecords request

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

CSWHarvest

CSWHarvest

Description

CSWHarvest

CSWHarvest

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a CSW Harvest request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> CSWHarvest

Public fields

`Source` source property for request XML encoding

`ResourceType` resource type property for request XML encoding

`ResourceFormat` resource format property for request XML encoding

Methods

Public methods:

- [CSWHarvest\\$new\(\)](#)
- [CSWHarvest\\$clone\(\)](#)

Method `new()`: Initializes a [CSWHarvest](#) service request

Usage:

```
CSWHarvest$new(
  capabilities,
  op,
  url,
  serviceVersion = "2.0.2",
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = list(),
  config = httr::config(),
  source = NULL,
  resourceType = "http://www.isotc211.org/schemas/2005/gmd/",
  resourceFormat = "application/xml",
  logger = NULL,
  ...
)
```

Arguments:

`capabilities` an object of class [CSWCapabilities](#)
`op` object of class [OWSOperation](#) as retrieved from capabilities
`url` url
`serviceVersion` serviceVersion. Default is "2.0.2"
`user` user
`pwd` password
`token` token
`headers` headers
`config` config
`source` source
`resourceType` resource type. Default is "http://www.isotc211.org/schemas/2005/gmd/"
`resourceFormat` resource format. Default is "application/xml"
`logger` logger
`...` any parameter to pass to the service request

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CSWHarvest$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a CSW Harvest request

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

CSWQuery

CSWQuery

Description

CSWQuery

CSWQuery

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an CSW Query

Super class

[ows4R::OGCAbstractObject](#) -> CSWQuery

Public fields

ElementSetName element set name property for request XML encoding

constraint property for request XML encoding

Methods**Public methods:**

- [CSWQuery\\$new\(\)](#)
- [CSWQuery\\$setServiceVersion\(\)](#)
- [CSWQuery\\$clone\(\)](#)

Method new(): This method is used to instantiate an CSWQuery object. The elementSetName can be either "full" (default), "brief" or "summary". A constraint CSWConstraint can be defined for the query. The typeName indicates to query (default "csw:Record"). The serviceVersion gives the CSW service version (default "2.0.2")

Usage:

```
CSWQuery$new(
  elementSetName = "full",
  constraint = NULL,
  typeNames = "csw:Record",
  serviceVersion = "2.0.2"
)
```

Arguments:

elementSetName element set name. Default is "full"
 constraint object of class [CSWConstraint](#)
 typeNames type names
 serviceVersion CSW service version

Method `setServiceVersion()`: Set service version. The methods ensures property naming of `typeNames` depending on the service version

Usage:

```
CSWQuery$setServiceVersion(serviceVersion)
```

Arguments:

serviceVersion service version

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CSWQuery$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
#CSWQuery - elementSetName
query_full <- CSWQuery$new()
query_brief <- CSWQuery$new(elementSetName = "brief")
query_summary <- CSWQuery$new(elementSetName = "summary")

#CSWQuery - cqlText with title
cons <- CSWConstraint$new(cqlText = "dc:title like '%ips%'")
query <- CSWQuery$new(constraint = cons)

#CSW 2.0.2 - Query - Filter / AnyText
filter <- OGCFilter$new( PropertyIsLike$new("csw:AnyText", "%Physio%"))
cons <- CSWConstraint$new(filter = filter)
query <- CSWQuery$new(constraint = cons)

#CSW 2.0.2 - Query - Filter / AnyText Equal
filter <- OGCFilter$new( PropertyIsEqualTo$new("csw:AnyText", "species"))
```

```

cons <- CSWConstraint$new(filter = filter)
query <- CSWQuery$new(constraint = cons)

#CSW 2.0.2 - Query - Filter / AnyText And Not
filter <- OGCFilter$new(And$new(
  PropertyIsLike$new("csw:AnyText", "%lorem%"),
  PropertyIsLike$new("csw:AnyText", "%ipsum%"),
  Not$new(
    PropertyIsLike$new("csw:AnyText", "%dolor%")
  )
))
cons <- CSWConstraint$new(filter = filter)
query <- CSWQuery$new(constraint = cons)

#CSW 2.0.2 - Query - Filter / AnyText And nested Or
filter <- OGCFilter$new(And$new(
  PropertyIsEqualTo$new("dc:title", "Aliquam fermentum purus quis arcu"),
  PropertyIsEqualTo$new("dc:format", "application/pdf"),
  Or$new(
    PropertyIsEqualTo$new("dc:type", "http://purl.org/dc/dcmitype/Dataset"),
    PropertyIsEqualTo$new("dc:type", "http://purl.org/dc/dcmitype/Service"),
    PropertyIsEqualTo$new("dc:type", "http://purl.org/dc/dcmitype/Image"),
    PropertyIsEqualTo$new("dc:type", "http://purl.org/dc/dcmitype/Text")
  )
))
cons <- CSWConstraint$new(filter = filter)
query <- CSWQuery$new(elementSetName = "brief", constraint = cons)

#CSW 2.0.2 - Query - Filter / BBOX
bbox <- matrix(c(-180,180,-90,90), nrow = 2, ncol = 2, byrow = TRUE,
  dimnames = list(c("x", "y"), c("min","max")))
filter <- OGCFilter$new( BBOX$new(bbox = bbox) )
cons <- CSWConstraint$new(filter = filter)
query <- CSWQuery$new(elementSetName = "brief", constraint = cons)

```

CSWRecordProperty

CSWRecordProperty

Description

CSWRecordProperty

CSWRecordProperty

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an CSW RecordProperty

Super class

`ows4R::OGCAbstractObject` -> CSWRecordProperty

Public fields

`wrap` internal property for XML encoding

`Name` name property for request XML encoding

`Value` property for request XML encoding

Methods**Public methods:**

- `CSWRecordProperty$new()`
- `CSWRecordProperty$clone()`

Method `new()`: Initializes an object of class `CSWRecordProperty`

Usage:

```
CSWRecordProperty$new(name, value, cswVersion = "2.0.2")
```

Arguments:

`name` name

`value` value

`cswVersion` CSW service version. Default is "2.0.2"

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CSWRecordProperty$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
rp <- CSWRecordProperty$new(name = "NAME", value = "VALUE")
rp_xml <- rp$encode() #see how it looks in XML
```

CSWTransaction	<i>CSWTransaction</i>
----------------	-----------------------

Description

CSWTransaction

CSWTransaction

Format[R6Class](#) object.**Value**Object of [R6Class](#) for modelling a CSW Transaction request**Super classes**[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> CSWTransaction**Methods****Public methods:**

- [CSWTransaction\\$new\(\)](#)
- [CSWTransaction\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [CSWTransaction](#) service request*Usage:*

```
CSWTransaction$new(  
  capabilities,  
  op,  
  url,  
  serviceVersion,  
  type,  
  user = NULL,  
  pwd = NULL,  
  token = NULL,  
  headers = list(),  
  record = NULL,  
  recordProperty = NULL,  
  constraint = NULL,  
  logger = NULL,  
  ...  
)
```

*Arguments:*capabilities an object of class [CSWCapabilities](#)

op object of class [OWSOperation](#) as retrieved from capabilities
 url url
 serviceVersion serviceVersion. Default is "2.0.2"
 type type of transaction, either "Insert", "Update", or "Delete"
 user user
 pwd password
 token token
 headers headers
 record record
 recordProperty record property
 constraint constraint
 logger logger
 . . . any parameter to pass to the service request

Method clone(): The objects of this class are cloneable with this method.

Usage:

CSWTransaction\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a CSW Transaction request

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

getOWSNamespace

getOWSNamespace

Description

getOWSNamespace gets a namespace given its id

Usage

getOWSNamespace(id)

Arguments

id namespace prefix

Author(s)

Emmanuel Blondel, <emmanuel.blondel1@gmail.com>

Examples

```
getOWSNamespace("GMD")
```

getOWSNamespace	<i>getOWSNamespace</i>
-----------------	------------------------

Description

getOWSNamespace gets the list of namespaces registered

Usage

```
getOWSNamespace()
```

Author(s)

Emmanuel Blondel, <emmanuel.blondel1@gmail.com>

Examples

```
getOWSNamespace()
```

Not	<i>Not</i>
-----	------------

Description

Not
Not

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an Not

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OGCExpression](#) -> [ows4R::UnaryLogicOpType](#) -> Not

Methods**Public methods:**

- [Not\\$new\(\)](#)
- [Not\\$clone\(\)](#)

Method `new()`: Initializes an [Not](#) expression

Usage:

`Not$new(...)`

Arguments:

... list of objects of class [OGCExpression](#)

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`Not$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
expr <- PropertyIsEqualTo$new(PropertyName = "property", Literal = "value")
not <- Not$new(expr)
not_xml <- not$encode() #see how it looks like in XML
```

OGCAbstractObject

OGCAbstractObject

Description

OGCAbstractObject

OGCAbstractObject

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGCAbstractObject

Public fields

verbose.info logical property to indicate whether INFO logs have to be displayed
verbose.debug logical property to indicate whether DEBUG logs have to be displayed
loggerType logger type, either NULL, "INFO", or "DEBUG"
wrap internal property for XML encoding
element element used for XML encoding
namespace namespace used for XML encoding
defaults default values to be used for XML encoding
attrs attributes to be used for XML encoding

Methods**Public methods:**

- [OGCAbstractObject\\$logger\(\)](#)
- [OGCAbstractObject\\$INFO\(\)](#)
- [OGCAbstractObject\\$WARN\(\)](#)
- [OGCAbstractObject\\$ERROR\(\)](#)
- [OGCAbstractObject\\$new\(\)](#)
- [OGCAbstractObject\\$getClassname\(\)](#)
- [OGCAbstractObject\\$getClass\(\)](#)
- [OGCAbstractObject\\$isFieldInheritedFrom\(\)](#)
- [OGCAbstractObject\\$getNamespaceDefinition\(\)](#)
- [OGCAbstractObject\\$encode\(\)](#)
- [OGCAbstractObject\\$print\(\)](#)
- [OGCAbstractObject\\$clone\(\)](#)

Method `logger()`: A basic logger function

Usage:

`OGCAbstractObject$logger(type, text)`

Arguments:

type type of logs message.
text log message text to be displayed

Method `INFO()`: a basic INFO logger function

Usage:

`OGCAbstractObject$INFO(text)`

Arguments:

text log message text to be displayed

Method `WARN()`: a basic WARN logger function

Usage:

`OGCAbstractObject$WARN(text)`

Arguments:

text log message text to be displayed

Method ERROR(): a basic ERROR logger function

Usage:

```
OGCAbstractObject$ERROR(text)
```

Arguments:

text log message text to be displayed

Method new(): Initializes an object extending [OGCAbstractObject](#)

Usage:

```
OGCAbstractObject$new(
  xml = NULL,
  element = NULL,
  namespacePrefix = NULL,
  attrs = list(),
  defaults = list(),
  wrap = FALSE,
  logger = NULL
)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from [XML](#)

element element name

namespacePrefix namespace prefix for XML encoding

attrs list of attributes

defaults list of default values

wrap whether XML element has to be wrapped during XML encoding

logger logger

Method getClassName(): Get class name

Usage:

```
OGCAbstractObject$getClassName()
```

Returns: an object of class character

Method getClass(): Get class

Usage:

```
OGCAbstractObject$getClass()
```

Returns: an object of class R6Class

Method isFieldInheritedFrom(): Utility to return the parent class in which field is defined

Usage:

```
OGCAbstractObject$isFieldInheritedFrom(field)
```

Arguments:

field field name

Returns: object of class R6Class

Method getNamespaceDefinition(): Gets the namespace definition

Usage:

```
OGCAbstractObject$getNamespaceDefinition(recursive = FALSE)
```

Arguments:

recursive Get all namespace recursively

Returns: the namespace definitions as named list

Method encode(): Encodes as XML. The addNS . Extra parameters related to **geometa** objects: geometa_validate (TRUE by default) and geometa_inspire (FALSE by default) can be used to perform ISO and INSPIRE validation respectively. In that case on object of class geometa::INSPIREMetadataValidator, with a proper user API key, should be specified as geometa_inspireValidator argument.

Usage:

```
OGCAbstractObject$encode(
  addNS = TRUE,
  geometa_validate = TRUE,
  geometa_inspire = FALSE,
  geometa_inspireValidator = NULL
)
```

Arguments:

addNS addNS controls the addition of XML namespaces

geometa_validate Relates to **geometa** object ISO validation. Default is TRUE

geometa_inspire Relates to **geometa** object INSPIRE validation. Default is FALSE

geometa_inspireValidator Relates to **geometa** object INSPIRE validation. Default is NULL

Returns: an object of class [XMLInternalNode-class](#) from **XML**

Method print(): Provides a custom print output (as tree) of the current class

Usage:

```
OGCAbstractObject$print(..., depth = 1)
```

Arguments:

... args

depth class nesting depth

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
OGCAbstractObject$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

abstract class used by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

OGCEXpression

OGCEXpression

Description

OGCEXpression

OGCEXpression

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGC Expression

Super class

[ows4R::OGCAbstractObject](#) -> OGCEXpression

Methods**Public methods:**

- [OGCEXpression\\$new\(\)](#)
- [OGCEXpression\\$setExprVersion\(\)](#)
- [OGCEXpression\\$getExprVersion\(\)](#)
- [OGCEXpression\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [OGCEXpression](#)

Usage:

```
OGCEXpression$new(
  element,
  namespacePrefix,
  attrs = NULL,
  defaults = NULL,
  exprVersion = "1.1.0"
)
```

Arguments:

element element name
 namespacePrefix XML namespace prefix
 attrs attributes
 defaults default values

exprVersion OGC version for the expression

Method setExprVersion(): Sets expression version. The methods will control proper XML namespace prefix setting

Usage:

OGCExpression\$setExprVersion(exprVersion)

Arguments:

exprVersion OGC expression version

Method getExprVersion(): Gets expression version

Usage:

OGCExpression\$getExprVersion()

Returns: object of class character

Method clone(): The objects of this class are cloneable with this method.

Usage:

OGCExpression\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

abstract class

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

OGCFilter

OGCFilter

Description

OGCFilter

OGCFilter

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGC Filter

Super class

`ows4R::OGCAbstractObject` -> OGCFilter

Public fields

`expr` OGC expression

Methods**Public methods:**

- `OGCFilter$new()`
- `OGCFilter$setFilterVersion()`
- `OGCFilter$clone()`

Method `new()`: Initializes an object of class `OGCFilter`.

Usage:

```
OGCFilter$new(expr, filterVersion = "1.1.0")
```

Arguments:

`expr` object of class `OGCExpression`

`filterVersion` OGC filter version. Default is "1.1.0"

Method `setFilterVersion()`: Sets the OGC filter version

Usage:

```
OGCFilter$setFilterVersion(filterVersion)
```

Arguments:

`filterVersion` OGC filter version

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
OGCFilter$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
expr <- PropertyIsEqualTo$new(PropertyName = "property", Literal = "value")
not <- Not$new(expr)
not_xml <- not$encode() #see how it looks like in XML
```

Or

Or

Description

Or

Or

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an Or operator

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OGCExpression](#) -> [ows4R::BinaryLogicOpType](#) -> Or

Methods

Public methods:

- [Or\\$new\(\)](#)
- [Or\\$clone\(\)](#)

Method `new()`: Initializes an [Or](#) expression

Usage:

`Or$new(...)`

Arguments:

... list of objects of class [OGCExpression](#)

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`Or$clone(deep = FALSE)`

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
expr1 <- PropertyIsEqualTo$new(PropertyName = "property1", Literal = "value1")
expr2 <- PropertyIsEqualTo$new(PropertyName = "property2", Literal = "value2")
or <- Or$new(expr1,expr2)
or_xml <- or$encode() #see how it looks like in XML
```

ows4R

Interface to OGC Web-Services

Description

Provides an Interface to Web-Services defined as standards by the Open Geospatial Consortium (OGC), including Web Feature Service (WFS) for vector data, Web Coverage Service (WCS), Catalogue Service (CSW) for ISO/OGC metadata, and associated standards such as the common web-service specification (OWS) and OGC Filter Encoding. Partial support is provided for the Web Map Service (WMS) and Web Processing Service (WPS). The purpose is to add support for additional OGC service standards such as Web Coverage Processing Service (WCPS) or OGC API.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

See Also

Useful links:

- <https://github.com/eblondel/ows4R>
- <https://eblondel.github.io/ows4R/>
- <https://www.ogc.org/standards/>
- Report bugs at <https://github.com/eblondel/ows4R/issues>

OWSBoundingBox

OWSBoundingBox

Description

OWSBoundingBox

OWSBoundingBox

Format

R6Class object.

Value

Object of [R6Class](#) for modelling an OGC Bounding Box

Super class

[ows4R: :OGCAbstractObject](#) -> OWSBoundingBox

Public fields

attrs attributes to be associated to XML

LowerCorner lower corner coordinates

UpperCorner upper corner coordinates

Methods**Public methods:**

- [OWSBoundingBox\\$new\(\)](#)
- [OWSBoundingBox\\$decode\(\)](#)
- [OWSBoundingBox\\$getBBOX\(\)](#)
- [OWSBoundingBox\\$clone\(\)](#)

Method new(): Initializes an object of class [OWSBoundingBox](#)

Usage:

```
OWSBoundingBox$new(  
  xml = NULL,  
  element = NULL,  
  namespacePrefix = NULL,  
  owsVersion,  
  serviceVersion,  
  logger = NULL  
)
```

Arguments:

xml an object of class [XMLInternalNode-class](#) to initialize from XML

element element name

namespacePrefix namespace prefix

owsVersion OWS version

serviceVersion service version

logger logger

Method decode(): Decodes an object of class [OWSBoundingBox](#) from XML

Usage:

```
OWSBoundingBox$decode(xml)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from XML

Method `getBBOX()`: Get BBOX as object of class `bbox` from `sf` package

Usage:

```
OWSBoundingBox$getBBOX()
```

Returns: a numeric vector of length four, with `xmin`, `ymin`, `xmax` and `ymax` values

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
OWSBoundingBox$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

OWSCapabilities

OWSGetCapabilities

Description

OWSGetCapabilities

OWSGetCapabilities

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing an abstract OWS Get Capabilities document.

Super class

[ows4R::OGCAbstractObject](#) -> OWSCapabilities

Methods

Public methods:

- [OWSCapabilities\\$new\(\)](#)
- [OWSCapabilities\\$setClient\(\)](#)
- [OWSCapabilities\\$getClient\(\)](#)
- [OWSCapabilities\\$getUrl\(\)](#)
- [OWSCapabilities\\$getService\(\)](#)
- [OWSCapabilities\\$getServiceVersion\(\)](#)
- [OWSCapabilities\\$getOWSVersion\(\)](#)

- [OWSCapabilities\\$getRequest\(\)](#)
- [OWSCapabilities\\$getServiceIdentification\(\)](#)
- [OWSCapabilities\\$getServiceProvider\(\)](#)
- [OWSCapabilities\\$getOperationsMetadata\(\)](#)
- [OWSCapabilities\\$clone\(\)](#)

Method new(): Initializes a [OWSCapabilities](#) object

Usage:

```
OWSCapabilities$new(
  element = NULL,
  namespacePrefix = NULL,
  url,
  service,
  owsVersion,
  serviceVersion,
  logger = NULL,
  ...
)
```

Arguments:

element element

namespacePrefix namespace prefix

url url

service service

owsVersion OWS version

serviceVersion service version

logger logger type NULL, "INFO" or "DEBUG"

... any other parameter to pass to [OWSGetCapabilities](#) service request

Method setClient(): Sets the OGC client

Usage:

```
OWSCapabilities$setClient(client)
```

Arguments:

client an object extending [OWSClient](#)

Method getClient(): Get client

Usage:

```
OWSCapabilities$getClient()
```

Arguments:

an object extending [OWSClient](#)

Method getUrl(): Get URL

Usage:

```
OWSCapabilities$getUrl()
```

Returns: an object of class character

Method getService(): Get service

Usage:

OWSCapabilities\$getService()

Returns: an object of class character

Method getServiceVersion(): Get service version

Usage:

OWSCapabilities\$getServiceVersion()

Returns: an object of class character

Method getOWSVersion(): Get OWS version

Usage:

OWSCapabilities\$getOWSVersion()

Returns: an object of class character

Method getRequest(): Get request

Usage:

OWSCapabilities\$getRequest()

Returns: an object of class [OWSGetCapabilities](#)

Method getServiceIdentification(): Get service identification

Usage:

OWSCapabilities\$getServiceIdentification()

Returns: an object of class [OWSServiceIdentification](#)

Method getServiceProvider(): Get service provider

Usage:

OWSCapabilities\$getServiceProvider()

Returns: an object of class [OWSServiceProvider](#)

Method getOperationsMetadata(): Get service operations metadata

Usage:

OWSCapabilities\$getOperationsMetadata()

Returns: an object of class [OWSOperationsMetadata](#)

Method clone(): The objects of this class are cloneable with this method.

Usage:

OWSCapabilities\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

abstract class used by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

OWSClient

OWSClient

Description

OWSClient

OWSClient

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing a Common OGC web-service.

Super class

[ows4R: :OGCAbstractObject](#) -> OWSClient

Public fields

url Base url of the OWS service

version version of the OWS service

capabilities object giving the OWS service capabilities

Methods

Public methods:

- [OWSClient\\$new\(\)](#)
- [OWSClient\\$getUrl\(\)](#)
- [OWSClient\\$getVersion\(\)](#)
- [OWSClient\\$getCapabilities\(\)](#)
- [OWSClient\\$getUser\(\)](#)
- [OWSClient\\$getPwd\(\)](#)
- [OWSClient\\$getToken\(\)](#)
- [OWSClient\\$getHeaders\(\)](#)
- [OWSClient\\$getConfig\(\)](#)
- [OWSClient\\$getCASUrl\(\)](#)
- [OWSClient\\$clone\(\)](#)

Method new(): This method is used to instantiate a OWSClient with the url of the OGC service. Authentication is supported using basic auth (using user/pwd arguments), bearer token (using token argument), or custom (using headers argument). By default, the logger argument will be set to NULL (no logger). This argument accepts two possible values: INFO: to print only **ows4R** logs, DEBUG: to print more verbose logs

Usage:

```
OWSClient$new(  
  url,  
  service,  
  serviceVersion,  
  user = NULL,  
  pwd = NULL,  
  token = NULL,  
  headers = c(),  
  config = httr::config(),  
  cas_url = NULL,  
  logger = NULL  
)
```

Arguments:

url url
service service name
serviceVersion CSW service version
user user
pwd password
token token
headers headers
config config
cas_url Central Authentication Service (CAS) URL
logger logger

Method getUrl(): Get URL*Usage:*

```
OWSClient$getUrl()
```

Returns: the url of the service, object of class character

Method getVersion(): Get version*Usage:*

```
OWSClient$getVersion()
```

Returns: the version of the service, object of class character

Method getCapabilities(): Get capabilities*Usage:*

```
OWSClient$getCapabilities()
```

Returns: the capabilities, object of class [OWSCapabilities](#)

Method getUser(): Get user*Usage:*

```
OWSClient$getUser()
```

Returns: the user, object of class character

Method getPwd(): Get password

Usage:

OWSClient\$getPwd()

Returns: the password, object of class character

Method getToken(): Get token

Usage:

OWSClient\$getToken()

Returns: the token, object of class character

Method getHeaders(): Get headers

Usage:

OWSClient\$getHeaders()

Returns: the headers, object of class character

Method getConfig(): Get **httr** config

Usage:

OWSClient\$config()

Returns: the **httr** config, if any

Method getCASUrl(): Get CAS URL

Usage:

OWSClient\$CASUrl()

Returns: a CAS URL

Method clone(): The objects of this class are cloneable with this method.

Usage:

OWSClient\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

OWSCodeType

OWSCodeType

Description

OWSCodeType

OWSCodeType

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OWS CodeType

Super class

[ows4R: :OGCAbstractObject](#) -> OWSCodeType

Public fields

value code type

Methods

Public methods:

- [OWSCodeType\\$new\(\)](#)
- [OWSCodeType\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [OWSCodeType](#)

Usage:

```
OWSCodeType$new(xml = NULL, owsVersion = "1.1", value)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**

owsVersion OWS version. Default is "1.1"

value the code type

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
OWSCodeType$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

OWSEException

OWSEException

Description

OWSEException

OWSEException

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a OWS Service exception

Super class

[ows4R:OGCAbstractObject](#) -> OWSEException

Public fields

ExceptionText exception text

Methods

Public methods:

- [OWSEException\\$new\(\)](#)
- [OWSEException\\$getLocator\(\)](#)
- [OWSEException\\$getCode\(\)](#)
- [OWSEException\\$getText\(\)](#)
- [OWSEException\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [OWSEException](#)

Usage:

[OWSEException\\$new\(xmlObj, logger = NULL\)](#)

Arguments:

xmlObj object of class [XMLInternalNode-class](#) from **XML**

logger logger

Method [getLocator\(\)](#): Get exception locator

Usage:

[OWSEException\\$getLocator\(\)](#)

Returns: the exception locator, object of class character

Method getCode(): Get exception code

Usage:

OWSException\$getCode()

Returns: the exception code, object of class character

Method getText(): Get exception text explanation

Usage:

OWSException\$getText()

Returns: the exception text, object of class character

Method clone(): The objects of this class are cloneable with this method.

Usage:

OWSException\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

OWSGetCapabilities *OWSGetCapabilities*

Description

OWSGetCapabilities

OWSGetCapabilities

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a GetCapabilities request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> OWSGetCapabilities

Methods**Public methods:**

- [OWSGetCapabilities\\$new\(\)](#)
- [OWSGetCapabilities\\$clone\(\)](#)

Method `new()`: Initializes an [OWSGetCapabilities](#) service request

Usage:

```
OWSGetCapabilities$new(  
  element = NULL,  
  namespacePrefix = NULL,  
  url,  
  service,  
  version,  
  user = NULL,  
  pwd = NULL,  
  token = NULL,  
  headers = c(),  
  config = httr::config(),  
  ...  
)
```

Arguments:

element element
namespacePrefix namespace prefix
url url
service service name
version service version
user user
pwd password
token token
headers headers
config config
... any other parameter to pass to the request

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
OWSGetCapabilities$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a OWS GetCapabilities request

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

OWSHttpRequest

OWSHttpRequest

Description

OWSHttpRequest

OWSHttpRequest

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a generic OWS http request

Super class

[ows4R::OGCAbstractObject](#) -> OWSHttpRequest

Methods

Public methods:

- [OWSHttpRequest\\$new\(\)](#)
- [OWSHttpRequest\\$execute\(\)](#)
- [OWSHttpRequest\\$getCapabilities\(\)](#)
- [OWSHttpRequest\\$getRequest\(\)](#)
- [OWSHttpRequest\\$getRequestHeaders\(\)](#)
- [OWSHttpRequest\\$status\(\)](#)
- [OWSHttpRequest\\$response\(\)](#)
- [OWSHttpRequest\\$exception\(\)](#)
- [OWSHttpRequest\\$hasException\(\)](#)
- [OWSHttpRequest\\$result\(\)](#)
- [OWSHttpRequest\\$setResult\(\)](#)
- [OWSHttpRequest\\$clone\(\)](#)

Method new(): Initializes an OWS HTTP request

Usage:

```
OWSHttpRequest$new(  
  element,  
  namespacePrefix,  
  capabilities,  
  op,  
  type,  
  url,
```

```

    request,
    user = NULL,
    pwd = NULL,
    token = NULL,
    headers = c(),
    config = httr::config(),
    namedParams = NULL,
    attrs = NULL,
    contentType = "text/xml",
    mimeType = "text/xml",
    skipXmlComments = TRUE,
    logger = NULL,
    ...
)

```

Arguments:

element element
 namespacePrefix namespace prefix
 capabilities object of class or extending [OWSCapabilities](#)
 op object of class [OWSOperation](#)
 type type of request, eg. GET, POST
 url url
 request request name
 user user
 pwd password
 token token
 headers headers
 config config
 namedParams a named list
 attrs attributes
 contentType content type. Default value is "text/xml"
 mimeType mime type. Default value is "text/xml"
 skipXmlComments Skip XML comments from response
 logger logger
 ... any other parameter

Method `execute()`: Executes the request

Usage:

```
OWSHttpRequest$execute()
```

Method `getCapabilities()`: Get capabilities

Usage:

```
OWSHttpRequest$getCapabilities()
```

Returns: an object of class or extending [OWSCapabilities](#)

Method `getRequest()`: Get request

Usage:

`OWSHttpRequest$request()`

Returns: the request

Method `getRequestHeaders():` Get request headers

Usage:

`OWSHttpRequest$requestHeaders()`

Returns: the request headers

Method `getStatus():` get status code

Usage:

`OWSHttpRequest$status()`

Returns: the request status code

Method `getResponse():` get request response

Usage:

`OWSHttpRequest$response()`

Returns: the request response

Method `getException():` get request exception

Usage:

`OWSHttpRequest$exception()`

Returns: the request exception

Method `hasException():` Indicates if it has an exception

Usage:

`OWSHttpRequest$hasException()`

Returns: TRUE if it has an exception, FALSE otherwise

Method `getResult():` Get the result TRUE if the request is successful, FALSE otherwise

Usage:

`OWSHttpRequest$result()`

Returns: the result, object of class logical

Method `setResult():` Set the result

Usage:

`OWSHttpRequest$result(result)`

Arguments:

result object of class logical

Method `clone():` The objects of this class are cloneable with this method.

Usage:

`OWSHttpRequest$clone(deep = FALSE)`

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

OWSNamespace

OWSNamespace

Description

OWSNamespace

OWSNamespace

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OWS Namespace

Public fields

id namespace id

uri namespace uri

Methods**Public methods:**

- [OWSNamespace\\$new\(\)](#)
- [OWSNamespace\\$getDefinition\(\)](#)
- [OWSNamespace\\$clone\(\)](#)

Method [new\(\)](#): Initializes an [OWSNamespace](#)

Usage:

[OWSNamespace\\$new](#)(id, uri)

Arguments:

id id

uri uri

Method [getDefinition\(\)](#): Get namespace definition

Usage:

[OWSNamespace\\$getDefinition](#)()

Returns: a named list with id and uri

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
OWSNamespace$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

class used internally by ows4R for specifying XML namespaces

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

OWSOperation

OWSOperation

Description

OWSOperation

OWSOperation

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGC Operation

Methods

Public methods:

- [OWSOperation\\$new\(\)](#)
- [OWSOperation\\$getName\(\)](#)
- [OWSOperation\\$getParameters\(\)](#)
- [OWSOperation\\$getParameter\(\)](#)
- [OWSOperation\\$clone\(\)](#)

Method `new()`: Initializes an object of class [OWSOperation](#).

Usage:

```
OWSOperation$new(xmlObj, owsVersion, serviceVersion)
```

Arguments:

xmlObj object of class [XMLInternalNode-class](#) from **XML**
owsVersion OWS version
serviceVersion service version

Method getName(): Get operation name

Usage:

OWSOperation\$getName()

Returns: an object of class character

Method getParameters(): Get parameters

Usage:

OWSOperation\$getParameters()

Returns: the parameters

Method getParameter(): Get parameter

Usage:

OWSOperation\$getParameter(name)

Arguments:

name name

Returns: the parameter

Method clone(): The objects of this class are cloneable with this method.

Usage:

OWSOperation\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Internal class used internally by **ows4R** when reading capabilities documents

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

OWSOperationsMetadata *OWSOperationsMetadata*

Description

OWSOperationsMetadata

OWSOperationsMetadata

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGC Operations Metadata

Methods

Public methods:

- [OWSOperationsMetadata\\$new\(\)](#)
- [OWSOperationsMetadata\\$getOperations\(\)](#)
- [OWSOperationsMetadata\\$clone\(\)](#)

Method [new\(\)](#): Initializes an [OWSOperationsMetadata](#) object

Usage:

```
OWSOperationsMetadata$new(xmlObj, owsVersion, serviceVersion)
```

Arguments:

xmlObj object of class [XMLInternalNode-class](#) from **XML**

owsVersion OWS version

serviceVersion service version

Method [getOperations\(\)](#): Get operations

Usage:

```
OWSOperationsMetadata$getOperations()
```

Returns: a list of [OWSOperation](#)

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
OWSOperationsMetadata$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

OWSRequest

OWSRequest

Description

OWSRequest

OWSRequest

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a OWS Service Capability Request

Super class

[ows4R: :OGCAbstractObject](#) -> OWSRequest

Methods**Public methods:**

- [OWSRequest\\$new\(\)](#)
- [OWSRequest\\$getName\(\)](#)
- [OWSRequest\\$getFormats\(\)](#)
- [OWSRequest\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [OWSRequest](#)

Usage:

[OWSRequest\\$new\(xmlObj, capabilities, version, logger = NULL\)](#)

Arguments:

[xmlObj](#) object of class [XMLInternalNode-class](#) from **XML**
[capabilities](#) an object of class or extending [OWSCapabilities](#)
[version](#) version
[logger](#) logger

Method [getName\(\)](#): Get request name

Usage:

[OWSRequest\\$getName\(\)](#)

Returns: the name, object of class character

Method getFormats(): Get request formats

Usage:

OWSRequest\$getFormats()

Returns: the formats, object (vector) of class character

Method clone(): The objects of this class are cloneable with this method.

Usage:

OWSRequest\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

OWSServiceIdentification

OWSServiceIdentification

Description

OWSServiceIdentification

OWSServiceIdentification

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGC Service Identification

Methods

Public methods:

- [OWSServiceIdentification\\$new\(\)](#)
- [OWSServiceIdentification\\$name\(\)](#)
- [OWSServiceIdentification\\$title\(\)](#)
- [OWSServiceIdentification\\$abstract\(\)](#)
- [OWSServiceIdentification\\$keywords\(\)](#)
- [OWSServiceIdentification\\$onlineResource\(\)](#)

- [OWSServiceIdentification\\$getServiceType\(\)](#)
- [OWSServiceIdentification\\$getServiceTypeVersion\(\)](#)
- [OWSServiceIdentification\\$getFees\(\)](#)
- [OWSServiceIdentification\\$getAccessConstraints\(\)](#)
- [OWSServiceIdentification\\$clone\(\)](#)

Method new(): Initializes an object of class [OWSServiceIdentification](#)

Usage:

```
OWSServiceIdentification$new(xmlObj, owsVersion, serviceVersion)
```

Arguments:

xmlObj object of class [XMLInternalNode-class](#) from **XML**

owsVersion OWS version

serviceVersion service version

Method getName(): Get service identification - name

Usage:

```
OWSServiceIdentification$getName()
```

Returns: the name, object of class character

Method getTitle(): Get service identification - title

Usage:

```
OWSServiceIdentification$title()
```

Returns: the title, object of class character

Method getAbstract(): Get service identification - abstract

Usage:

```
OWSServiceIdentification$getAbstract()
```

Returns: the abstract, object of class character

Method getKeywords(): Get service identification - keywords

Usage:

```
OWSServiceIdentification$getKeywords()
```

Returns: the keywords, object of class character

Method getOnlineResource(): Get service identification - online resource

Usage:

```
OWSServiceIdentification$getOnlineResource()
```

Returns: the online resource, object of class character

Method getServiceType(): Get service identification - service type

Usage:

```
OWSServiceIdentification$getServiceType()
```

Returns: the service type, object of class character

Method getServiceTypeVersion(): Get service identification - service type version

Usage:

OWSServiceIdentification\$getServiceTypeVersion()

Returns: the service type version, object of class character

Method getFees(): Get service identification - fees

Usage:

OWSServiceIdentification\$getFees()

Returns: the fees, object of class character

Method getAccessConstraints(): Get service identification - access constraints

Usage:

OWSServiceIdentification\$getAccessConstraints()

Returns: the access constraints, object of class character

Method clone(): The objects of this class are cloneable with this method.

Usage:

OWSServiceIdentification\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

OWSServiceProvider *OWSServiceProvider*

Description

OWSServiceProvider

OWSServiceProvider

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGC Service Provider

Methods**Public methods:**

- [OWSServiceProvider\\$new\(\)](#)
- [OWSServiceProvider\\$getProviderName\(\)](#)
- [OWSServiceProvider\\$getProviderSite\(\)](#)
- [OWSServiceProvider\\$getServiceContact\(\)](#)
- [OWSServiceProvider\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [OWSServiceProvider](#)

Usage:

`OWSServiceProvider$new(xmlObj, owsVersion, serviceVersion)`

Arguments:

`xmlObj` object of class [XMLInternalNode-class](#) from **XML**

`owsVersion` OWS version

`serviceVersion` service version

Method [getProviderName\(\)](#): Get provider name

Usage:

`OWSServiceProvider$getProviderName()`

Arguments:

the provider name, object of class character

Method [getProviderSite\(\)](#): Get provider site

Usage:

`OWSServiceProvider$getProviderSite()`

Arguments:

the provider site, object of class character

Method [getServiceContact\(\)](#): Get provider contact

Usage:

`OWSServiceProvider$getServiceContact()`

Arguments:

the provider contact, object of class [ISOResponsibleParty](#) from **geometa**

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

`OWSServiceProvider$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Note

Abstract class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

OWSUtils

OWSUtils

Description

OWSUtils

Usage

OWSUtils

Format

[R6Class](#) object.

Value

set of OWS Utilities

Static methods

`getNamespaces()` Get the namespaces associated to a given XML object
`findNamespace(namespaces, id, uri)` Finds a namespace by id or by URI
`toBBOX(xmin, xmax, ymin, ymax)` Creates a bbox matrix from min/max x/y coordinates
`findP4s(srsName, morphToESRI)` Finds the PROJ4 string definition for a given srsName
`toCRS(srsName)` Converts a srsName into a CRS object
`toEPSG(crs)` Get the EPSG code from a CRS object
`getAspectRatio(bbox)` Get the aspect ratio for a given bbox

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
#toBBOX
bbox <- OWSUtils$toBBOX(-180,-90,180,90)

#toCRS
crs <- OWSUtils$toCRS("EPSG:4326")
```

OWSWG84BoundingBox *OWSWG84BoundingBox*

Description

OWSWG84BoundingBox

OWSWG84BoundingBox

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGC WS84 BoundingBox

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSBoundingBox](#) -> OWSWG84BoundingBox

Methods

Public methods:

- [OWSWG84BoundingBox\\$new\(\)](#)
- [OWSWG84BoundingBox\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [OWSBoundingBox](#)

Usage:

```
OWSWG84BoundingBox$new(xml = NULL, owsVersion, serviceVersion, logger = NULL)
```

Arguments:

xml an object of class [XMLInternalNode-class](#) to initialize from XML

owsVersion OWS version

serviceVersion service version

logger logger

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
OWSWG84BoundingBox$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **geometa**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

PropertyIsBetween *PropertyIsBetween*

Description

PropertyIsBetween

PropertyIsBetween

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an PropertyIsBetween

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OGCEXpression](#) -> PropertyIsBetween

Public fields

PropertyName property name field for XML encoding

lower lower value

upper upper value

Methods**Public methods:**

- [PropertyIsBetween\\$new\(\)](#)
- [PropertyIsBetween\\$clone\(\)](#)

Method `new()`: Initializes an object extending [PropertyIsLike](#)

Usage:

`PropertyIsBetween$new(PropertyName, lower, upper)`

Arguments:

PropertyName property name

lower lower value

upper upper value

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`PropertyIsBetween$clone(deep = FALSE)`

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
expr <- PropertyIsBetween$new(PropertyName = "property", lower = 1, upper = 10)
expr_xml <- expr$encode() #see how it looks like in XML
```

PropertyIsEqualTo	PropertyIsEqualTo
-------------------	-------------------

Description

PropertyIsEqualTo

PropertyIsEqualTo

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an PropertyIsEqualTo

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OGCEXpression](#) -> [ows4R::BinaryComparisonOpType](#)
-> PropertyIsEqualTo

Methods**Public methods:**

- [PropertyIsEqualTo\\$new\(\)](#)
- [PropertyIsEqualTo\\$clone\(\)](#)

Method `new()`: Initializes an object extending [PropertyIsEqualTo](#)

Usage:

```
PropertyIsEqualTo$new(PropertyName, Literal, matchCase = NA)
```

Arguments:

PropertyName property name

Literal literal

matchCase match case

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PropertyIsEqualTo$new(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
expr <- PropertyIsEqualTo$new(PropertyName = "property", Literal = "value")
expr_xml <- expr$encode() #see how it looks like in XML
```

PropertyIsGreaterThan *PropertyIsGreaterThan*

Description

PropertyIsGreaterThan

PropertyIsGreaterThan

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an PropertyIsGreaterThan

Super classes

```
ows4R::OGCAbstractObject -> ows4R::OGCExpression -> ows4R::BinaryComparisonOpType
-> PropertyIsGreaterThan
```

Methods**Public methods:**

- [PropertyIsGreaterThan\\$new\(\)](#)
- [PropertyIsGreaterThan\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object extending [PropertyIsGreaterThan](#)

Usage:

```
PropertyIsGreaterThan$new(PropertyName, Literal, matchCase = NA)
```

Arguments:

PropertyName property name
 Literal literal
 matchCase match case

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PropertyIsGreaterThanOrEqualTo$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
expr <- PropertyIsGreaterThanOrEqualTo$new(PropertyName = "property", Literal = "value")
expr_xml <- expr$encode() #see how it looks like in XML
```

PropertyIsGreaterThanOrEqualTo
PropertyIsGreaterThanOrEqualTo

Description

PropertyIsGreaterThanOrEqualTo
 PropertyIsGreaterThanOrEqualTo

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an PropertyIsGreaterThanOrEqualTo

Super classes

```
ows4R::OGCAbstractObject -> ows4R::OGCExpression -> ows4R::BinaryComparisonOpType
-> PropertyIsGreaterThanOrEqualTo
```

Methods**Public methods:**

- [PropertyIsGreaterThanOrEqualTo\\$new\(\)](#)
- [PropertyIsGreaterThanOrEqualTo\\$clone\(\)](#)

Method `new()`: Initializes an object extending [PropertyIsGreaterThanOrEqualTo](#)

Usage:

```
PropertyIsGreaterThanOrEqualTo$new(PropertyName, Literal, matchCase = NA)
```

Arguments:

PropertyName property name

Literal literal

matchCase match case

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PropertyIsGreaterThanOrEqualTo$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
expr <- PropertyIsGreaterThanOrEqualTo$new(PropertyName = "property", Literal = "value")
expr_xml <- expr$encode() #see how it looks like in XML
```

PropertyIsLessThan *PropertyIsLessThan*

Description

PropertyIsLessThan

PropertyIsLessThan

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an PropertyIsLessThan

Super classes

```
ows4R::OGCAbstractObject -> ows4R::OGCEXpression -> ows4R::BinaryComparisonOpType
-> PropertyIsLessThan
```

Methods**Public methods:**

- [PropertyIsLessThan\\$new\(\)](#)
- [PropertyIsLessThan\\$clone\(\)](#)

Method `new()`: Initializes an object extending [PropertyIsLessThan](#)

Usage:

```
PropertyIsLessThan$new(PropertyName, Literal, matchCase = NA)
```

Arguments:

PropertyName property name

Literal literal

matchCase match case

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PropertyIsLessThan$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
expr <- PropertyIsLessThan$new(PropertyName = "property", Literal = "value")
expr_xml <- expr$encode() #see how it looks like in XML
```

PropertyIsLessThanOrEqualTo

PropertyIsLesserThanOrEqualTo

Description

PropertyIsLesserThanOrEqualTo

PropertyIsLesserThanOrEqualTo

Format

R6Class object.

Value

Object of R6Class for modelling an PropertyIsLessThanOrEqualTo

Super classes

ows4R::OGCAbstractObject -> ows4R::OGCEXpression -> ows4R::BinaryComparisonOpType
-> PropertyIsLessThanOrEqualTo

Methods**Public methods:**

- [PropertyIsLessThanOrEqualTo\\$new\(\)](#)
- [PropertyIsLessThanOrEqualTo\\$clone\(\)](#)

Method `new()`: Initializes an object extending [PropertyIsLessThanOrEqualTo](#)

Usage:

```
PropertyIsLessThanOrEqualTo$new(PropertyName, Literal, matchCase = NA)
```

Arguments:

PropertyName property name

Literal literal

matchCase match case

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PropertyIsLessThanOrEqualTo$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
expr <- PropertyIsLessThanOrEqualTo$new(PropertyName = "property", Literal = "value")  
expr_xml <- expr$encode() #see how it looks like in XML
```

PropertyIsLike	<i>PropertyIsLike</i>
----------------	-----------------------

Description

PropertyIsLike

PropertyIsLike

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an PropertyIsLike

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OGCExpression](#) -> PropertyIsLike

Public fields

PropertyName property name field for XML encoding

Literal literal field for XML encoding

attrs attributes for XML encoding

Methods**Public methods:**

- [PropertyIsLike\\$new\(\)](#)
- [PropertyIsLike\\$clone\(\)](#)

Method `new()`: Initializes an object extending [PropertyIsLike](#)

Usage:

```
PropertyIsLike$new(  
  PropertyName,  
  Literal,  
  escapeChar = "\\\"",  
  singleChar = "_",  
  wildCard = "%",  
  matchCase = NA  
)
```

Arguments:

PropertyName property name

Literal literal

escapeChar escape character. Default is "\"
 singleChar single character. Default is "_"
 wildCard wildcard
 matchCase match case

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PropertyIsLike$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
expr <- PropertyIsLike$new(PropertyName = "property", Literal = "value")
expr_xml <- expr$encode() #see how it looks like in XML
```

PropertyIsNotEqualTo *PropertyIsNotEqualTo*

Description

PropertyIsNotEqualTo

PropertyIsNotEqualTo

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an PropertyIsNotEqualTo

Super classes

```
ows4R::OGCAbstractObject -> ows4R::OGCExpression -> ows4R::BinaryComparisonOpType
-> PropertyIsNotEqualTo
```

Methods**Public methods:**

- [PropertyIsNotEqualTo\\$new\(\)](#)
- [PropertyIsNotEqualTo\\$clone\(\)](#)

Method `new()`: Initializes an object extending [PropertyIsNotEqualTo](#)

Usage:

```
PropertyIsNotEqualTo$new(PropertyName, Literal, matchCase = NA)
```

Arguments:

PropertyName property name

Literal literal

matchCase match case

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PropertyIsNotEqualTo$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
expr <- PropertyIsNotEqualTo$new(PropertyName = "property", Literal = "value")
expr_xml <- expr$encode() #see how it looks like in XML
```

PropertyIsNull

PropertyIsNull

Description

PropertyIsNull

PropertyIsNull

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an PropertyIsNull

Super classes

`ows4R::OGCAbstractObject` -> `ows4R::OGCExpression` -> `PropertyIsNull`

Public fields

`PropertyName` property name field for XML encoding

Methods**Public methods:**

- `PropertyIsNull$new()`
- `PropertyIsNull$clone()`

Method `new()`: Initializes an object extending `PropertyIsLike`

Usage:

```
PropertyIsNull$new(PropertyName)
```

Arguments:

`PropertyName` property name

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PropertyIsNull$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
expr <- PropertyIsNull$new(PropertyName = "property")
expr_xml <- expr$encode() #see how it looks like in XML
```

`registerOWSNamespace` *registerOWSNamespace*

Description

`registerOWSNamespace` allows to register a new namespace in **ows4R**

Usage

```
registerOWSNamespace(id, uri, force)
```

Arguments

<code>id</code>	prefix of the namespace
<code>uri</code>	URI of the namespace
<code>force</code>	logical parameter indicating if registration has to be forced in case the identified namespace is already registered

Author(s)

Emmanuel Blondel, <emmanuel.blondel1@gmail.com>

Examples

```
registerOWSNamespace(id = "myprefix", uri = "http://someuri")
```

setOWSNamespace	<i>setOWSNamespace</i>
-----------------	------------------------

Description

setOWSNamespace

Usage

```
setOWSNamespace()
```

UnaryLogicOpType	<i>UnaryLogicOpType</i>
------------------	-------------------------

Description

UnaryLogicOpType

UnaryLogicOpType

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an UnaryLogicOpType

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OGCEXpression](#) -> UnaryLogicOpType

Public fields

operations a list OGC expressions

Methods**Public methods:**

- [UnaryLogicOpType\\$new\(\)](#)
- [UnaryLogicOpType\\$setExprVersion\(\)](#)
- [UnaryLogicOpType\\$clone\(\)](#)

Method `new()`: Initializes a [UnaryLogicOpType](#) expression

Usage:

```
UnaryLogicOpType$new(..., element, namespacePrefix, exprVersion = "1.1.0")
```

Arguments:

... list of objects of class [OGCExpression](#)

element element

namespacePrefix namespacePrefix

exprVersion OGC expression version. Default is "1.1.0"

Method `setExprVersion()`: Sets expression version. The methods will control that expression versions are set for each of the operations specified in the expression.

Usage:

```
UnaryLogicOpType$setExprVersion(exprVersion)
```

Arguments:

exprVersion OGC expression version

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
UnaryLogicOpType$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

abstract super class of all the unary logical operation classes

WCSCapabilities	<i>WCSCapabilities</i>
-----------------	------------------------

Description

WCSCapabilities

WCSCapabilities

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing an OGC Web Coverage Service Get Capabilities document.

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSCapabilities](#) -> WCSCapabilities

Methods

Public methods:

- [WCSCapabilities\\$new\(\)](#)
- [WCSCapabilities\\$getCoverageSummaries\(\)](#)
- [WCSCapabilities\\$findCoverageSummaryById\(\)](#)
- [WCSCapabilities\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WCSCapabilities](#) object

Usage:

```
WCSCapabilities$new(url, version, client = NULL, logger = NULL, ...)
```

Arguments:

url url

version version

client an object of class [WCSCClient](#)

logger logger type NULL, "INFO" or "DEBUG"

... any other parameter to pass to [OWSGetCapabilities](#) service request

Method [getCoverageSummaries\(\)](#): Get coverage summaries

Usage:

```
WCSCapabilities$getCoverageSummaries()
```

Returns: a list of [WCSCoverageSummary](#) objects

Method findCoverageSummaryById(): Finds a coverage by name

Usage:

WCSCapabilities\$findCoverageSummaryById(expr, exact = FALSE)

Arguments:

expr expr

exact exact matching? Default is TRUE

Method clone(): The objects of this class are cloneable with this method.

Usage:

WCSCapabilities\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
## Not run:
  WCSCapabilities$new("http://localhost:8080/geoserver/wcs", serviceVersion = "2.0.1")

## End(Not run)
```

WCSCient

WCSCient

Description

WCSCient

WCSCient

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing an OGC Web Coverage Service.

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSCient](#) -> WCSCient

Methods

Public methods:

- [WCSClient\\$new\(\)](#)
- [WCSClient\\$getCapabilities\(\)](#)
- [WCSClient\\$reloadCapabilities\(\)](#)
- [WCSClient\\$describeCoverage\(\)](#)
- [WCSClient\\$getCoverage\(\)](#)
- [WCSClient\\$clone\(\)](#)

Method `new()`: This method is used to instantiate a [WCSClient](#) with the url of the OGC service. Authentication is supported using basic auth (using user/pwd arguments), bearer token (using token argument), or custom (using headers argument). By default, the logger argument will be set to NULL (no logger). This argument accepts two possible values: INFO: to print only **ows4R** logs, DEBUG: to print more verbose logs

Usage:

```
WCSClient$new(  
  url,  
  serviceVersion = NULL,  
  user = NULL,  
  pwd = NULL,  
  token = NULL,  
  headers = c(),  
  config = httr::config(),  
  cas_url = NULL,  
  logger = NULL  
)
```

Arguments:

```
url url  
serviceVersion WFS service version  
user user  
pwd password  
token token  
headers headers  
config config  
cas_url Central Authentication Service (CAS) URL  
logger logger
```

Method `getCapabilities()`: Get WCS capabilities

Usage:

```
WCSClient$getCapabilities()
```

Returns: an object of class [WCSCapabilities](#)

Method `reloadCapabilities()`: Reloads WCS capabilities

Usage:

WCSClient\$reloadCapabilities()

Method describeCoverage(): Describes coverage

Usage:

```
WCSClient$describeCoverage(identifier)
```

Arguments:

identifier identifier

Returns: an object of class [WCSCoverageDescription](#)

Method getCoverage(): Get coverage

Usage:

```
WCSClient$getCoverage(
  identifier,
  bbox = NULL,
  crs = NULL,
  time = NULL,
  format = NULL,
  rangesubset = NULL,
  gridbaseCRS = NULL,
  gridtype = NULL,
  gridCS = NULL,
  gridorigin = NULL,
  gridoffsets = NULL,
  method = "GET",
  filename = NULL,
  ...
)
```

Arguments:

identifier Coverage identifier. Object of class character

bbox bbox. Object of class matrix. Default is NULL. eg. `OWSUtils$toBBOX(-180,180,-90,90)`

crs crs. Object of class character giving the CRS identifier (EPSG prefixed code, or URI/URN). Default is NULL.

time time. Object of class character representing time instant/period. Default is NULL

format format. Object of class character Default will be GeoTIFF, coded differently depending on the WCS version.

rangesubset rangesubset. Default is NULL

gridbaseCRS grid base CRS. Default is NULL

gridtype grid type. Default is NULL

gridCS grid CS. Default is NULL

gridorigin grid origin. Default is NULL

gridoffsets grid offsets. Default is NULL

method method to get coverage, either 'GET' or 'POST' (experimental - under development). Object of class character.

filename filename. Object of class character. Optional filename to download the coverage

... any other argument to [WCSGetCoverage](#)
 elevation elevation. Object of class character or numeric. Default is NULL
Returns: an object of class SpatRaster from **terra**

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WCSClient$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
## Not run:
  wcs <- WCSClient$new("http://localhost:8080/geoserver/wcs", serviceVersion = "2.0.1")

## End(Not run)
```

WCSCoverage

WCSCoverage

Description

WCSCoverage

WCSCoverage

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WCS coverage

Super class

[ows4R::OGCAbstractObject](#) -> WCSCoverage

Public fields

description description

Methods**Public methods:**

- [WCSCoverage\\$new\(\)](#)
- [WCSCoverage\\$getIdentifier\(\)](#)
- [WCSCoverage\\$getTitle\(\)](#)
- [WCSCoverage\\$getAbstract\(\)](#)
- [WCSCoverage\\$getReference\(\)](#)
- [WCSCoverage\\$getData\(\)](#)
- [WCSCoverage\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WCSCoverage](#)

Usage:

```
WCSCoverage$new(xmlObj, serviceVersion, owsVersion, logger = NULL)
```

Arguments:

xmlObj object of class [XMLInternalNode-class](#)

serviceVersion WCS service version

owsVersion OWS version

logger logger

Method [getIdentifier\(\)](#): Get identifier

Usage:

```
WCSCoverage$getIdentifier()
```

Returns: an object of class character

Method [getTitle\(\)](#): Get title

Usage:

```
WCSCoverage$getTitle()
```

Returns: an object of class character

Method [getAbstract\(\)](#): Get abstract

Usage:

```
WCSCoverage$getAbstract()
```

Returns: an object of class character

Method [getReference\(\)](#): Get reference

Usage:

```
WCSCoverage$getReference()
```

Returns: an object of class character

Method [getData\(\)](#): Get data

Usage:

```
WCSCoverage$getData(filename = NULL)
```

Arguments:

filename filename. Optional file name where to download the coverage

Returns: an object of class SpatRaster from **terra**

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WCSCoverage$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by ows4R.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WCSCoverageDescription

WCSCoverageDescription

Description

WCSCoverageDescription

WCSCoverageDescription

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WCS coverage summary

Super classes

```
geometa::geometaLogger -> geometa::ISOAbstractObject -> geometa::GMLAbstractObject  
-> geometa::GMLAbstractFeature -> geometa::GMLAbstractCoverage -> geometa::GMLCOVAbstractCoverage  
-> WCSCoverageDescription
```

Public fields

CoverageId coverage ID
 SupportedCRS supported CRS
 SupportedFormat supported Format
 Domain domain
 Range range
 ServiceParameters service parameters

Methods**Public methods:**

- [WCSCoverageDescription\\$new\(\)](#)
- [WCSCoverageDescription\\$getId\(\)](#)
- [WCSCoverageDescription\\$getSupportedCRS\(\)](#)
- [WCSCoverageDescription\\$getSupportedFormats\(\)](#)
- [WCSCoverageDescription\\$getDomain\(\)](#)
- [WCSCoverageDescription\\$getRange\(\)](#)
- [WCSCoverageDescription\\$clone\(\)](#)

Method new(): Initializes an object of class [WCSCoverageDescription](#)

Usage:

`WCSCoverageDescription$new(xmlObj, serviceVersion, owsVersion, logger = NULL)`

Arguments:

`xmlObj` an object of class [XMLInternalNode-class](#) to initialize from XML
`serviceVersion` service version
`owsVersion` OWS version
`logger` logger

Method getId(): getId

Usage:

`WCSCoverageDescription$getId()`

Returns: the coverage id, object of class character

Method getSupportedCRS(): getSupported CRS. Applies to WCS 1 coverage descriptions

Usage:

`WCSCoverageDescription$getSupportedCRS()`

Method getSupportedFormats(): get supported formats. Applies to WCS 1 coverage descriptions

Usage:

`WCSCoverageDescription$getSupportedFormats()`

Method getDomain(): get domain. Applies to WCS 1 coverage descriptions

Usage:

WCSCoverageDescription\$getDomain()

Method getRange(): get range. Applies to WCS 1.0 coverage descriptions

Usage:

WCSCoverageDescription\$getRange()

Method clone(): The objects of this class are cloneable with this method.

Usage:

WCSCoverageDescription\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by ows4R.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WCSCoverageDomain

WCSCoverageDomain

Description

WCSCoverageDomain

WCSCoverageDomain

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WCS coverage domain

Super class

[ows4R::OGCAbstractObject](#) -> WCSCoverageDomain

Public fields

spatialDomain spatial domain

temporalDomain temporal domain

Methods**Public methods:**

- [WCSCoverageDomain\\$new\(\)](#)
- [WCSCoverageDomain\\$getSpatialDomain\(\)](#)
- [WCSCoverageDomain\\$getTemporalDomain\(\)](#)
- [WCSCoverageDomain\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WCSCoverageDomain](#)

Usage:

```
WCSCoverageDomain$new(xmlObj, serviceVersion, owsVersion, logger = NULL)
```

Arguments:

xmlObj an object of class [XMLInternalNode-class](#) to initialize from XML

serviceVersion service version

owsVersion OWS version

logger logger

Method [getSpatialDomain\(\)](#): Get spatial domain

Usage:

```
WCSCoverageDomain$getSpatialDomain()
```

Returns: object of class [WCSCoverageSpatialDomain](#)

Method [getTemporalDomain\(\)](#): Get spatial domain

Usage:

```
WCSCoverageDomain$getTemporalDomain()
```

Returns: object of class [WCSCoverageTemporalDomain](#)

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
WCSCoverageDomain$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by ows4R.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WCSCoverageFilenameHandler
WCSCoverageFilenameHandler

Description

WCSCoverageFilenameHandler provides a coverage filename handler for coverage download

Usage

WCSCoverageFilenameHandler(identifier, time, elevation, bbox, format)

Arguments

identifier	coverage identifier
time	time
elevation	elevation
bbox	bbox
format	format

Value

the filename to use for coverage download

Author(s)

Emmanuel Blondel, <emmanuel.blondel1@gmail.com>

WCSCoverageSpatialDomain
WCSCoverageSpatialDomain

Description

WCSCoverageSpatialDomain
WCSCoverageSpatialDomain

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WCS coverage spatial domain

Super class

[ows4R::OGCAbstractObject](#) -> WCSCoverageSpatialDomain

Public fields

envelopes envelopes. For WCS 1.0

BoundingBox bounding box. For WCS 1.1

grids For WCS 1.0

GridCRS grid CRS. For WCS 1.1

Methods**Public methods:**

- [WCSCoverageSpatialDomain\\$new\(\)](#)
- [WCSCoverageSpatialDomain\\$getEnvelopes\(\)](#)
- [WCSCoverageSpatialDomain\\$getBoundingBox\(\)](#)
- [WCSCoverageSpatialDomain\\$getGrids\(\)](#)
- [WCSCoverageSpatialDomain\\$getGridCRS\(\)](#)
- [WCSCoverageSpatialDomain\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WCSCoverageDomain](#)

Usage:

```
WCSCoverageSpatialDomain$new(xmlObj, serviceVersion, owsVersion, logger = NULL)
```

Arguments:

xmlObj an object of class [XMLInternalNode-class](#) to initialize from XML

serviceVersion service version

owsVersion OWS version

logger logger

Method [getEnvelopes\(\)](#): Get envelopes. Method that applies to WCS 1.0 only

Usage:

```
WCSCoverageSpatialDomain$getEnvelopes()
```

Returns: a list of objects of class [GMLEnvelope](#) or [GMLEnvelopeWithTimePeriod](#)

Method [getBoundingBox\(\)](#): Get bounding boxes. Method that applies to WCS 1.1 only

Usage:

```
WCSCoverageSpatialDomain$getBoundingBox()
```

Returns: a list of objects of class [OWSBoundingBox](#)

Method [getGrids\(\)](#): Get grids. Method that applies to WCS 1.0 only

Usage:

```
WCSCoverageSpatialDomain$getGrids()
```

Returns: a list of objects of class [GMLGrid](#) or [GMLRectifiedGrid](#)

Method `getGridCRS()`: Get Grid CRS. Method that applies to WCS 1.1 only

Usage:

`WCSCoverageSpatialDomain$getGridCRS()`

Returns: a list of objects of class [WCSGridCRS](#)

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`WCSCoverageSpatialDomain$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by ows4R.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WCSCoverageSummary *WCSCoverageSummary*

Description

WCSCoverageSummary

WCSCoverageSummary

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WCS coverage summary

Super class

[ows4R::OGCAbstractObject](#) -> WCSCoverageSummary

Public fields

CoverageId coverage id

CoverageSubtype coverage subtype

CoverageSubtypeParent coverage subtype parent

WGS84BoundingBox WGS84 bounding box

BoundingBox bounding box

Methods**Public methods:**

- [WCSCoverageSummary\\$new\(\)](#)
- [WCSCoverageSummary\\$getId\(\)](#)
- [WCSCoverageSummary\\$getSubtype\(\)](#)
- [WCSCoverageSummary\\$getSubtypeParent\(\)](#)
- [WCSCoverageSummary\\$getWGS84BoundingBox\(\)](#)
- [WCSCoverageSummary\\$getBoundingBox\(\)](#)
- [WCSCoverageSummary\\$getDescription\(\)](#)
- [WCSCoverageSummary\\$getDimensions\(\)](#)
- [WCSCoverageSummary\\$getCoverage\(\)](#)
- [WCSCoverageSummary\\$getCoverageStack\(\)](#)
- [WCSCoverageSummary\\$clone\(\)](#)

Method new(): Initializes a [WCSCoverageSummary](#) object

Usage:

```
WCSCoverageSummary$new(
  xmlObj,
  capabilities,
  serviceVersion,
  owsVersion,
  logger = NULL
)
```

Arguments:

xmlObj object of class [XMLInternalNode-class](#) from **XML**
 capabilities object of class [WCSCapabilities](#)
 serviceVersion WCS service version
 owsVersion version
 logger logger type NULL, "INFO" or "DEBUG"

Method getId(): Get coverage ID

Usage:

```
WCSCoverageSummary$getId()
```

Returns: an object of class character

Method getSubtype(): Get sub type

Usage:

```
WCSCoverageSummary$getSubtype()
```

Returns: an object of class character

Method getSubtypeParent(): Get sub type parent

Usage:

```
WCSCoverageSummary$getSubtypeParent()
```

Returns: an object of class character

Method `getWGS84BoundingBox()`: Get bounding box

Usage:

```
WCSCoverageSummary$getWGS84BoundingBox()
```

Returns: an object of class [OWSWGS84BoundingBox](#)

Method `getBoundingBox()`: Get WGS84 bounding box

Usage:

```
WCSCoverageSummary$getBoundingBox()
```

Returns: an object of class [OWSBoundingBox](#)

Method `getDescription()`: Get description

Usage:

```
WCSCoverageSummary$getDescription()
```

Returns: an object of class [WCSCoverageDescription](#)

Method `getDimensions()`: Get dimensions

Usage:

```
WCSCoverageSummary$getDimensions()
```

Returns: the list of dimensions

Method `getCoverage()`: Get coverage data

Usage:

```
WCSCoverageSummary$getCoverage(
  bbox = NULL,
  crs = NULL,
  time = NULL,
  elevation = NULL,
  format = NULL,
  rangesubset = NULL,
  gridbaseCRS = NULL,
  gridtype = NULL,
  gridCS = NULL,
  gridorigin = NULL,
  gridoffsets = NULL,
  method = "GET",
  filename = NULL,
  ...
)
```

Arguments:

`bbox` `bbox`. Object of class `matrix`. Default is `NULL`. eg. `OWSUtils$toBBOX(-180,180,-90,90)`

`crs` `crs`. Object of class character giving the CRS identifier (EPSG prefixed code, or URI/URN). Default is `NULL`.

`time` `time`. Object of class character representing time instant/period. Default is `NULL`

elevation elevation. Object of class character or numeric. Default is NULL

format format. Object of class character Default will be GeoTIFF, coded differently depending on the WCS version.

rangesubset rangesubset. Default is NULL

gridbaseCRS grid base CRS. Default is NULL

gridtype grid type. Default is NULL

gridCS grid CS. Default is NULL

gridorigin grid origin. Default is NULL

gridoffsets grid offsets. Default is NULL

method method to get coverage, either 'GET' or 'POST' (experimental - under development).
Object of class character.

filename filename. Object of class character. Optional filename to download the coverage
... any other argument to [WCSGetCoverage](#)

Returns: an object of class SpatRaster from **terra**

Method `getCoverageStack()`: Get a spatio-temporal coverage data cubes as coverage [stack](#)

Usage:

```
WCSCoverageSummary$getCoverageStack(
  time = NULL,
  elevation = NULL,
  bbox = NULL,
  filename_handler = NULL,
  ...
)
```

Arguments:

time time

elevation elevation

bbox bbox

filename_handler Optional filename handling function with arguments 'identifier', 'time', 'elevation', 'bbox', 'format' See [WCSCoverageFilenameHandler](#) as generic filename handler that can be used.

... any other parameter to pass to `getCoverage`

Returns: an object of class [stack](#) from **raster**

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WCSCoverageSummary$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by ows4R.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WCSCoverageTemporalDomain
WCSCoverageTemporalDomain

Description

WCSCoverageTemporalDomain
WCSCoverageTemporalDomain

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WCS coverage temporal domain

Super class

[ows4R: :OGCAbstractObject](#) -> WCSCoverageTemporalDomain

Public fields

instants instants
periods periods

Methods**Public methods:**

- [WCSCoverageTemporalDomain\\$new\(\)](#)
- [WCSCoverageTemporalDomain\\$getInstants\(\)](#)
- [WCSCoverageTemporalDomain\\$getPeriods\(\)](#)
- [WCSCoverageTemporalDomain\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WCSCoverageTemporalDomain](#)

Usage:

```
WCSCoverageTemporalDomain$new(  
  xmlObj,  
  serviceVersion,  
  owsVersion,  
  logger = NULL  
)
```

Arguments:

xmlObj an object of class [XMLInternalNode-class](#) to initialize from XML
serviceVersion service version

owsVersion OWS version
logger logger

Method `getInstants()`: Get time instants

Usage:

`WCSCoverageTemporalDomain$getInstants()`

Returns: a list of objects of class `POSIXct`

Method `getPeriods()`: Get time periods

Usage:

`WCSCoverageTemporalDomain$getPeriods()`

Returns: a list of objects of class [GMLTimePeriod](#)

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`WCSCoverageTemporalDomain$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by `ows4R`.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WCSDescribeCoverage *WCSDescribeCoverage*

Description

WCSDescribeCoverage

WCSDescribeCoverage

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WCS DescribeCoverage request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> `WCSDescribeCoverage`

Methods**Public methods:**

- [WCSDescribeCoverage\\$new\(\)](#)
- [WCSDescribeCoverage\\$clone\(\)](#)

Method `new()`: Initializes a [WCSDescribeCoverage](#) service request

Usage:

```
WCSDescribeCoverage$new(
  capabilities,
  op,
  url,
  serviceVersion,
  coverageId,
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = c(),
  config = httr::config(),
  logger = NULL,
  ...
)
```

Arguments:

`capabilities` an object of class [WCSCapabilities](#)
`op` object of class [OWSOperation](#) as retrieved from `capabilities`
`url` url
`serviceVersion` serviceVersion
`coverageId` coverage ID
`user` user
`pwd` password
`token` token
`headers` headers
`config` config
`logger` logger
`...` any parameter to pass to the service request

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WCSDescribeCoverage$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a WCS DescribeCoverage request

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WCSGetCoverage

WCSGetCoverage

Description

WCSGetCoverage

WCSGetCoverage

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WCS GetCoverage request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> WCSGetCoverage

Public fields

CoverageId coverage identifier

format coverage format

Methods**Public methods:**

- [WCSGetCoverage\\$new\(\)](#)
- [WCSGetCoverage\\$clone\(\)](#)

Method new(): Initializes a [WCSGetCoverage](#) service request

Usage:

```
WCSGetCoverage$new(  
  capabilities,  
  op,  
  url,  
  serviceVersion,  
  coverage,  
  envelope = NULL,  
  crs = NULL,  
  time = NULL,  
  elevation = NULL,
```

```

    format = NULL,
    rangesubset = NULL,
    gridbaseCRS = NULL,
    gridtype = NULL,
    gridCS = NULL,
    gridorigin = NULL,
    gridoffsets = NULL,
    user = NULL,
    pwd = NULL,
    token = NULL,
    headers = c(),
    config = htr::config(),
    method = "GET",
    logger = NULL,
    ...
)

```

Arguments:

capabilities an object of class [WCSCapabilities](#)
op object of class [OWSOperation](#) as retrieved from capabilities
url url
serviceVersion serviceVersion
coverage coverage, object of class [WCSCoverageSummary](#)
envelope envelope
crs crs
time time
elevation elevation
format format
rangesubset range subset
gridbaseCRS grid base CRS
gridtype grid type
gridCS grid CS
gridorigin grid origin
gridoffsets grid offsets
user user
pwd password
token token
headers headers
config config
method method
logger logger
... any parameter to pass to the service request

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WCSGetCoverage$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a WCS GetCoverage request

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WCSGridCRS

WCSGridCRS

Description

WCSGridCRS

WCSGridCRS

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WCS grid CRS

Super class

[ows4R::OGCAbstractObject](#) -> WCSGridCRS

Public fields

GridBaseCRS grid base CRS

GridType grid type

GridOrigin grid origin

GridOffsets grid offsets

GridCS grid CS

Methods**Public methods:**

- [WCSGridCRS\\$new\(\)](#)
- [WCSGridCRS\\$clone\(\)](#)

Method `new()`: Initializes an object of class [WCSGridCRS](#)

Usage:

```
WCSGridCRS$new(xmlObj, serviceVersion, owsVersion, logger = NULL)
```

Arguments:

`xmlObj` an object of class [XMLInternalNode-class](#) to initialize from XML
`serviceVersion` service version
`owsVersion` OWS version
`logger` logger

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WCSGridCRS$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by ows4R.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WCSGSElevationDomain *WCSGSElevationDomain*

Description

WCSGSElevationDomain

WCSGSElevationDomain

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WCS geoserver elevation domain object

Super classes

[geometa::geometaLogger](#) -> [geometa::ISOAbstractObject](#) -> [WCSGSElevationDomain](#)

Public fields

[SingleValue](#) single values

Methods**Public methods:**

- [WCSGSElevationDomain\\$decode\(\)](#)
- [WCSGSElevationDomain\\$clone\(\)](#)

Method [decode\(\)](#): Decodes from XML

Usage:

[WCSGSElevationDomain\\$decode\(xml\)](#)

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

[WCSGSElevationDomain\\$clone\(deep = FALSE\)](#)

Arguments:

deep Whether to make a deep clone.

Note

Experimental

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WCSGSTimeDomain

WCSGSTimeDomain

Description

WCSGSTimeDomain

WCSGSTimeDomain

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WCS geoserver time domain object

Super classes

[geometa::geometaLogger](#) -> [geometa::ISOAbstractObject](#) -> [WCSGSTimeDomain](#)

Public fields

TimeInstant time instants

Methods**Public methods:**

- [WCSGSTimeDomain\\$decode\(\)](#)
- [WCSGSTimeDomain\\$clone\(\)](#)

Method [decode\(\)](#): Decodes from XML

Usage:

[WCSGSTimeDomain\\$decode\(xml\)](#)

Arguments:

xml object of class [XMLInternalNode-class](#) from [XML](#)

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

[WCSGSTimeDomain\\$clone\(deep = FALSE\)](#)

Arguments:

deep Whether to make a deep clone.

Note

Experimental

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WFSCapabilities	<i>WFSCapabilities</i>
-----------------	------------------------

Description

WFSCapabilities

WFSCapabilities

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing an OGC Web Feature Service Get Capabilities document.

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSCapabilities](#) -> WFSCapabilities

Methods**Public methods:**

- [WFSCapabilities\\$new\(\)](#)
- [WFSCapabilities\\$getFeatureTypes\(\)](#)
- [WFSCapabilities\\$findFeatureTypeByName\(\)](#)
- [WFSCapabilities\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WFSCapabilities](#) object

Usage:

```
WFSCapabilities$new(url, version, logger = NULL, ...)
```

Arguments:

url url

version version

logger logger type NULL, "INFO" or "DEBUG"

... any other parameter to pass to [OWSGetCapabilities](#) service request

Method [getFeatureTypes\(\)](#): List the feature types available. If pretty is TRUE, the output will be an object of class data.frame

Usage:

```
WFSCapabilities$getFeatureTypes(pretty = FALSE)
```

Arguments:

pretty whether the output should be summarized as data.frame

Returns: a list of [WFSFeatureType](#) or a `data.frame`

Method `findFeatureTypeByName()`: Finds a feature type by name

Usage:

```
WFSCapabilities$findFeatureTypeByName(expr, exact = TRUE)
```

Arguments:

`expr` `expr`

`exact` exact matching? Default is TRUE

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WFSCapabilities$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used to read a `WFSCapabilities` document. The use of `WFSCient` is recommended instead to benefit from the full set of capabilities associated to a WFS server.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WFSCient

WFSCient

Description

WFSCient

WFSCient

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing an OGC Web Feature Service.

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSCient](#) -> `WFSCient`

Methods**Public methods:**

- [WFSCClient\\$new\(\)](#)
- [WFSCClient\\$getCapabilities\(\)](#)
- [WFSCClient\\$reloadCapabilities\(\)](#)
- [WFSCClient\\$describeFeatureType\(\)](#)
- [WFSCClient\\$getFeatures\(\)](#)
- [WFSCClient\\$getFeatureTypes\(\)](#)
- [WFSCClient\\$clone\(\)](#)

Method new(): This method is used to instantiate a [WFSCClient](#) with the url of the OGC service. Authentication is supported using basic auth (using user/pwd arguments), bearer token (using token argument), or custom (using headers argument). By default, the logger argument will be set to NULL (no logger). This argument accepts two possible values: INFO: to print only **ows4R** logs, DEBUG: to print more verbose logs

Usage:

```
WFSCClient$new(
  url,
  serviceVersion = NULL,
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = c(),
  config = httr::config(),
  cas_url = NULL,
  logger = NULL
)
```

Arguments:

```
url url
serviceVersion WFS service version
user user
pwd password
token token
headers headers
config config
cas_url Central Authentication Service (CAS) URL
logger logger
```

Method getCapabilities(): Get WFS capabilities

Usage:

```
WFSCClient$getCapabilities()
```

Returns: an object of class [WFSCapabilities](#)

Method reloadCapabilities(): Reloads WFS capabilities

Usage:

```
WFSClient$reloadCapabilities()
```

Method describeFeatureType(): Describes a feature type

Usage:

```
WFSClient$describeFeatureType(typeName)
```

Arguments:

typeName the name of the feature type

Returns: a list of [WFSFeatureTypeElement](#)

Method getFeatures(): Get features

Usage:

```
WFSClient$getFeatures(typeName, ...)
```

Arguments:

typeName the name of the feature type

... any other parameter to pass to the [WFSGetFeature](#) request

Returns: features as object of class sf

Method getFeatureTypes(): List the feature types available. If pretty is TRUE, the output will be an object of class data.frame

Usage:

```
WFSClient$getFeatureTypes(pretty = FALSE)
```

Arguments:

pretty whether the output should be summarized as data.frame

Returns: a list of [WFSFeatureType](#) or a data.frame

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WFSClient$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
## Not run:
#example based on a WFS endpoint responding at http://localhost:8080/geoserver/wfs
wfs <- WFSClient$new("http://localhost:8080/geoserver/wfs", serviceVersion = "1.1.1")

#get capabilities
caps <- wfs$getCapabilities()
```

```

#find feature type
ft <- caps$findFeatureTypeByName("mylayer")
if(length(ft)>0){
  data <- ft$getFeatures()
  data_with_filter <- ft$getFeatures(cql_filter = "somefilter")
}

#Advanced examples at https://github.com/eblondel/ows4R/wiki#wfs

## End(Not run)

```

WFSDescribeFeatureType

WFSDescribeFeatureType

Description

WFSDescribeFeatureType

WFSDescribeFeatureType

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WFS DescribeFeatureType request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> WFSDescribeFeatureType

Methods

Public methods:

- [WFSDescribeFeatureType\\$new\(\)](#)
- [WFSDescribeFeatureType\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WFSDescribeFeatureType](#) service request

Usage:

```

WFSDescribeFeatureType$new(
  capabilities,
  op,
  url,
  version,
  typeName,

```

```

    user = NULL,
    pwd = NULL,
    token = NULL,
    headers = c(),
    config = httr::config(),
    logger = NULL,
    ...
)

```

Arguments:

capabilities an object of class [WFSCapabilities](#)
op object of class [OWSOperation](#) as retrieved from capabilities
url url
version service version
typeName typeName
user user
pwd pwd
token token
headers headers
config config
logger logger
... any parameter to pass to the service request

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WFSDescribeFeatureType$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used by **ows4R** to trigger a WFS DescribeFeatureType request

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WFSFeatureType

WFSFeatureType

Description

WFSFeatureType

WFSFeatureType

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WFS feature type

Super class

[ows4R::OGCAbstractObject](#) -> WFSFeatureType

Public fields

description description

features features

Methods**Public methods:**

- [WFSFeatureType\\$new\(\)](#)
- [WFSFeatureType\\$getName\(\)](#)
- [WFSFeatureType\\$getTitle\(\)](#)
- [WFSFeatureType\\$getAbstract\(\)](#)
- [WFSFeatureType\\$getKeywords\(\)](#)
- [WFSFeatureType\\$getDefaultCRS\(\)](#)
- [WFSFeatureType\\$getBoundingBox\(\)](#)
- [WFSFeatureType\\$getDescription\(\)](#)
- [WFSFeatureType\\$hasGeometry\(\)](#)
- [WFSFeatureType\\$getGeometryType\(\)](#)
- [WFSFeatureType\\$getFeaturesCRS\(\)](#)
- [WFSFeatureType\\$getFeatures\(\)](#)
- [WFSFeatureType\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WFSFeatureType](#)

Usage:

```
WFSFeatureType$new(xmlObj, capabilities, version, logger = NULL)
```

Arguments:

xmlObj an object of class [XMLInternalNode-class](#) to initialize from XML

capabilities object of class [WFSCapabilities](#)

version service version

logger logger

Method [getName\(\)](#): Get feature type name

Usage:

```
WFSFeatureType$getName()
```

Arguments:

object of class character

Method getTitle(): Get feature type title

Usage:

WFSFeatureType\$title()

Arguments:

object of class character

Method getAbstract(): Get feature type abstract

Usage:

WFSFeatureType\$getAbstract()

Arguments:

object of class character

Method getKeywords(): Get feature type keywords

Usage:

WFSFeatureType\$getKeywords()

Arguments:

object of class character

Method getDefaultCRS(): Get feature type default CRS

Usage:

WFSFeatureType\$getDefaultCRS()

Arguments:

object of class character

Method getBoundingBox(): Get feature type bounding box

Usage:

WFSFeatureType\$getBoundingBox()

Arguments:

object of class matrix

Method getDescription(): Describes a feature type

Usage:

WFSFeatureType\$getDescription(pretty = FALSE)

Arguments:

pretty pretty whether to return a prettified data.frame. Default is FALSE

Returns: a list of [WFSFeatureTypeElement](#) or data.frame

Method hasGeometry(): Indicates with feature type has a geometry

Usage:

WFSFeatureType\$hasGeometry()

Returns: object of class [logical](#)

Method getGeometryType(): Get geometry type

Usage:

WFSFeatureType\$getGeometryType()

Returns: object of class [character](#) representing the geometry tpe

Method getFeaturesCRS(): Inherits features CRS

Usage:

WFSFeatureType\$getFeaturesCRS(obj)

Arguments:

obj features object

Returns: object of class [integer](#)

Method getFeatures(): Get features

Usage:

```
WFSFeatureType$getFeatures(
  ...,
  validate = TRUE,
  outputFormat = NULL,
  paging = FALSE,
  paging_length = 1000,
  parallel = FALSE,
  parallel_handler = NULL,
  cl = NULL
)
```

Arguments:

... any other parameter to pass to the [WFSGetFeature](#) request

validate Whether features have to be validated vs. the feature type description. Default is TRUE

outputFormat output format

paging paging. Default is FALSE

paging_length number of features to request per page. Default is 1000

parallel whether to get features using parallel multicore strategy. Default is FALSE

parallel_handler Handler function to parallelize the code. eg [mclapply](#)

cl optional cluster object for parallel cluster approaches using eg. `parallel::makeCluster`

typeName the name of the feature type

Returns: features as object of class sf

Method clone(): The objects of this class are cloneable with this method.

Usage:

WFSFeatureType\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a WFS DescribeFeatureType request

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WFSFeatureTypeElement *WFSFeatureTypeElement*

Description

WFSFeatureTypeElement

WFSFeatureTypeElement

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WFS feature type element

Methods**Public methods:**

- [WFSFeatureTypeElement\\$new\(\)](#)
- [WFSFeatureTypeElement\\$getMinOccurs\(\)](#)
- [WFSFeatureTypeElement\\$getMaxOccurs\(\)](#)
- [WFSFeatureTypeElement\\$isNilable\(\)](#)
- [WFSFeatureTypeElement\\$name\(\)](#)
- [WFSFeatureTypeElement\\$type\(\)](#)
- [WFSFeatureTypeElement\\$isGeometry\(\)](#)
- [WFSFeatureTypeElement\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WFSFeatureTypeElement](#)

Usage:

```
WFSFeatureTypeElement$new(xmlObj, namespaces)
```

Arguments:

xmlObj object of class [XMLInternalNode-class](#) from **XML**

namespaces namespaces definitions inherited from parent XML, as data.frame

Method [getMinOccurs\(\)](#): get min occurs

Usage:

WFSFeatureTypeElement\$getMinOccurs()

Returns: an object of class character

Method getMaxOccurs(): get max occurs

Usage:

WFSFeatureTypeElement\$getMaxOccurs()

Returns: an object of class character

Method isNillable(): get if nillable

Usage:

WFSFeatureTypeElement\$isNillable()

Returns: an object of class logical

Method getName(): get name

Usage:

WFSFeatureTypeElement\$getName()

Returns: an object of class character

Method getType(): get type

Usage:

WFSFeatureTypeElement\$getType()

Returns: an object of class character

Method isGeometry(): Is geometry

Usage:

WFSFeatureTypeElement\$isGeometry()

Arguments:

return object of class logical

Method clone(): The objects of this class are cloneable with this method.

Usage:

WFSFeatureTypeElement\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WFSGetFeature	<i>WFSGetFeature</i>
---------------	----------------------

Description

WFSGetFeature

WFSGetFeature

Format[R6Class](#) object.**Value**Object of [R6Class](#) for modelling a WFS GetFeature request**Super classes**[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> WFSGetFeature**Methods****Public methods:**

- [WFSGetFeature\\$new\(\)](#)
- [WFSGetFeature\\$clone\(\)](#)

Method `new()`: Initializes a [WFSGetFeature](#) service request*Usage:*

```
WFSGetFeature$new(
  capabilities,
  op,
  url,
  version,
  typeName,
  outputFormat = NULL,
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = c(),
  config = httr::config(),
  logger = NULL,
  ...
)
```

*Arguments:*capabilities an object of class [WFSCapabilities](#)op object of class [OWSOperation](#) as retrieved from capabilities

url url
 version service version
 typeName typeName
 outputFormat output format
 user user
 pwd password
 token token
 headers headers
 config config
 logger logger
 . . . any parameter to pass to the service request

Method clone(): The objects of this class are cloneable with this method.

Usage:

WFSGetFeature\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a WFS GetFeature request

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WMSCapabilities

WMSCapabilities

Description

WMSCapabilities

WMSCapabilities

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing an OGC Web Map Service Get Capabilities document.

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSCapabilities](#) -> WMSCapabilities

Methods**Public methods:**

- [WMSCapabilities\\$new\(\)](#)
- [WMSCapabilities\\$getRequests\(\)](#)
- [WMSCapabilities\\$getRequestNames\(\)](#)
- [WMSCapabilities\\$getLayers\(\)](#)
- [WMSCapabilities\\$findLayerByName\(\)](#)
- [WMSCapabilities\\$clone\(\)](#)

Method `new()`: Initializes a [WMSCapabilities](#) object

Usage:

```
WMSCapabilities$new(url, version, logger = NULL, ...)
```

Arguments:

`url` url

`version` version

`logger` logger type NULL, "INFO" or "DEBUG"

`...` any other parameter to pass to [OWSGetCapabilities](#) service request

Method `getRequests()`: List the requests available. If `pretty` is TRUE, the output will be an object of class `data.frame`

Usage:

```
WMSCapabilities$getRequests(pretty = FALSE)
```

Arguments:

`pretty` pretty

Returns: a list of [OWSRequest](#) available, or a `data.frame`

Method `getRequestNames()`: List the names of requests available.

Usage:

```
WMSCapabilities$getRequestNames()
```

Returns: object of class `character`

Method `getLayers()`: List the layers available. If `pretty` is TRUE, the output will be an object of class `data.frame`

Usage:

```
WMSCapabilities$getLayers(pretty = FALSE)
```

Arguments:

`pretty` pretty

Returns: a list of [WMSLayer](#) available, or a `data.frame`

Method `findLayerByName()`: Finds a layer by name

Usage:

```
WMSCapabilities$findLayerByName(expr, exact = TRUE)
```

Arguments:

expr expr

exact exact matching? Default is TRUE

Method clone(): The objects of this class are cloneable with this method.

Usage:

WMSCapabilities\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Class used to read a WMSCapabilities document. The use of WMSClient is recommended instead to benefit from the full set of capabilities associated to a WMS server.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WMSClient

WMSClient

Description

WMSClient

WMSClient

Format[R6Class](#) object.**Value**Object of [R6Class](#) with methods for interfacing an OGC Web Map Service.**Super classes**[ows4R::OGCAbstractObject](#) -> [ows4R::OWSClient](#) -> WMSClient

Methods**Public methods:**

- [WMSClient\\$new\(\)](#)
- [WMSClient\\$getCapabilities\(\)](#)
- [WMSClient\\$reloadCapabilities\(\)](#)
- [WMSClient\\$getLayers\(\)](#)
- [WMSClient\\$getMap\(\)](#)
- [WMSClient\\$getFeatureInfo\(\)](#)
- [WMSClient\\$getLegendGraphic\(\)](#)
- [WMSClient\\$clone\(\)](#)

Method new(): This method is used to instantiate a [WMSClient](#) with the url of the OGC service. Authentication is supported using basic auth (using user/pwd arguments), bearer token (using token argument), or custom (using headers argument). By default, the logger argument will be set to NULL (no logger). This argument accepts two possible values: INFO: to print only **ows4R** logs, DEBUG: to print more verbose logs

Usage:

```
WMSClient$new(
  url,
  serviceVersion = NULL,
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = c(),
  config = httr::config(),
  cas_url = NULL,
  logger = NULL
)
```

Arguments:

```
url url
serviceVersion WFS service version
user user
pwd password
token token
headers headers
config config
cas_url Central Authentication Service (CAS) URL
logger logger
```

Method getCapabilities(): Get WMS capabilities

Usage:

```
WMSClient$getCapabilities()
```

Returns: an object of class [WMSCapabilities](#)

Method reloadCapabilities(): Reloads WFS capabilities

Usage:

```
WMSClient$reloadCapabilities()
```

Method getLayers(): List the layers available. If pretty is TRUE, the output will be an object of class data.frame

Usage:

```
WMSClient$getLayers(pretty = FALSE)
```

Arguments:

pretty pretty

Returns: a list of [WMSLayer](#) available, or a data.frame

Method getMap(): Get map. NOT YET IMPLEMENTED

Usage:

```
WMSClient$getMap()
```

Method getFeatureInfo(): Get feature info

Usage:

```
WMSClient$getFeatureInfo(
  layer,
  srs = NULL,
  styles = NULL,
  feature_count = 1,
  x,
  y,
  width,
  height,
  bbox,
  info_format = "application/vnd.ogc.gml",
  ...
)
```

Arguments:

layer layer name

srs srs

styles styles

feature_count feature count. Default is 1

x x

y y

width width

height height

bbox bbox

info_format info format. Default is "application/vnd.ogc.gml"

... any other parameter to pass to a [WMSGetFeatureInfo](#) request

Returns: an object of class sf given the feature(s)

Method getLegendGraphic(): Get legend graphic. NOT YET IMPLEMENTED

Usage:

```
WMSClient$getLegendGraphic()
```

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WMSClient$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
## Not run:
#example based on a WMS endpoint responding at http://localhost:8080/geoserver/wms
wms <- WMSClient$new("http://localhost:8080/geoserver/wms", serviceVersion = "1.1.1")

#get capabilities
caps <- wms$getCapabilities()

#get feature info

#Advanced examples at https://github.com/eblondel/ows4R/wiki#wms

## End(Not run)
```

WMSGetFeatureInfo

WMSGetFeatureInfo

Description

WMSGetFeatureInfo

WMSGetFeatureInfo

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WMS GetFeatureInfo request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> WMSGetFeatureInfo

Methods**Public methods:**

- [WMSGetFeatureInfo\\$new\(\)](#)
- [WMSGetFeatureInfo\\$clone\(\)](#)

Method `new()`: Initializes a [WMSGetFeatureInfo](#) service request

Usage:

```
WMSGetFeatureInfo$new(
  capabilities,
  op,
  url,
  version,
  layers,
  srs,
  styles,
  feature_count = 1,
  x,
  y,
  width,
  height,
  bbox,
  info_format = "text/xml",
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = c(),
  config = httr::config(),
  logger = NULL,
  ...
)
```

Arguments:

`capabilities` an object of class [WMSCapabilities](#)
`op` object of class [OWSOperation](#) as retrieved from `capabilities`
`url` url
`version` version
`layers` layers
`srs` srs
`styles` styles
`feature_count` feature count
`x` x
`y` y

width width
height height
bbox bbox
info_format info format
user user
pwd pwd
token token
headers headers
config config
logger logger
... any parameter to pass to the service request

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WMSGetFeatureInfo$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a WMS GetFeatureInfo request

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WMSLayer

WMSLayer

Description

WMSLayer

WMSLayer

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WMS layer

Super class

[ows4R::OGCAbstractObject](#) -> WMSLayer

Public fields

description description
 features features

Methods**Public methods:**

- [WMSLayer\\$new\(\)](#)
- [WMSLayer\\$getName\(\)](#)
- [WMSLayer\\$getTitle\(\)](#)
- [WMSLayer\\$getAbstract\(\)](#)
- [WMSLayer\\$getKeywords\(\)](#)
- [WMSLayer\\$getDefaultCRS\(\)](#)
- [WMSLayer\\$getBoundingBox\(\)](#)
- [WMSLayer\\$getBoundingBoxSRS\(\)](#)
- [WMSLayer\\$getBoundingBoxCRS\(\)](#)
- [WMSLayer\\$getStyle\(\)](#)
- [WMSLayer\\$getStyleNames\(\)](#)
- [WMSLayer\\$getDimensions\(\)](#)
- [WMSLayer\\$getTimeDimension\(\)](#)
- [WMSLayer\\$getElevationDimension\(\)](#)
- [WMSLayer\\$getFeatureInfo\(\)](#)
- [WMSLayer\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WMSLayer](#)

Usage:

`WMSLayer$new(xmlObj, capabilities, version, logger = NULL)`

Arguments:

`xmlObj` an object of class [XMLInternalNode-class](#) to initialize from XML
`capabilities` object of class [WMSCapabilities](#)
`version` service version
`logger` logger

Method [getName\(\)](#): Get layer name

Usage:

`WMSLayer$getName()`

Returns: object of class character

Method [getTitle\(\)](#): Get layer title

Usage:

`WMSLayer$getTitle()`

Returns: object of class character

Method getAbstract(): Get layer abstract

Usage:

WMSLayer\$getAbstract()

Returns: object of class character

Method getKeywords(): Get layer keywords

Usage:

WMSLayer\$getKeywords()

Returns: object of class character

Method getDefaultCRS(): Get layer default CRS

Usage:

WMSLayer\$getDefaultCRS()

Returns: object of class character

Method getBoundingBox(): Get layer bounding box

Usage:

WMSLayer\$getBoundingBox()

Returns: object of class matrix

Method getBoundingBoxSRS(): Get layer bounding box SRS

Usage:

WMSLayer\$getBoundingBoxSRS()

Returns: object of class character

Method getBoundingBoxCRS(): Get layer bounding box CRS

Usage:

WMSLayer\$getBoundingBoxCRS()

Returns: object of class character

Method getStyles(): Get layer styles

Usage:

WMSLayer\$getStyles()

Returns: an object of class list

Method getStylenames(): Get layer style names

Usage:

WMSLayer\$getStylenames()

Returns: list of object of class character

Method getDimensions(): Get layer dimensions

Usage:

WMSLayer\$getDimensions(time_format = "character")

Arguments:

time_format time format. Default is character

Returns: a list including default value and listed possible values

Method getTimeDimension(): Get layer TIME dimensions

Usage:

```
WMSLayer$getTimeDimension(time_format = "character")
```

Arguments:

time_format time format. Default is character

Returns: a list including default value and listed possible values

Method getElevationDimension(): Get layer ELEVATION dimensions

Usage:

```
WMSLayer$getElevationDimension()
```

Returns: a list including default value and listed possible values

Method getFeatureInfo(): Get feature info

Usage:

```
WMSLayer$getFeatureInfo(
  srs = NULL,
  styles = NULL,
  feature_count = 1,
  x,
  y,
  width,
  height,
  bbox,
  info_format = "text/xml",
  ...
)
```

Arguments:

srs srs

styles styles

feature_count feature count. Default is 1

x x

y y

width width

height height

bbox bbox

info_format info format. Default is "text/xml"

... any other parameter to pass to a [WMSGetFeatureInfo](#) request

Returns: an object of class sf given the feature(s)

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WMSLayer$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSBoundingBoxData *WPSBoundingBoxData*

Description

WPSBoundingBoxData

WPSBoundingBoxData

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGC WPS BoundingBox data

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSBoundingBox](#) -> WPSBoundingBoxData

Methods**Public methods:**

- [WPSBoundingBoxData\\$new\(\)](#)
- [WPSBoundingBoxData\\$clone\(\)](#)

Method `new()`: Initializes an object of class [WPSBoundingBoxData](#)

Usage:

```
WPSBoundingBoxData$new(  
  xml = NULL,  
  owsVersion,  
  serviceVersion = "1.0.0",  
  logger = NULL,  
  ...  
)
```

Arguments:

xml an object of class [XMLInternalNode-class](#) to initialize from XML
 owsVersion OWS version
 serviceVersion WPS service version
 logger logger
 ... any other parameter

Method clone(): The objects of this class are cloneable with this method.

Usage:

WPSCapabilities\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSCapabilities

WPSCapabilities

Description

WPSCapabilities

WPSCapabilities

Format

[R6Class](#) object.

Value

Object of [R6Class](#) with methods for interfacing an OGC Web Processing Service (WPS) Get Capabilities document.

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSCapabilities](#) -> WPSCapabilities

Methods

Public methods:

- [WPSCapabilities\\$new\(\)](#)
- [WPSCapabilities\\$getProcesses\(\)](#)
- [WPSCapabilities\\$describeProcess\(\)](#)
- [WPSCapabilities\\$execute\(\)](#)
- [WPSCapabilities\\$clone\(\)](#)

Method `new()`: Initializes a [WPSCapabilities](#) object

Usage:

```
WPSCapabilities$new(url, version, client = NULL, logger = NULL, ...)
```

Arguments:

url url

version version

client an object of class [WPSClient](#)

logger logger type NULL, "INFO" or "DEBUG"

... any other parameter to pass to [OWSGetCapabilities](#) service request

Method `getProcesses()`: Get the list of processes offered by the service capabilities. `pretty` allows to control the type output. If TRUE, a `data.frame` will be returned. When prettified output, it is also possible to get a 'full' description of the process by setting `full = TRUE` in which case a the WPS client will request a process description (with more information about the process) for each process listed in the capabilities.

Usage:

```
WPSCapabilities$getProcesses(pretty = FALSE, full = FALSE)
```

Arguments:

pretty pretty

full full

Returns: a list of [WPSProcessDescription](#) or a `data.frame`

Method `describeProcess()`: Get the description of a process, given its identifier, returning an object of class `WPSProcessDescription`

Usage:

```
WPSCapabilities$describeProcess(identifier)
```

Arguments:

identifier process identifier

Returns: an object of class [WPSProcessDescription](#)

Method `execute()`: Execute a process, given its identifier

Usage:

```

WPSCapabilities$execute(
  identifier,
  dataInputs = list(),
  responseForm = NULL,
  storeExecuteResponse = FALSE,
  lineage = NULL,
  status = NULL,
  update = FALSE,
  updateInterval = 1
)

```

Arguments:

identifier process identifier

dataInputs a named list of data inputs, objects of class [WPSLiteralData](#), [WPSComplexData](#) or [WPSBoundingBoxData](#)

responseForm response form, object of class [WPSResponseDocument](#)

storeExecuteResponse store execute response? object of class logical. FALSE by default

lineage lineage, object of class logical

status status, object of class logical

update update, object of class logical. For asynchronous requests

updateInterval update interval, object of class integer. For asynchronous requests

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WPSCapabilities$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used to read a `WPSCapabilities` document. The use of `WPSClient` is recommended instead to benefit from the full set of capabilities associated to a WPS server.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSClient

WPSClient

Description

WPSClient

WPSClient

Format

R6Class object.

Value

Object of R6Class with methods for interfacing an OGC Web Processing Service.

Super classes

ows4R::OGCAbstractObject -> ows4R::OWSClient -> WPSClient

Methods**Public methods:**

- WPSClient\$new()
- WPSClient\$getCapabilities()
- WPSClient\$reloadCapabilities()
- WPSClient\$getProcesses()
- WPSClient\$describeProcess()
- WPSClient\$execute()
- WPSClient\$clone()

Method new(): This method is used to instantiate a WPSClient with the url of the OGC service. Authentication is supported using basic auth (using user/pwd arguments), bearer token (using token argument), or custom (using headers argument). By default, the logger argument will be set to NULL (no logger). This argument accepts two possible values: INFO: to print only **ows4R** logs, DEBUG: to print more verbose logs

Usage:

```
WPSClient$new(
  url,
  serviceVersion = NULL,
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = c(),
  config = httr::config(),
  cas_url = NULL,
  logger = NULL
)
```

Arguments:

```
url url
serviceVersion WFS service version
user user
pwd password
token token
headers headers
```

```

config config
cas_url Central Authentication Service (CAS) URL
logger logger

```

Method `getCapabilities()`: Get WPS capabilities

Usage:

```
WPSClient$getCapabilities()
```

Returns: an object of class [WPSCapabilities](#)

Method `reloadCapabilities()`: Reloads WPS capabilities

Usage:

```
WPSClient$reloadCapabilities()
```

Method `getProcesses()`: Get the list of processes offered by the service capabilities. `pretty` allows to control the type output. If `TRUE`, a `data.frame` will be returned. When prettified output, it is also possible to get a 'full' description of the process by setting `full = TRUE` in which case the WPS client will request a process description (with more information about the process) for each process listed in the capabilities.

Usage:

```
WPSClient$getProcesses(pretty = FALSE, full = FALSE)
```

Arguments:

```
pretty pretty
```

```
full full
```

Returns: a list of [WPSProcessDescription](#) or a `data.frame`

Method `describeProcess()`: Get the description of a process, given its identifier, returning an object of class `WPSProcessDescription`

Usage:

```
WPSClient$describeProcess(identifier)
```

Arguments:

```
identifier process identifier
```

Returns: an object of class [WPSProcessDescription](#)

Method `execute()`: Execute a process, given its identifier

Usage:

```

WPSClient$execute(
  identifier,
  dataInputs = list(),
  responseForm = NULL,
  storeExecuteResponse = FALSE,
  lineage = NULL,
  status = NULL,
  update = FALSE,
  updateInterval = 1
)

```

Arguments:

identifier process identifier
 dataInputs a named list of data inputs, objects of class [WPSLiteralData](#), [WPSComplexData](#)
 or [WPSBoundingBoxData](#)
 responseForm response form, object of class [WPSResponseDocument](#)
 storeExecuteResponse store execute response? object of class logical. FALSE by default
 lineage lineage, object of class logical
 status status, object of class logical
 update update, object of class logical. For asynchronous requests
 updateInterval update interval, object of class integer. For asynchronous requests

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WPSClient$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Examples

```
## Not run:
#example based on a WPS endpoint responding at http://localhost:8080/geoserver/wps
wps <- WPSClient$new("http://localhost:8080/geoserver/wps", serviceVersion = "1.0.0")

#get capabilities
caps <- wps$getCapabilities()

## End(Not run)
```

WPSComplexData

WPSComplexData

Description

WPSComplexData

WPSComplexData

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WPS Complex Data

Super class

[ows4R::OGCAbstractObject](#) -> WPSComplexData

Public fields

value value

Methods**Public methods:**

- [WPSComplexData\\$new\(\)](#)
- [WPSComplexData\\$decode\(\)](#)
- [WPSComplexData\\$checkValidity\(\)](#)
- [WPSComplexData\\$getFeatures\(\)](#)
- [WPSComplexData\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WPSComplexData](#)

Usage:

```
WPSComplexData$new(
  xml = NULL,
  value = NULL,
  schema = NULL,
  mimeType = NULL,
  serviceVersion = "1.0.0",
  cdata = TRUE
)
```

Arguments:

xml an object of class [XMLInternalNode-class](#) to initialize from XML
 value value
 schema schema
 mimeType mime type
 serviceVersion WPS service version
 cdata whether value has to be wrapped in a XML CDATA. Default is TRUE

Method [decode\(\)](#): Decodes an object of class [WPSComplexData](#) from XML

Usage:

```
WPSComplexData$decode(xml)
```

Arguments:

xml an object of class [XMLInternalNode-class](#) to initialize from XML

Method `checkValidity()`: Check the object against a parameter description inherited from a WPS process description, object of class `WPSComplexInputDescription`. If not valid, the function will raise an error.

Usage:

```
WPSComplexData$checkValidity(parameterDescription)
```

Arguments:

`parameterDescription` object of class [WPSComplexInputDescription](#)

Returns: an error if not valid

Method `getFeatures()`: Get features

Usage:

```
WPSComplexData$getFeatures()
```

Returns: object of class `sf`

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WPSComplexData$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSComplexInputDescription

WPSComplexInputDescription

Description

WPSComplexInputDescription

WPSComplexInputDescription

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process complex input description

Super classes

```
ows4R::OGCAbstractObject -> ows4R::WPSParameter -> ows4R::WPSDescriptionParameter  
-> ows4R::WPSInputDescription -> WPSComplexInputDescription
```

Methods**Public methods:**

- [WPSComplexInputDescription\\$new\(\)](#)
- [WPSComplexInputDescription\\$clone\(\)](#)

Method `new()`: Initializes a [WPSComplexInputDescription](#)

Usage:

```
WPSComplexInputDescription$new(xml = NULL, version, logger = NULL, ...)
```

Arguments:

`xml` object of class [XMLInternalNode-class](#) from **XML**

`version` WPS service version

`logger` logger

... any other parameter

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WPSComplexInputDescription$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSComplexOutputDescription

WPSComplexOutputDescription

Description

WPSComplexOutputDescription

WPSComplexOutputDescription

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process complex input description

Super classes

`ows4R::OGCAbstractObject` -> `ows4R::WPSParameter` -> `ows4R::WPSDescriptionParameter`
-> `ows4R::WPSOutputDescription` -> `WPSComplexOutputDescription`

Methods**Public methods:**

- `WPSComplexOutputDescription$new()`
- `WPSComplexOutputDescription$clone()`

Method `new()`: Initializes a `WPSComplexOutputDescription`

Usage:

`WPSComplexOutputDescription$new(xml = NULL, version, logger = NULL, ...)`

Arguments:

`xml` object of class `XMLInternalNode-class` from `XML`

`version` WPS service version

`logger` logger

`...` any other parameter

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`WPSComplexOutputDescription$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by `ows4R`

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSDescribeProcess *WPSDescribeProcess*

Description

WPSDescribeProcess

WPSDescribeProcess

Format

`R6Class` object.

Value

Object of [R6Class](#) for modelling a WPS DescribeProcess request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> WPSDescribeProcess

Methods**Public methods:**

- [WPSDescribeProcess\\$new\(\)](#)
- [WPSDescribeProcess\\$clone\(\)](#)

Method new(): Initializes a [WPSDescribeProcess](#) service request

Usage:

```
WPSDescribeProcess$new(
  capabilities,
  op,
  url,
  serviceVersion,
  identifier,
  user = NULL,
  pwd = NULL,
  token = NULL,
  headers = c(),
  config = httr::config(),
  logger = NULL,
  ...
)
```

Arguments:

capabilities object of class [WPSCapabilities](#)

op object of class [OWSOperation](#)

url url

serviceVersion WPS service version

identifier process identifier

user user

pwd password

token token

headers headers

config config

logger logger

... any other parameter to pass to the request

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WPSDescribeProcess$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a WPS DescribeProcess request

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSDescriptionParameter

WPSDescriptionParameter

Description

WPSDescriptionParameter

WPSDescriptionParameter

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process input description parameter

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::WSPParameter](#) -> WPSDescriptionParameter

Methods

Public methods:

- [WPSDescriptionParameter\\$new\(\)](#)
- [WPSDescriptionParameter\\$getDataType\(\)](#)
- [WPSDescriptionParameter\\$getFormats\(\)](#)
- [WPSDescriptionParameter\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WPSDescriptionParameter](#)

Usage:

```
WPSDescriptionParameter$new(xml = NULL, version, logger = NULL, ...)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from XML
 version WPS service version
 logger logger
 ... any other parameter

Method `getDataType()`: Get data type

Usage:

`WPSExceptionParameter.getDataType()`

Returns: object of class character

Method `getFormats()`: get formats

Usage:

`WPSExceptionParameter.getFormats()`

Returns: the formats

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`WPSExceptionParameter.clone(deep = FALSE)`

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSException

WPSException

Description

WPSException

WPSException

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WPS Exception

Super class

[ows4R: :OGCAbstractObject](#) -> WPSEException

Public fields

value value

percentCompleted percent of completion

Methods**Public methods:**

- [WPSEException\\$new\(\)](#)
- [WPSEException\\$decode\(\)](#)
- [WPSEException\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WPSEException](#)

Usage:

```
WPSEException$new(xml = NULL, serviceVersion = "1.0.0")
```

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**
serviceVersion service version. Default "1.0.0"

Method [decode\(\)](#): Decodes an object of class [WPSEException](#) from XML

Usage:

```
WPSEException$decode(xml)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

```
WPSEException$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

 WPSExecute

WPSExecute

Description

WPSExecute

WPSExecute

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WPS Execute request

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::OWSHttpRequest](#) -> WPSExecute

Public fields

Identifier process identifier

DataInputs list of [WPSInput](#)

ResponseForm response form

Methods**Public methods:**

- [WPSExecute\\$new\(\)](#)
- [WPSExecute\\$getProcessDescription\(\)](#)
- [WPSExecute\\$clone\(\)](#)

Method new(): Initializes a [WPSExecute](#) service request

Usage:

```
WPSExecute$new(
  capabilities,
  op,
  url,
  serviceVersion,
  identifier,
  dataInputs = list(),
  responseForm = NULL,
  storeExecuteResponse = FALSE,
  lineage = NULL,
  status = NULL,
```

```

    user = NULL,
    pwd = NULL,
    token = NULL,
    headers = c(),
    config = httr::config(),
    logger = NULL,
    ...
)

```

Arguments:

capabilities object of class [WPSCapabilities](#)
op object of class [OWSOperation](#)
url url
serviceVersion WPS service version
identifier process identifier
dataInputs a named list of data inputs, objects of class [WPSLiteralData](#), [WPSComplexData](#)
or [WPSBoundingBoxData](#)
responseForm response form, object of class [WPSResponseDocument](#)
storeExecuteResponse store execute response? object of class logical. FALSE by default
lineage lineage, object of class logical
status status, object of class logical
user user
pwd password
token token
headers headers
config config
logger logger
... any other parameter to pass to the request

Method `getProcessDescription()`: Get process description

Usage:

```
WPSExecute$getProcessDescription()
```

Returns: an object of class [WPSProcessDescription](#)

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WPSExecute$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R** to trigger a WPS Execute request

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSExecuteResponse *WPSExecuteResponse*

Description

WPSExecuteResponse

WPSExecuteResponse

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WPS Execute response

Super class

[ows4R: :OGCAbstractObject](#) -> WPSExecuteResponse

Public fields

process process

status status

statusLocation status location

statusHistory status history

processOutputs process outputs

exception exception

Methods

Public methods:

- [WPSExecuteResponse\\$new\(\)](#)
- [WPSExecuteResponse\\$getProcess\(\)](#)
- [WPSExecuteResponse\\$getStatus\(\)](#)
- [WPSExecuteResponse\\$getStatusLocation\(\)](#)
- [WPSExecuteResponse\\$getStatusHistory\(\)](#)
- [WPSExecuteResponse\\$getProcessOutputs\(\)](#)
- [WPSExecuteResponse\\$getException\(\)](#)
- [WPSExecuteResponse\\$decode\(\)](#)
- [WPSExecuteResponse\\$update\(\)](#)
- [WPSExecuteResponse\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WPSExecuteResponse](#)

Usage:

```
WPSExecuteResponse$new(  
  xml,  
  capabilities,  
  processDescription = NULL,  
  logger = NULL  
)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**
capabilities object of class [WPSCapabilities](#)
processDescription process description
logger logger

Method `getProcess()`: Get process

Usage:

```
WPSExecuteResponse$getProcess()
```

Returns: an object of class [WPSProcess](#)

Method `getStatus()`: Get status

Usage:

```
WPSExecuteResponse$getStatus()
```

Returns: an object of class [WPSStatus](#)

Method `getStatusLocation()`: Get status location

Usage:

```
WPSExecuteResponse$getStatusLocation()
```

Returns: an object of class character

Method `getStatusHistory()`: Get status history

Usage:

```
WPSExecuteResponse$getStatusHistory()
```

Returns: an object of class character

Method `getProcessOutputs()`: Get list of process outputs

Usage:

```
WPSExecuteResponse$getProcessOutputs()
```

Returns: a list of outputs

Method `getException()`: Get exception

Usage:

```
WPSExecuteResponse$getException()
```

Returns: an object of class [WPSException](#)

Method `decode()`: Decodes an object of class [WPSExecuteResponse](#) from XML

Usage:

WPSExecuteResponse\$decode(xml, capabilities, processDescription, logger)

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**
 capabilities object of class [WPSCapabilities](#)
 processDescription process description
 logger logger

Method update(): Updates status history

Usage:

WPSExecuteResponse\$update(verbose = FALSE)

Arguments:

verbose verbose. Default is FALSE

Method clone(): The objects of this class are cloneable with this method.

Usage:

WPSExecuteResponse\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSFormat

WPSFormat

Description

WPSFormat

WPSFormat

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process input description

Super class

[ows4R::OGCAbstractObject](#) -> WPSFormat

Methods**Public methods:**

- [WPSFormat\\$new\(\)](#)
- [WPSFormat\\$getMimeType\(\)](#)
- [WPSFormat\\$getEncoding\(\)](#)
- [WPSFormat\\$getSchema\(\)](#)
- [WPSFormat\\$setIsDefault\(\)](#)
- [WPSFormat\\$isDefault\(\)](#)
- [WPSFormat\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WPSFormat](#)

Usage:

```
WPSFormat$new(xml = NULL, version, logger = NULL, ...)
```

Arguments:

xml an object of class [XMLInternalNode-class](#) to initialize from XML

version WPS service version

logger logger

... any additional parameter

Method [getMimeType\(\)](#): Get mime type

Usage:

```
WPSFormat$getMimeType()
```

Returns: object of class character

Method [getEncoding\(\)](#): Get encoding

Usage:

```
WPSFormat$getEncoding()
```

Returns: object of class character

Method [getSchema\(\)](#): Get schema

Usage:

```
WPSFormat$getSchema()
```

Returns: object of class character

Method [setIsDefault\(\)](#): set is default

Usage:

```
WPSFormat$setIsDefault(default)
```

Arguments:

default object of class logical

Method [isDefault\(\)](#): is default

Usage:

WPSFormat\$isDefault()

Returns: TRUE if default, FALSE otherwise

Method clone(): The objects of this class are cloneable with this method.

Usage:

WPSFormat\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSInput

WPSInput

Description

WPSInput

WPSInput

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WPS Input

Super class

[ows4R::OGCAbstractObject](#) -> WPSInput

Public fields

Identifier identifier

Data data

Methods

Public methods:

- [WPSInput\\$new\(\)](#)
- [WPSInput\\$clone\(\)](#)

Method `new()`: Initializes a [WPSInput](#)

Usage:

```
WPSInput$new(xml = NULL, identifier, data, serviceVersion = "1.0.0")
```

Arguments:

`xml` object of class [XMLInternalNode-class](#) from **XML**

`identifier` identifier

`data` data

`serviceVersion` service version. Default "1.0.0"

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WPSInput$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSInputDescription *WPSInputDescription*

Description

WPSInputDescription

WPSInputDescription

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process input description

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::WPSParameter](#) -> [ows4R::WPSDescriptionParameter](#)
-> [WPSInputDescription](#)

Methods**Public methods:**

- [WPSInputDescription\\$new\(\)](#)
- [WPSInputDescription\\$getMinOccurs\(\)](#)
- [WPSInputDescription\\$getMaxOccurs\(\)](#)
- [WPSInputDescription\\$asDataFrame\(\)](#)
- [WPSInputDescription\\$clone\(\)](#)

Method `new()`: Initializes a [WPSInputDescription](#)

Usage:

```
WPSInputDescription$new(xml = NULL, version, logger = NULL, ...)
```

Arguments:

`xml` object of class [XMLInternalNode-class](#) from [XML](#)

`version` WPS service version

`logger` logger

... any other parameter

Method `getMinOccurs()`: Get min occurs

Usage:

```
WPSInputDescription$getMinOccurs()
```

Returns: the min occurs

Method `getMaxOccurs()`: Get max occurs

Usage:

```
WPSInputDescription$getMaxOccurs()
```

Returns: the max occurs

Method `asDataFrame()`: Get input description as data.frame

Usage:

```
WPSInputDescription$asDataFrame()
```

Returns: object of class character

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WPSInputDescription$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSLiteralData	<i>WPSLiteralData</i>
----------------	-----------------------

Description

WPSLiteralData

WPSLiteralData

Format[R6Class](#) object.**Value**Object of [R6Class](#) for modelling a WPS Literal Data**Super class**[ows4R::OGCAbstractObject](#) -> WPSLiteralData**Public fields**

value value

Methods**Public methods:**

- [WPSLiteralData\\$new\(\)](#)
- [WPSLiteralData\\$decode\(\)](#)
- [WPSLiteralData\\$checkValidity\(\)](#)
- [WPSLiteralData\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WPSLiteralData](#)*Usage:*`WPSLiteralData$new(xml = NULL, value = NULL, serviceVersion = "1.0.0")`*Arguments:*xml an object of class [XMLInternalNode-class](#) to initialize from XML

value value

serviceVersion WPS service version

Method [decode\(\)](#): Decodes an object of class [WPSLiteralData](#) from XML*Usage:*`WPSLiteralData$decode(xml)`*Arguments:*xml an object of class [XMLInternalNode-class](#) to initialize from XML

Method `checkValidity()`: Check the object against a parameter description inherited from a WPS process description, object of class `WPSLiteralInputDescription`. If not valid, the function will raise an error.

Usage:

`WPSLiteralData$checkValidity(parameterDescription)`

Arguments:

`parameterDescription` object of class [WPSLiteralInputDescription](#)

Returns: an error if not valid

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`WPSLiteralData$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSLiteralInputDescription

WPSLiteralInputDescription

Description

WPSLiteralInputDescription

WPSLiteralInputDescription

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process input description

Super classes

`ows4R::OGCAbstractObject` -> `ows4R::WPSParameter` -> `ows4R::WPSDescriptionParameter`
-> `ows4R::WPSInputDescription` -> `WPSLiteralInputDescription`

Methods**Public methods:**

- [WPSLiteralInputDescription\\$new\(\)](#)
- [WPSLiteralInputDescription\\$getDataType\(\)](#)
- [WPSLiteralInputDescription\\$getDefaultValue\(\)](#)
- [WPSLiteralInputDescription\\$getAllowedValues\(\)](#)
- [WPSLiteralInputDescription\\$clone\(\)](#)

Method `new()`: Initializes a [WPSLiteralInputDescription](#)

Usage:

```
WPSLiteralInputDescription$new(xml = NULL, version, logger = NULL, ...)
```

Arguments:

`xml` object of class [XMLInternalNode-class](#) from [XML](#)

`version` WPS service version

`logger` logger

... any other parameter

Method `getDataType()`: Get data type

Usage:

```
WPSLiteralInputDescription$getDataType()
```

Returns: the data type, object of class character

Method `getDefaultValue()`: Get default value

Usage:

```
WPSLiteralInputDescription$getDefaultValue()
```

Returns: the default value, object of class character

Method `getAllowedValues()`: Get allowed values

Usage:

```
WPSLiteralInputDescription$getAllowedValues()
```

Returns: the allowed values

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WPSLiteralInputDescription$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSLiteralOutputDescription
WPSLiteralOutputDescription

Description

WPSLiteralOutputDescription
 WPSLiteralOutputDescription

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process literal output description

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::WPSParameter](#) -> [ows4R::WPSDescriptionParameter](#)
 -> [ows4R::WPSOutputDescription](#) -> WPSLiteralOutputDescription

Methods**Public methods:**

- [WPSLiteralOutputDescription\\$new\(\)](#)
- [WPSLiteralOutputDescription\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WPSLiteralOutputDescription](#)

Usage:

[WPSLiteralOutputDescription\\$new](#)(xml = NULL, version, logger = NULL, ...)

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**

version WPS service version

logger logger

... any other parameter

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

[WPSLiteralOutputDescription\\$clone](#)(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSOutput

WPSOutput

Description

WPSOutput

WPSOutput

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WPS Input

Super class

[ows4R::OGCAbstractObject](#) -> WPSOutput

Public fields

Identifier identifier

Title tile

Data data

Methods**Public methods:**

- [WPSOutput\\$new\(\)](#)
- [WPSOutput\\$decode\(\)](#)
- [WPSOutput\\$getData\(\)](#)
- [WPSOutput\\$getDataValue\(\)](#)
- [WPSOutput\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WPSOutput](#)

Usage:

```
WPSOutput$new(  
  xml = NULL,  
  identifier = NULL,  
  title = NULL,  
  data = NULL,  
  dataType = NULL,  
  serviceVersion = "1.0.0"  
)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**
identifier identifier
title title
data data
dataType data type
serviceVersion WPS service version

Method decode(): Decodes an object of class [WPSOutput](#) from **XML**

Usage:

```
WPSOutput$decode(xml)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**

Method getData(): Get data

Usage:

```
WPSOutput$getData()
```

Returns: data

Method getDataValue(): Get data value

Usage:

```
WPSOutput$getDataValue()
```

Returns: data value

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WPSOutput$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSOutputDescription *WPSOutputDescription*

Description

WPSOutputDescription

WPSOutputDescription

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process input description

Super classes

[ows4R::OGCAbstractObject](#) -> [ows4R::WPSParameter](#) -> [ows4R::WPSDescriptionParameter](#)
-> [WPSOutputDescription](#)

Methods**Public methods:**

- [WPSOutputDescription\\$new\(\)](#)
- [WPSOutputDescription\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WPSOutputDescription](#)

Usage:

[WPSOutputDescription\\$new](#)(xml = NULL, version, logger = NULL, ...)

Arguments:

xml object of class [XMLInternalNode-class](#) from [XML](#)

version WPS service version

logger logger

... any other parameter

Method [clone\(\)](#): The objects of this class are cloneable with this method.

Usage:

[WPSOutputDescription\\$clone](#)(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WSPParameter

WSPParameter

Description

WSPParameter

WSPParameter

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS parameter

Super class

[ows4R::OGCAbstractObject](#) -> WSPParameter

Methods**Public methods:**

- [WSPParameter\\$new\(\)](#)
- [WSPParameter\\$getIdentifier\(\)](#)
- [WSPParameter\\$getTitle\(\)](#)
- [WSPParameter\\$getAbstract\(\)](#)
- [WSPParameter\\$clone\(\)](#)

Method [new\(\)](#): Initializes an object of class [WSPParameter](#)

Usage:

```
WSPParameter$new(xml = NULL, version, logger = NULL, ...)
```

Arguments:

xml an object of class [XMLInternalNode-class](#) to initialize from XML

version WPS service version

logger logger

... any additional parameter

Method [getIdentifier\(\)](#): Get identifier

Usage:

```
WSPParameter$getIdentifier()
```

Returns: object of class character

Method getTitle(): Get title

Usage:

WSPParameter\$getTitle()

Returns: object of class character

Method getAbstract(): Get abstract

Usage:

WSPParameter\$getAbstract()

Returns: object of class character

Method clone(): The objects of this class are cloneable with this method.

Usage:

WSPParameter\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSProcess

WPSProcess

Description

WPSProcess

WPSProcess

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process

Super class

[ows4R::OGCAbstractObject](#) -> WPSProcess

Methods**Public methods:**

- [WPSProcess\\$new\(\)](#)
- [WPSProcess\\$getIdentifier\(\)](#)
- [WPSProcess\\$getTitle\(\)](#)
- [WPSProcess\\$getVersion\(\)](#)
- [WPSProcess\\$getDescription\(\)](#)
- [WPSProcess\\$execute\(\)](#)
- [WPSProcess\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WPSProcess](#)

Usage:

`WPSProcess$new(xml, capabilities = NULL, version, logger = NULL, ...)`

Arguments:

`xml` object of class [XMLInternalNode-class](#) from **XML**

`capabilities` object of class [WPSCapabilities](#)

`version` service version

`logger` logger

`...` any additional parameter

Method [getIdentifier\(\)](#): Get identifier

Usage:

`WPSProcess$getIdentifier()`

Returns: object of class character

Method [getTitle\(\)](#): Get title

Usage:

`WPSProcess$getTitle()`

Returns: object of class character

Method [getVersion\(\)](#): Get version

Usage:

`WPSProcess$getVersion()`

Returns: object of class character

Method [getDescription\(\)](#): Get description

Usage:

`WPSProcess$getDescription()`

Returns: object of class [WPSProcessDescription](#)

Method [execute\(\)](#): Execute process

Usage:


```

WSPProcess$execute(
  dataInputs = list(),
  responseForm = NULL,
  storeExecuteResponse = FALSE,
  lineage = NULL,
  status = NULL,
  update = FALSE,
  updateInterval = 1
)

```

Arguments:

`dataInputs` a named list of data inputs, objects of class [WPSLiteralData](#), [WPSComplexData](#) or [WPSBoundingBoxData](#)

`responseForm` response form, object of class [WPSResponseDocument](#)

`storeExecuteResponse` store execute response? object of class logical. FALSE by default

`lineage` lineage, object of class logical

`status` status, object of class logical

`update` update, object of class logical. For asynchronous requests

`updateInterval` update interval, object of class integer. For asynchronous requests

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
WSPProcess$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WSPProcessDescription *WSPProcessDescription*

Description

WSPProcessDescription

WSPProcessDescription

Format

[R6Class](#) object.

Value

Object of [R6Class](#) modelling a WPS process description

Super class

[ows4R::OGCAbstractObject](#) -> WPSProcessDescription

Methods**Public methods:**

- [WPSProcessDescription\\$new\(\)](#)
- [WPSProcessDescription\\$getIdentifier\(\)](#)
- [WPSProcessDescription\\$title\(\)](#)
- [WPSProcessDescription\\$getAbstract\(\)](#)
- [WPSProcessDescription\\$version\(\)](#)
- [WPSProcessDescription\\$isStatusSupported\(\)](#)
- [WPSProcessDescription\\$isStoreSupported\(\)](#)
- [WPSProcessDescription\\$getDataInputs\(\)](#)
- [WPSProcessDescription\\$getProcessOutputs\(\)](#)
- [WPSProcessDescription\\$asDataFrame\(\)](#)
- [WPSProcessDescription\\$clone\(\)](#)

Method new(): Initializes an object of class [WPSProcessDescription](#)

Usage:

```
WPSProcessDescription$new(xml, version, logger = NULL, ...)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from [XML](#)

version version

logger logger

... any other parameter

Method getIdentifier(): Get process identifier

Usage:

```
WPSProcessDescription$getIdentifier()
```

Returns: the identifier, object of class character

Method getTitle(): Get process title

Usage:

```
WPSProcessDescription$title()
```

Returns: the title, object of class character

Method getAbstract(): Get process abstract

Usage:

```
WPSProcessDescription$getAbstract()
```

Returns: the abstract, object of class character

Method getVersion(): Get process version

Usage:

WSPProcessDescription\$getVersion()

Arguments:

the version, object of class character

Method isStatusSupported(): Indicates if the status is supported

Usage:

WSPProcessDescription\$isStatusSupported()

Returns: TRUE if supported, FALSE otherwise

Method isStoreSupported(): Indicates if the store is supported

Usage:

WSPProcessDescription\$isStoreSupported()

Returns: TRUE if supported, FALSE otherwise

Method getDataInputs(): Get data inputs

Usage:

WSPProcessDescription\$getDataInputs()

Returns: a list of objects extending [WPSInputDescription](#)

Method getProcessOutputs(): Get process outputs

Usage:

WSPProcessDescription\$getProcessOutputs()

Returns: a list of objects extending [WPSOutputDescription](#)

Method asDataFrame(): Convenience method to export a process description as data.frame

Usage:

WSPProcessDescription\$asDataFrame()

Returns: a data.frame giving the process description

Method clone(): The objects of this class are cloneable with this method.

Usage:

WSPProcessDescription\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Class used internally by **ows4R**

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

WPSResponseDocument *WPSResponseDocument*

Description

WPSResponseDocument
 WPSResponseDocument

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an OGC WPS response document

Super class

[ows4R: :OGCAbstractObject](#) -> WPSResponseDocument

Public fields

Output output property

Methods

Public methods:

- [WPSResponseDocument\\$new\(\)](#)
- [WPSResponseDocument\\$clone\(\)](#)

Method [new\(\)](#): Initializes a [WPSResponseDocument](#)

Usage:

```
WPSResponseDocument$new(
  xml = NULL,
  storeExecuteResponse = FALSE,
  lineage = NULL,
  status = NULL,
  output = NULL,
  serviceVersion = "1.0.0"
)
```

Arguments:

xml object of class [XMLInternalNode-class](#) from **XML**
 storeExecuteResponse store execute response, object of class logical
 lineage lineage, object of class logical
 status status, object of class logical

output output
 serviceVersion WPS service version

Method clone(): The objects of this class are cloneable with this method.

Usage:

WPSResponseDocument\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

WPSStatus

WPSStatus

Description

WPSStatus

WPSStatus

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a WPS Status

Super class

[ows4R::OGCAbstractObject](#) -> WPSStatus

Public fields

value status value

percentCompleted status percentage of completion

Methods

Public methods:

- [WPSStatus\\$new\(\)](#)
- [WPSStatus\\$decode\(\)](#)
- [WPSStatus\\$getValue\(\)](#)
- [WPSStatus\\$getPercentCompleted\(\)](#)
- [WPSStatus\\$getCreationTime\(\)](#)

- [WPSStatus\\$clone\(\)](#)

Method new(): Initializes a [WPSStatus](#) object

Usage:

```
WPSStatus$new(xml = NULL, serviceVersion = "1.0.0")
```

Arguments:

xml an object of class [XMLInternalNode-class](#) from **XML**
serviceVersion WPS service version. Default is "1.0.0"

Method decode(): Decodes WPS status from XML

Usage:

```
WPSStatus$decode(xml)
```

Arguments:

xml an object of class [XMLInternalNode-class](#) from **XML**

Method getValue(): Get status value, among accepted WPS status values defined in the WPS standard: ProcessAccepted, ProcessStarted, ProcessPaused, ProcessSucceeded, ProcessFailed.

Usage:

```
WPSStatus$getValue()
```

Returns: value, object of class character

Method getPercentCompleted(): Get percentage of completion

Usage:

```
WPSStatus$getPercentCompleted()
```

Returns: the percentage of completion, object of class integer

Method getCreationTime(): Get creation time

Usage:

```
WPSStatus$getCreationTime()
```

Returns: the creation time, object of class POSIXct

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
WPSStatus$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Index

- * **Abstract**
 - OGCAbstractObject, 32
- * **And**
 - And, 4
- * **Authentication**
 - CASClient, 9
- * **BBOX**
 - BBOX, 5
- * **BinaryComparisonOpType**
 - BinaryComparisonOpType, 6
 - PropertyIsEqualTo, 67
 - PropertyIsGreaterThan, 68
 - PropertyIsGreaterThanOrEqualTo, 69
 - PropertyIsLessThan, 70
 - PropertyIsLessThanOrEqualTo, 71
 - PropertyIsNotEqualTo, 74
- * **BinaryLogicOpType**
 - And, 4
 - BinaryLogicOpType, 7
 - Or, 39
- * **Bounding**
 - WPSBoundingBoxData, 127
- * **Box**
 - WPSBoundingBoxData, 127
- * **CAS**
 - CASClient, 9
- * **CSW**
 - CSWCapabilities, 10
 - CSWClient, 11
 - CSWDescribeRecord, 18
 - CSWGetRecordById, 20
 - CSWGetRecords, 21
 - CSWHarvest, 23
 - CSWRecordProperty, 27
 - CSWTransaction, 29
- * **Capabilities**
 - CSWCapabilities, 10
 - WPSCapabilities, 128
- * **Central**
 - CASClient, 9
- * **CodeType**
 - OWSCodeType, 48
- * **Common**
 - OWSClient, 45
- * **ComplexData**
 - WPSComplexData, 133
- * **Coverage**
 - WCSCoverage, 83
 - WCSCoverageDescription, 85
 - WCSCoverageDomain, 87
 - WCSCoverageSpatialDomain, 89
 - WCSCoverageSummary, 91
 - WCSCoverageTemporalDomain, 95
 - WCSGridCRS, 100
- * **DescribeCoverage**
 - WCSDescribeCoverage, 96
- * **DescribeFeatureType**
 - WFSDescribeFeatureType, 108
- * **DescribeProcess**
 - WPSDescribeProcess, 137
- * **DescribeRecord**
 - CSWDescribeRecord, 18
- * **Exception**
 - WPSException, 140
- * **ExecuteResponse**
 - WPSExecuteResponse, 144
- * **Execute**
 - WPSExecute, 142
- * **Expression**
 - And, 4
 - BBOX, 5
 - BinaryComparisonOpType, 6
 - BinaryLogicOpType, 7
 - Not, 31
 - OGCExpression, 36
 - Or, 39
 - PropertyIsBetween, 66

- PropertyIsEqualTo, [67](#)
- PropertyIsGreaterThan, [68](#)
- PropertyIsGreaterThanOrEqualTo, [69](#)
- PropertyIsLessThan, [70](#)
- PropertyIsLessThanOrEqualTo, [71](#)
- PropertyIsLike, [73](#)
- PropertyIsNotEqualTo, [74](#)
- PropertyIsNull, [75](#)
- UnaryLogicOpType, [77](#)
- * **FeatureType**
 - WFSFeatureType, [109](#)
 - WFSFeatureTypeElement, [113](#)
- * **Feature**
 - WFSClient, [105](#)
- * **Filter**
 - CSWConstraint, [17](#)
 - OGCFilter, [37](#)
- * **GeoServer**
 - WCSGSElevationDomain, [101](#)
 - WCSGSTimeDomain, [102](#)
- * **GetCapabilities**
 - OWSCapabilities, [42](#)
 - OWSGetCapabilities, [50](#)
 - WCSCapabilities, [79](#)
 - WFSCapabilities, [104](#)
 - WMSCapabilities, [116](#)
- * **GetCoverage**
 - WCSGetCoverage, [98](#)
- * **GetFeatureInfo**
 - WMSClient, [118](#)
 - WMSGetFeatureInfo, [121](#)
- * **GetFeature**
 - WFSGetFeature, [115](#)
- * **GetRecordById**
 - CSWGetRecordById, [20](#)
- * **GetRecords**
 - CSWGetRecords, [21](#)
- * **HTTP**
 - OWSHttpRequest, [52](#)
- * **Harvest**
 - CSWHarvest, [23](#)
- * **Identification**
 - OWSServiceIdentification, [60](#)
- * **Input**
 - WPSInput, [148](#)
 - WPSOutput, [155](#)
- * **Layer**
 - WMSLayer, [123](#)
- * **LiteralData**
 - WPSLiteralData, [151](#)
- * **Map**
 - WMSClient, [118](#)
- * **Not**
 - Not, [31](#)
- * **OGC**
 - And, [4](#)
 - BBOX, [5](#)
 - BinaryComparisonOpType, [6](#)
 - BinaryLogicOpType, [7](#)
 - CSWCapabilities, [10](#)
 - CSWClient, [11](#)
 - CSWConstraint, [17](#)
 - CSWDescribeRecord, [18](#)
 - CSWGetRecordById, [20](#)
 - CSWGetRecords, [21](#)
 - CSWHarvest, [23](#)
 - CSWQuery, [25](#)
 - CSWTransaction, [29](#)
 - Not, [31](#)
 - OGCAbstractObject, [32](#)
 - OGCExpression, [36](#)
 - OGCFilter, [37](#)
 - Or, [39](#)
 - OWSBoundingBox, [40](#)
 - OWSCapabilities, [42](#)
 - OWSClient, [45](#)
 - OWSException, [49](#)
 - OWSGetCapabilities, [50](#)
 - OWSHttpRequest, [52](#)
 - OWSOperation, [56](#)
 - OWSOperationsMetadata, [58](#)
 - OWSRequest, [59](#)
 - OWSServiceIdentification, [60](#)
 - OWSServiceProvider, [62](#)
 - OWSUtils, [64](#)
 - OWSWGSS84BoundingBox, [65](#)
 - PropertyIsBetween, [66](#)
 - PropertyIsEqualTo, [67](#)
 - PropertyIsGreaterThan, [68](#)
 - PropertyIsGreaterThanOrEqualTo, [69](#)
 - PropertyIsLessThan, [70](#)
 - PropertyIsLessThanOrEqualTo, [71](#)
 - PropertyIsLike, [73](#)
 - PropertyIsNotEqualTo, [74](#)
 - PropertyIsNull, [75](#)
 - UnaryLogicOpType, [77](#)

- WCSCapabilities, 79
- WCSClient, 80
- WCSCoverage, 83
- WCSCoverageDescription, 85
- WCSCoverageDomain, 87
- WCSCoverageSpatialDomain, 89
- WCSCoverageSummary, 91
- WCSCoverageTemporalDomain, 95
- WCSDescribeCoverage, 96
- WCSGetCoverage, 98
- WCSGridCRS, 100
- WFSCapabilities, 104
- WFSClient, 105
- WFSDescribeFeatureType, 108
- WFSFeatureType, 109
- WFSFeatureTypeElement, 113
- WFSGetFeature, 115
- WMSCapabilities, 116
- WMSClient, 118
- WMSGetFeatureInfo, 121
- WMSLayer, 123
- WPSBoundingBoxData, 127
- WPSCapabilities, 128
- WPSClient, 130
- WPSComplexData, 133
- WPSComplexInputDescription, 135
- WPSComplexOutputDescription, 136
- WPSDescribeProcess, 137
- WPSDescriptionParameter, 139
- WPSException, 140
- WPSExecute, 142
- WPSExecuteResponse, 144
- WPSFormat, 146
- WPSInput, 148
- WPSInputDescription, 149
- WPSLiteralData, 151
- WPSLiteralInputDescription, 152
- WPSLiteralOutputDescription, 154
- WPSOutput, 155
- WPSOutputDescription, 157
- WPSParameter, 158
- WPSProcess, 159
- WPSProcessDescription, 161
- WPSResponseDocument, 164
- WPSStatus, 165
- * **OWS**
 - OWSBoundingBox, 40
 - OWSCapabilities, 42
 - OWSClient, 45
 - OWSCodeType, 48
 - OWSHttpRequest, 52
 - OWSNamespace, 55
 - OWSOperation, 56
 - OWSOperationsMetadata, 58
 - OWSServiceIdentification, 60
 - OWSServiceProvider, 62
 - OWSUtils, 64
 - OWSWG84BoundingBox, 65
 - * **Object**
 - OGCAbstractObject, 32
 - * **Or**
 - Or, 39
 - * **Parameter**
 - WPSParameter, 158
 - * **ProcessDescription**
 - WPSProcessDescription, 161
 - * **Processing**
 - WPSClient, 130
 - * **Process**
 - WPSClient, 130
 - WPSComplexInputDescription, 135
 - WPSComplexOutputDescription, 136
 - WPSDescriptionParameter, 139
 - WPSFormat, 146
 - WPSInputDescription, 149
 - WPSLiteralInputDescription, 152
 - WPSLiteralOutputDescription, 154
 - WPSOutputDescription, 157
 - WPSProcess, 159
 - WPSProcessDescription, 161
 - * **PropertyIsBetween**
 - PropertyIsBetween, 66
 - * **PropertyIsEqualTo**
 - PropertyIsEqualTo, 67
 - * **PropertyIsGreaterThanOrEqualTo**
 - PropertyIsGreaterThanOrEqualTo, 69
 - * **PropertyIsGreaterThan**
 - PropertyIsGreaterThan, 68
 - * **PropertyIsLessThan**
 - PropertyIsLessThan, 70
 - * **PropertyIsLesserThanOrEqualTo**
 - PropertyIsLessThanOrEqualTo, 71
 - * **PropertyIsLike**
 - PropertyIsLike, 73
 - * **PropertyIsNotEqualTo**
 - PropertyIsNotEqualTo, 74

- * **PropertyIsNull**
 - PropertyIsNull, 75
- * **Provider**
 - OWSServiceProvider, 62
- * **Query**
 - CSWQuery, 25
- * **RecordProperty**
 - CSWRecordProperty, 27
- * **Request**
 - OWSHttpRequest, 52
 - OWSRequest, 59
- * **ResponseDocument**
 - WPSResponseDocument, 164
- * **Service**
 - CASClient, 9
 - OWSRequest, 59
 - OWSServiceIdentification, 60
 - OWSServiceProvider, 62
- * **Status**
 - WPSStatus, 165
- * **Transaction**
 - CSWTransaction, 29
- * **UnaryLogicOpType**
 - Not, 31
 - UnaryLogicOpType, 77
- * **Utils**
 - OWSUtils, 64
- * **WCS**
 - WCSCapabilities, 79
 - WCSClient, 80
 - WCSCoverage, 83
 - WCSCoverageDescription, 85
 - WCSCoverageDomain, 87
 - WCSCoverageSpatialDomain, 89
 - WCSCoverageSummary, 91
 - WCSCoverageTemporalDomain, 95
 - WCSDescribeCoverage, 96
 - WCSGetCoverage, 98
 - WCSGridCRS, 100
 - WCSGSElevationDomain, 101
 - WCSGSTimeDomain, 102
- * **WFS**
 - WFSCapabilities, 104
 - WFSClient, 105
 - WFSDescribeFeatureType, 108
 - WFSFeatureType, 109
 - WFSFeatureTypeElement, 113
 - WFSGetFeature, 115
- * **WMS**
 - WMSCapabilities, 116
 - WMSClient, 118
 - WMSGetFeatureInfo, 121
 - WMSLayer, 123
- * **WPS**
 - WPSBoundingBoxData, 127
 - WPSCapabilities, 128
 - WPSClient, 130
 - WPSComplexData, 133
 - WPSComplexInputDescription, 135
 - WPSComplexOutputDescription, 136
 - WPSDescribeProcess, 137
 - WPSDescriptionParameter, 139
 - WPSException, 140
 - WPSExecute, 142
 - WPSExecuteResponse, 144
 - WPSFormat, 146
 - WPSInput, 148
 - WPSInputDescription, 149
 - WPSLiteralData, 151
 - WPSLiteralInputDescription, 152
 - WPSLiteralOutputDescription, 154
 - WPSOutput, 155
 - WPSOutputDescription, 157
 - WPSParameter, 158
 - WPSProcess, 159
 - WPSProcessDescription, 161
 - WPSResponseDocument, 164
 - WPSStatus, 165
- * **boundingbox**
 - OWSBoundingBox, 40
 - OWSWG84BoundingBox, 65
- * **catalogue**
 - CSWClient, 11
- * **complex**
 - WPSComplexInputDescription, 135
 - WPSComplexOutputDescription, 136
- * **crs**
 - WCSGridCRS, 100
- * **data**
 - WPSBoundingBoxData, 127
- * **description**
 - WPSComplexInputDescription, 135
 - WPSComplexOutputDescription, 136
 - WPSDescriptionParameter, 139
 - WPSFormat, 146
 - WPSInputDescription, 149

- WPSLiteralInputDescription, 152
- WPSLiteralOutputDescription, 154
- WPSOutputDescription, 157
- * **domain**
 - WCSCoverageDomain, 87
 - WCSCoverageSpatialDomain, 89
 - WCSCoverageTemporalDomain, 95
 - WCSGSElevationDomain, 101
 - WCSGSTimeDomain, 102
- * **elevation**
 - WCSGSElevationDomain, 101
- * **exception**
 - OWSException, 49
- * **grid**
 - WCSGridCRS, 100
- * **input**
 - WPSComplexInputDescription, 135
 - WPSDescriptionParameter, 139
 - WPSFormat, 146
 - WPSInputDescription, 149
 - WPSLiteralInputDescription, 152
- * **literal**
 - WPSLiteralOutputDescription, 154
- * **metadata**
 - OWSOperationsMetadata, 58
- * **namespace**
 - OWSNamespace, 55
- * **operation**
 - OWSOperation, 56
 - OWSOperationsMetadata, 58
- * **output**
 - WPSComplexOutputDescription, 136
 - WPSLiteralOutputDescription, 154
 - WPSOutputDescription, 157
- * **parameter**
 - WPSDescriptionParameter, 139
- * **service**
 - CSWClient, 11
- * **spatial**
 - WCSCoverageSpatialDomain, 89
- * **temporal**
 - WCSCoverageTemporalDomain, 95
- * **time**
 - WCSGSTimeDomain, 102
- * **web**
 - CSWClient, 11
- * **wgs84**
 - OWSWGSS84BoundingBox, 65
- And, 4, 4
- BBOX, 5, 5
- BinaryComparisonOpType, 6, 7
- BinaryLogicOpType, 7, 8
- CASClient, 9, 9
- character, 112
- CSWCapabilities, 10, 11, 13, 19, 21, 22, 24, 29
- CSWClient, 11, 11
- CSWConstraint, 14, 15, 17, 17, 26
- CSWDescribeRecord, 13, 18, 19
- CSWGetRecordById, 13, 20, 20, 22
- CSWGetRecords, 14, 21
- CSWHarvest, 23, 24
- CSWQuery, 14, 16, 22, 25
- CSWRecordProperty, 14, 15, 27, 28
- CSWTransaction, 14, 29, 29
- geometa::geometaLogger, 85, 102, 103
- geometa::GMLAbstractCoverage, 85
- geometa::GMLAbstractFeature, 85
- geometa::GMLAbstractObject, 85
- geometa::GMLCOVAbstractCoverage, 85
- geometa::ISOAbstractObject, 85, 102, 103
- getOWSNamespace, 30
- getOWSNamespace, 31
- GMLEnvelope, 5, 90
- GMLEnvelopeWithTimePeriod, 90
- GMLGrid, 90
- GMLRectifiedGrid, 90
- GMLTimePeriod, 96
- integer, 112
- ISOResponsibleParty, 63
- logical, 112
- mclapply, 112
- Not, 31, 32
- OGCAbstractObject, 32, 34
- OGCExpression, 4, 8, 32, 36, 36, 38, 39, 78
- OGCFilter, 17, 37, 38
- Or, 39, 39
- ows4R, 40
- ows4R-package (ows4R), 40

- ows4R::BinaryComparisonOpType, *67–69, 71, 72, 74*
- ows4R::BinaryLogicOpType, *4, 39*
- ows4R::OGCAbstractObject, *4–6, 8, 10, 12, 17, 18, 20, 22, 23, 25, 28, 29, 31, 36, 38, 39, 41, 42, 45, 48–50, 52, 59, 65–69, 71–74, 76, 77, 79, 80, 83, 87, 90, 91, 95, 96, 98, 100, 104, 105, 108, 110, 115, 116, 118, 122, 123, 127, 128, 131, 134, 135, 137–139, 141, 142, 144, 146, 148, 149, 151, 152, 154, 155, 157–159, 162, 164, 165*
- ows4R::OGCExpression, *4–6, 8, 31, 39, 66–69, 71–74, 76, 77*
- ows4R::OWSBoundingBox, *65, 127*
- ows4R::OWSCapabilities, *10, 79, 104, 116, 128*
- ows4R::OWSClient, *12, 80, 105, 118, 131*
- ows4R::OWSHttpRequest, *18, 20, 22, 23, 29, 50, 96, 98, 108, 115, 122, 138, 142*
- ows4R::UnaryLogicOpType, *31*
- ows4R::WPSDescriptionParameter, *135, 137, 149, 152, 154, 157*
- ows4R::WPSInputDescription, *135, 152*
- ows4R::WPSOutputDescription, *137, 154*
- ows4R::WPSParameter, *135, 137, 139, 149, 152, 154, 157*
- OWSBoundingBox, *40, 41, 65, 90, 93*
- OWSCapabilities, *42, 43, 46, 53, 59*
- OWSClient, *43, 45*
- OWSCodeType, *48, 48*
- OWSException, *49, 49*
- OWSGetCapabilities, *11, 43, 44, 50, 51, 79, 104, 117, 129*
- OWSHttpRequest, *52*
- OWSNamespace, *55, 55*
- OWSOperation, *19, 21, 22, 24, 30, 53, 56, 56, 58, 97, 99, 109, 115, 122, 138, 143*
- OWSOperationsMetadata, *44, 58, 58*
- OWSRequest, *59, 59, 117*
- OWSServiceIdentification, *44, 60, 61*
- OWSServiceProvider, *44, 62, 63*
- OWSUtils, *64*
- OWSWG84BoundingBox, *65, 93*
- PropertyIsBetween, *66*
- PropertyIsEqualTo, *67, 67*
- PropertyIsGreaterThan, *68, 68*
- PropertyIsGreaterThanOrEqualTo, *69, 70*
- PropertyIsLessThan, *70, 71*
- PropertyIsLessThanOrEqualTo, *71, 72*
- PropertyIsLike, *66, 73, 73, 76*
- PropertyIsNotEqualTo, *74, 75*
- PropertyIsNull, *75*
- R6Class, *4–6, 8–11, 17, 18, 20–23, 25, 27, 29, 31, 32, 36, 37, 39–42, 45, 48–50, 52, 55, 56, 58–60, 62, 64–70, 72–75, 77, 79, 80, 83, 85, 87, 89, 91, 95, 96, 98, 100–105, 108, 110, 113, 115, 116, 118, 121, 123, 127, 128, 131, 133–140, 142, 144, 146, 148, 149, 151, 152, 154, 155, 157–159, 161, 162, 164, 165*
- registerOWSNamespace, *76*
- setOWSNamespace, *77*
- stack, *94*
- UnaryLogicOpType, *77, 78*
- WSCCapabilities, *79, 79, 81, 92, 97, 99*
- WCSClient, *79, 80, 81*
- WCSCoverage, *83, 84*
- WCSCoverageDescription, *82, 85, 86, 93*
- WCSCoverageDomain, *87, 88, 90*
- WCSCoverageFilenameHandler, *89, 94*
- WCSCoverageSpatialDomain, *88, 89*
- WCSCoverageSummary, *79, 91, 92, 99*
- WCSCoverageTemporalDomain, *88, 95, 95*
- WCSDescribeCoverage, *96, 97*
- WCSGetCoverage, *83, 94, 98, 98*
- WCSGridCRS, *91, 100, 101*
- WCSGSElevationDomain, *101*
- WCSGSTimeDomain, *102*
- WFSCapabilities, *104, 104, 106, 109, 110, 115*
- WFSCClient, *105, 106*
- WFSDescribeFeatureType, *108, 108*
- WFSFeatureType, *105, 107, 109, 110*
- WFSFeatureTypeElement, *107, 111, 113, 113*
- WFSGetFeature, *107, 112, 115, 115*
- WMSCapabilities, *116, 117, 119, 122, 124*
- WMSClient, *118, 119*
- WMSGetFeatureInfo, *120, 121, 122, 126*
- WMSLayer, *117, 120, 123, 124*
- WPSBoundingBoxData, *127, 127, 130, 133, 143, 161*

WPSCapabilities, [128](#), [129](#), [132](#), [138](#), [143](#),
[145](#), [146](#), [160](#)
WPSClient, [129](#), [130](#), [131](#)
WPSComplexData, [130](#), [133](#), [133](#), [134](#), [143](#), [161](#)
WPSComplexInputDescription, [135](#), [135](#),
[136](#)
WPSComplexOutputDescription, [136](#), [137](#)
WPSDescribeProcess, [137](#), [138](#)
WPSDescriptionParameter, [139](#), [139](#)
WPSException, [140](#), [141](#), [145](#)
WPSExecute, [142](#), [142](#)
WPSExecuteResponse, [144](#), [144](#), [145](#)
WPSFormat, [146](#), [147](#)
WPSInput, [142](#), [148](#), [149](#)
WPSInputDescription, [149](#), [150](#), [163](#)
WPSLiteralData, [130](#), [133](#), [143](#), [151](#), [151](#), [161](#)
WPSLiteralInputDescription, [152](#), [152](#),
[153](#)
WPSLiteralOutputDescription, [154](#), [154](#)
WPSOutput, [155](#), [155](#), [156](#)
WPSOutputDescription, [157](#), [157](#), [163](#)
WPSParameter, [158](#), [158](#)
WPSProcess, [145](#), [159](#), [160](#)
WPSProcessDescription, [129](#), [132](#), [143](#), [160](#),
[161](#), [162](#)
WPSResponseDocument, [130](#), [133](#), [143](#), [161](#),
[164](#), [164](#)
WPSStatus, [145](#), [165](#), [166](#)

XMLInternalNode-class, [34](#), [35](#), [41](#), [48](#), [49](#),
[57–59](#), [61](#), [63](#), [65](#), [84](#), [86](#), [88](#), [90](#), [92](#),
[95](#), [101–103](#), [110](#), [113](#), [124](#), [128](#),
[134](#), [136](#), [137](#), [140](#), [141](#), [145–147](#),
[149–151](#), [153](#), [154](#), [156–158](#), [160](#),
[162](#), [164](#), [166](#)