

Package ‘pushbar’

October 14, 2022

Title Create Sliders for 'Shiny'

Version 0.1.0

Date 2019-03-13

Description Create sliders from left, right, top and bottom which may include any html or 'Shiny' input or output.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Imports shiny, jsonlite

RoxygenNote 6.1.1

URL <https://github.com/JohnCoene/pushbar>

BugReports <https://github.com/JohnCoene/pushbar/issues>

NeedsCompilation no

Author John Coene [aut, cre]

Maintainer John Coene <jcoenep@gmail.com>

Repository CRAN

Date/Publication 2019-03-15 17:11:22 UTC

R topics documented:

pushbar	2
pushbar-buttons	3
pushbar_style	3

Index	4
--------------	----------

pushbar

Setup Pushbar

Description

Set up pushbar.

Creates element containing pushbar content.

Usage

```
pushbar_deps()
```

```
setup_pushbar(blur = FALSE, overlay = TRUE)
```

```
pushbar(..., id = from, from = c("left", "right", "top", "bottom"),  
class = NULL, style = pushbar_style())
```

Arguments

blur	Whether to blur the background when pushbar is opened.
overlay	Whether to darken the background when pushbar is opened.
...	Any other valid tags .
id	Id of pushbar.
from	Wherefrom the pushbar should open.
class	Additional class to pass to div.
style	Valid css defaults to pushbar_style .

Details

Creates a div.

Note

You are advised to add padding inside your pushbar i.e.: `style="padding: 20px;"`

Examples

```
library(shiny)  
  
ui <- fluidPage(  
  pushbar_deps(),  
  actionButton("open", "Open pushbar"),  
  pushbar(  
    h4("HELLO")  
  )  
)
```

```
server <- function(input, output, session){  
  setup_pushbar()  
  observeEvent(input$open, {  
    pushbar_open()  
  })  
}  
  
if(interactive()) shinyApp(ui, server)
```

pushbar-buttons	<i>Pushbar Buttons</i>
-----------------	------------------------

Description

Open and close pushbar programatically.

Usage

```
pushbar_open(id = c("left", "right", "top", "bottom"))  
pushbar_close()
```

Arguments

id	Id of pushbar to open.
----	------------------------

pushbar_style	<i>Style</i>
---------------	--------------

Description

Default pushbar CSS, used in [pushbar](#).

Usage

```
pushbar_style()
```

Index

pushbar, [2](#), [3](#)
pushbar-buttons, [3](#)
pushbar_close (pushbar-buttons), [3](#)
pushbar_deps (pushbar), [2](#)
pushbar_open (pushbar-buttons), [3](#)
pushbar_style, [2](#), [3](#)

setup_pushbar (pushbar), [2](#)

tags, [2](#)