

btable


Enrico Schumann
es@enricoschumann.net

1 btable

btable creates a simple barplot in a \LaTeX tabular. As an example, add this to a Sweave file:

```
\begin{tabular}{ll}  
<<echo=false, results=tex>>=  
x <- 1:5  
cat(btable(x, before = paste(x, "&"), after= "\\ \\ \\n"))  
@  
\end{tabular}
```

The output should be:



2 dtable

```
> x <- array(1:6, dim = c(3, 2))
```

```
--  
--  
--
```

> toLatex(sessionInfo())

- R Under development (unstable) (2024-03-31 r86238), x86_64-pc-linux-gnu
- Locale: LC_CTYPE=en_US.UTF-8, LC_NUMERIC=C, LC_TIME=en_GB.UTF-8, LC_COLLATE=C, LC_MONETARY=en_GB.UTF-8, LC_MESSAGES=en_US.UTF-8, LC_PAPER=en_GB.UTF-8, LC_NAME=C, LC_ADDRESS=C, LC_TELEPHONE=C, LC_MEASUREMENT=en_GB.UTF-8, LC_IDENTIFICATION=C
- Time zone: Europe/Zurich
- TZcode source: system (glibc)
- Running under: Ubuntu 23.10
- Matrix products: default
- BLAS: /home/es19/R-inst/R-devel-build/lib/libRblas.so
- LAPACK: /home/es19/R-inst/R-devel-build/lib/libRlapack.so ; LAPACK version3.12.0
- Base packages: base, datasets, grDevices, graphics, methods, stats, utils
- Other packages: textutils 0.4-1
- Loaded via a namespace (and not attached): compiler 4.5.0, tools 4.5.0