

Package ‘massProps’

January 30, 2025

Title Calculate Mass Properties and Uncertainties of Tree Structures

Version 0.2.0

Description Recursively calculates mass properties (mass, center of mass, moments and products of inertia, and optionally, their uncertainties) for arbitrary decomposition trees. R. L. Zimmerman, J. H. Nakai. (2005) <<https://www.sawe.org/product/paper-3360/>>.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.3.2

Imports rollupTree (>= 0.1.0)

Depends R (>= 3.5)

LazyData true

Suggests igraph, knitr, rmarkdown, testthat (>= 3.0.0)

Config/testthat/edition 3

VignetteBuilder knitr

URL <https://jsjuni.github.io/massProps/>,
<https://github.com/jsjuni/massProps>

BugReports <https://github.com/jsjuni/massProps/issues>

NeedsCompilation no

Author James Steven Jenkins [aut, cre, cph]
(<<https://orcid.org/0000-0002-0725-0884>>)

Maintainer James Steven Jenkins <sjenkins@studioj.us>

Repository CRAN

Date/Publication 2025-01-30 19:00:05 UTC

Contents

combine_mass_props	2
combine_mass_props_and_unc	3
combine_mass_props_unc	4

get_mass_props	5
get_mass_props_and_unc	6
get_mass_props_unc	7
mp_table	7
mp_tree	8
rollup_mass_props	9
rollup_mass_props_and_unc	9
rollup_mass_props_and_unc_fast	10
rollup_mass_props_fast	11
rollup_mass_props_unc	12
rollup_mass_props_unc_fast	13
sawe_table	13
sawe_tree	15
set_mass_props	15
set_mass_props_and_unc	16
set_mass_props_unc	17
set_poi_conv_from_target	18
set_poi_conv_minus	18
set_poi_conv_plus	19
test_table	20
test_tree	20
update_mass_props	21
update_mass_props_and_unc	21
update_mass_props_unc	22
validate_mass_props	23
validate_mass_props_and_unc	24
validate_mass_props_and_unc_table	25
validate_mass_props_table	26
validate_mass_props_unc	26
Index	28

combine_mass_props	<i>Combine mass properties</i>
--------------------	--------------------------------

Description

combine_mass_props() calculates the mass properties of an aggregate from a list of constituent mass properties.

Usage

```
combine_mass_props(mpl)
```

Arguments

- `mpl` A list of mass properties lists, each of which contains the following named elements:
- `mass` Numeric mass.
 - `center_mass` Numeric 3-vector center of mass.
 - `point` Logical indicating point mass. The inertia of point masses is excluded from calculations.
 - `inertia` Numeric 3x3 matrix inertia tensor.

Details

See vignette("massProps", package = "massProps") for details on the algorithms employed.

Value

Combined mass properties list with the same named elements.

Examples

```
leaves <- names(igraph::neighbors(test_tree, "A.3", mode = "in"))
mpl <- Map(f = function(id) get_mass_props(test_table, id), leaves)
combine_mass_props(mpl)
```

combine_mass_props_and_unc

Combine mass properties and uncertainties

Description

`combine_mass_props_and_unc()` is a convenience wrapper that concatenates the results of `combine_mass_props()` and `combine_mass_props_unc()`.

Usage

```
combine_mass_props_and_unc(mpl)
```

Arguments

- `mpl` A list of mass properties and uncertainties lists, each of which contains the following named elements:
- `mass` Numeric mass.
 - `center_mass` Numeric 3-vector center of mass.
 - `point` Logical indicating point mass. The inertia of point masses is excluded from calculations.
 - `inertia` Numeric 3x3 matrix inertia tensor.

- `sigma_mass` mass uncertainty
- `sigma_center_mass` center of mass uncertainty (3-dimensional numeric)
- `sigma_inertia` Inertia tensor uncertainty (3x3 numeric matrix)

Value

Combined mass properties list with the same named elements.

Examples

```
leaves <- names(igraph::neighbors(sawe_tree, "Combined", mode = "in"))
mpl <- Map(f = function(id) get_mass_props_and_unc(sawe_table, id), leaves)
combine_mass_props_and_unc(mpl)
```

combine_mass_props_unc

Combine mass properties uncertainties

Description

`combine_mass_prop_unc()` calculates the mass properties uncertainties of an aggregate from the mass properties and uncertainties of its constituents and the mass properties of the aggregate.

Usage

```
combine_mass_props_unc(mpl, amp)
```

Arguments

- | | |
|------------------|---|
| <code>mpl</code> | <p>A list of mass properties and uncertainties lists, each of which contains the following named elements:</p> <ul style="list-style-type: none"> • <code>mass</code> Numeric mass. • <code>center_mass</code> Numeric 3-vector center of mass. • <code>point</code> Logical indicating point mass. The inertia of point masses is excluded from calculations. • <code>inertia</code> Numeric 3x3 matrix inertia tensor. • <code>sigma_mass</code> mass uncertainty • <code>sigma_center_mass</code> center of mass uncertainty (3-dimensional numeric) • <code>sigma_inertia</code> Inertia tensor uncertainty (3x3 numeric matrix) |
| <code>amp</code> | <p>A named list of mass properties for the aggregate containing the following named elements:</p> <ul style="list-style-type: none"> • <code>mass</code> Numeric mass. • <code>center_mass</code> Numeric 3-vector center of mass. • <code>point</code> Logical indicating point mass. The inertia of point masses is excluded from calculations. • <code>inertia</code> Numeric 3x3 matrix inertia tensor. |

Details

See vignette("massProps", package = "massProps") for details on the algorithms employed.

Value

The mass properties and uncertainties of the aggregate. A list with the same elements as members of `mpl`.

Examples

```
leaves <- names(igraph::neighbors(sawe_tree, "Combined", mode = "in"))
mpl <- Map(f = function(id) get_mass_props_and_unc(sawe_table, id), leaves)
combine_mass_props_unc(mpl, amp = get_mass_props(sawe_table, "Combined"))
```

<code>get_mass_props</code>	<i>Get mass properties for a row in a data frame</i>
-----------------------------	--

Description

`get_mass_props()` creates a mass properties list from a selected row in a data frame.

Usage

```
get_mass_props(df, id)
```

Arguments

<code>df</code>	A data frame with (at least) these columns: <code>id</code> , <code>mass</code> , <code>Cx</code> , <code>Cy</code> , <code>Cz</code> , <code>Ixx</code> , <code>Iyy</code> , <code>Izz</code> , <code>Ixy</code> , <code>Ixz</code> , <code>Iyz</code> , <code>POIconv</code> , <code>Ipoint</code> .
<code>id</code>	The <code>id</code> value of the desired row.

Value

A list with the following named elements:

- `mass` Numeric mass.
- `center_mass` Numeric 3-vector center of mass.
- `point` Logical indicating point mass. The inertia of point masses is excluded from calculations.
- `inertia` Numeric 3x3 matrix inertia tensor. The signs of the off-diagonal elements of the inertia tensor are determined by `POIconv`. For example, the xy element of the inertia tensor is `Ixy` if `POIconv` is "-"; it is `-Ixy` if `POIconv` is "+".

Examples

```
get_mass_props(mp_table, "C.1.1.2.2.3.1.1.2.3")
```

`get_mass_props_and_unc`*Get mass properties and uncertainties for a row in a data frame*

Description

`get_mass_props_and_unc()` is a convenience wrapper that combines the results of `get_mass_props()` and `get_mass_props_unc()`.

Usage

```
get_mass_props_and_unc(df, id)
```

Arguments

<code>df</code>	A data frame with (at least) these columns: <code>id</code> , <code>mass</code> , <code>Cx</code> , <code>Cy</code> , <code>Cz</code> , <code>Ixx</code> , <code>Iyy</code> , <code>Izz</code> , <code>Ixy</code> , <code>Ixz</code> , <code>Iyz</code> , <code>POIconv</code> , <code>Ipoint</code> , <code>sigma_mass</code> , <code>sigma_Cx</code> , <code>sigma_Cy</code> , <code>sigma_Cz</code> , <code>sigma_Ixy</code> , <code>sigma_Ixz</code> , <code>sigma_Iyz</code> .
<code>id</code>	The <code>id</code> value of the desired row.

Value

A list with the following named elements:

- `mass` Numeric mass.
- `center_mass` Numeric 3-vector center of mass.
- `point` Logical indicating point mass. The inertia of point masses is excluded from calculations.
- `inertia` Numeric 3x3 matrix inertia tensor. The signs of the off-diagonal elements of the inertia tensor are determined by `POIconv`. For example, the xy element of the inertia tensor is `Ixy` if `POIconv` is "-"; it is `-Ixy` if `POIconv` is "+".
- `sigma_mass` Numeric mass uncertainty.
- `sigma_center_mass` Numeric 3-vector center of mass uncertainties.
- `sigma_inertia` Numeric 3x3 matrix inertia tensor uncertainties.

Examples

```
get_mass_props_and_unc(mp_table, "C.1.1.2.2.3.1.2.3")
```

get_mass_props_unc *Get mass properties uncertainties for a row in a data frame*

Description

get_mass_props_unc() creates a mass properties uncertainties list from a selected row in a data frame.

Usage

```
get_mass_props_unc(df, id)
```

Arguments

df	A data frame with (at least) these columns: id, sigma_mass, sigma_Cx, sigma_Cy, sigma_Cz, sigma_Ixx, sigma_Iyy, sigma_Izz, sigma_Ixy, sigma_Ixz, sigma_Iyz.
id	The id value of the desired row.

Value

A list with the following named elements:

- sigma_mass Numeric mass uncertainty.
- sigma_center_mass Numeric 3-vector center of mass uncertainties.
- sigma_inertia Numeric 3x3 matrix inertia tensor uncertainties.

Examples

```
get_mass_props_unc(mp_table, "C.1.2.2.3.1.2.3")
```

mp_table *Example Mass Properties Table*

Description

Example Mass Properties Table

Usage

```
mp_table
```

Format

A data frame with columns:

id unique key

name character name

POIconv sign convention for products of inertia (one of c("+", "-"))

mass mass

Cx x -component of center of mass

Cy y -component of center of mass

Cz z -component of center of mass

Ixx I_{xx} moment of inertia

Iyy I_{yy} moment of inertia

Izz I_{zz} moment of inertia

Ixy I_{xy} product of inertia

Ixz I_{xz} product of inertia

Iyz I_{yz} product of inertia

Ipoint logical indicator to consider item a point mass, i.e., with negligible inertia

sigma_mass mass uncertainty

sigma_Cx x -component of center of mass uncertainty

sigma_Cy y -component of center of mass uncertainty

sigma_Cz z -component of center of mass uncertainty

sigma_Ixx I_{xx} moment of inertia uncertainty

sigma_Iyy I_{yy} moment of inertia uncertainty

sigma_Izz I_{zz} moment of inertia uncertainty

sigma_Ixy I_{xy} product of inertia uncertainty

sigma_Ixz I_{xz} product of inertia uncertainty

sigma_Iyz I_{yz} product of inertia uncertainty

mp_tree

Example Mass Properties Tree

Description

Example Mass Properties Tree

Usage

mp_tree

Format

An 'igraph' tree whose vertices are named as the values of the id column of a mass properties table and whose directed edges point from child id to parent id.

rollup_mass_props	<i>Roll up mass properties</i>
-------------------	--------------------------------

Description

'rollup_mass_props()' rolls up mass properties in a data frame such that the mass properties of each non-leaf vertex element is the aggregation of those of its child elements.

Usage

```
rollup_mass_props(tree, df, validate_df = validate_mass_props_table, ...)
```

Arguments

tree	An 'igraph' tree whose vertices are named as the values of the id column of df and whose directed edges point from child id to parent id.
df	A data frame with (at least) these columns: id, mass, Cx, Cy, Cz, Ixx, Iyy, Izz, Ixy, Ixz, Iyz, POIconv, Ipoint.
validate_df	A validator for the tree and table, default validate_mass_props_table()
...	Other parameters passed to rollupTree::rollup()

Value

The updated data frame

Examples

```
rollup_mass_props(mp_tree, mp_table)[1:100, ]
```

rollup_mass_props_and_unc	<i>Roll up mass properties and uncertainties</i>
---------------------------	--

Description

'rollup_mass_props_and_unc()' rolls up mass properties in a data frame with (at least) these columns: id, mass, Cx, Cy, Cz, Ixx, Iyy, Izz, Ixy, Ixz, Iyz, POIconv, Ipoint, sigma_mass, sigma_Cx, sigma_Cy, sigma_Cz, sigma_Ixx, sigma_Iyy, sigma_Izz, sigma_Ixy, sigma_Ixz, sigma_Iyz.

The difference between rollup_mass_props_unc() and rollup_mass_props_and_unc() is that rollup_mass_props_unc() expects the mass properties in its input to have been rolled up, whereas rollup_mass_props_and_unc() performs the mass properties rollup itself.

Usage

```
rollup_mass_props_and_unc(
  tree,
  df,
  validate_df = validate_mass_props_and_unc_table,
  ...
)
```

Arguments

tree	An 'igraph' tree whose vertices are named as the values of the id column of df and whose directed edges point from child id to parent id.
df	A data frame with (at least) these columns: id, mass, Cx, Cy, Cz, Ixx, Iyy, Izz, Ixy, Izx, Iyz, POIconv, Ipoint.
validate_df	A validator for the tree and table, default validate_mass_props_and_unc_table()
...	Other parameters passed to rollupTree::rollup()

Value

The updated data frame

Examples

```
rollup_mass_props_and_unc(mp_tree, mp_table)[1:100, ]
```

```
rollup_mass_props_and_unc_fast
```

Roll up mass properties and uncertainties without input validation

Description

rollup_mass_props_and_unc_fast() performs the same operation as rollup_mass_props_and_unc() but omits input validation. It is somewhat faster than rollup_mass_propss_and_unc() but should be used with caution and only under circumstances in which the caller assumes responsibility for validity of input. Its behavior when passed ill-formed input is unspecified.

Usage

```
rollup_mass_props_and_unc_fast(tree, df)
```

Arguments

tree	An 'igraph' tree whose vertices are named as the values of the id column of df and whose directed edges point from child id to parent id.
df	A data frame with (at least) these columns: id, mass, Cx, Cy, Cz, Ixx, Iyy, Izz, Ixy, Izx, Iyz, POIconv, Ipoint.

Value

The updated data frame

Examples

```
rollup_mass_props_and_unc_fast(sawe_tree, sawe_table)
```

```
rollup_mass_props_fast
```

Roll up mass properties without input validation

Description

`rollup_mass_props_fast()` performs the same operation as `rollup_mass_props()` but omits input validation. It is somewhat faster than `rollup_mass_props()` but should be used with caution and only under circumstances in which the caller assumes responsibility for validity of input. Its behavior when passed ill-formed input is unspecified.

Usage

```
rollup_mass_props_fast(tree, df)
```

Arguments

<code>tree</code>	An 'igraph' tree whose vertices are named as the values of the <code>id</code> column of <code>df</code> and whose directed edges point from child <code>id</code> to parent <code>id</code> .
<code>df</code>	A data frame with (at least) these columns: <code>id</code> , <code>mass</code> , <code>Cx</code> , <code>Cy</code> , <code>Cz</code> , <code>Ixx</code> , <code>Iyy</code> , <code>Izz</code> , <code>Ixy</code> , <code>Ixz</code> , <code>Iyz</code> , <code>POIconv</code> , <code>Ipoint</code> .

Value

The updated data frame

Examples

```
rollup_mass_props_fast(test_tree, test_table)
```

rollup_mass_props_unc *Roll up mass properties uncertainties*

Description

rollup_mass_props_unc() rolls up mass properties uncertainties in a data frame such that the uncertainties of each non-leaf vertex element is the aggregation of the mass properties and uncertainties of its child elements.

The difference between rollup_mass_props_unc() and rollup_mass_props_and_unc() is that rollup_mass_props_unc() expects the mass properties in its input to have been rolled up, whereas rollup_mass_props_and_unc() performs the mass properties rollup itself.

Usage

```
rollup_mass_props_unc(
  tree,
  df,
  validate_df = validate_mass_props_and_unc_table,
  ...
)
```

Arguments

tree	An 'igraph' tree whose vertices are named as the values of the id column of df and whose directed edges point from child id to parent id.
df	A data frame with (at least) these columns: id, mass, Cx, Cy, Cz, Ixx, Iyy, Izz, Ixy, Ixz, Iyz, POIconv, Ipoint.
validate_df	A validator for the tree and table, default validate_mass_props_and_unc_table()
...	Other parameters passed to rollupTree::rollup()

Value

The updated data frame

Examples

```
mp_ru <- rollup_mass_props(mp_tree, mp_table)
rollup_mass_props_unc(mp_tree, mp_ru)[1:100, ]
```

 rollup_mass_props_unc_fast

Roll up mass properties uncertainties without input validation

Description

rollup_mass_props_unc_fast() performs the same operation as rollup_mass_props_unc() but omits input validation. It is somewhat faster than rollup_mass_props_unc() but should be used with caution and only under circumstances in which the caller assumes responsibility for validity of input. Its behavior when passed ill-formed input is unspecified.

Usage

```
rollup_mass_props_unc_fast(tree, df)
```

Arguments

tree	An 'igraph' tree whose vertices are named as the values of the id column of df and whose directed edges point from child id to parent id.
df	A data frame with (at least) these columns: id, mass, Cx, Cy, Cz, Ixx, Iyy, Izz, Ixy, Ixz, Iyz, POIconv, Ipoint.

Value

The updated data frame

Examples

```
rollup_mass_props_unc_fast(sawe_tree, sawe_table)
```

 sawe_table

Mass Properties and Uncertainties Table from SAWE Paper No. 3360

Description

Mass Properties and Uncertainties Table from SAWE Paper No. 3360

Usage

```
sawe_table
```

Format

A data frame with columns:

id unique key

mass mass

Cx x component of center of mass

Cy y component of center of mass

Cz z component of center of mass

Ixx Ixx moment of inertia

Iyy Iyy moment of inertia

Izz Izz moment of inertia

Ixy Ixy product of inertia

Ixz Ixz product of inertia

Iyz Iyz product of inertia

sigma_mass mass uncertainty

sigma_Cx x component of center of mass uncertainty

sigma_Cy y component of center of mass uncertainty

sigma_Cz z component of center of mass uncertainty

sigma_Ixx Ixx moment of inertia uncertainty

sigma_Iyy Iyy moment of inertia uncertainty

sigma_Izz Izz moment of inertia uncertainty

sigma_Ixy Ixy product of inertia uncertainty

sigma_Ixz Ixz product of inertia uncertainty

sigma_Iyz Iyz product of inertia uncertainty

Ipoint logical indicator to consider item a point mass

POIconv sign convention for products of inertia (one of c("+", "-"))

Source

Zimmerman, Robert L., and John H. Nakai. 2005. "Are You Sure? Uncertainty in Mass Properties Engineering." In 64th Annual International Conference on Mass Properties Engineering, 123–60. Society of Allied Weight Engineers.

Note: the results for combined mass properties and uncertainties in the published example are accurate only within approximately 0.2%.

sawe_tree	<i>Mass Properties and Uncertainties Tree from SAWE Paper No. 3360</i>
-----------	--

Description

Mass Properties and Uncertainties Tree from SAWE Paper No. 3360

Usage

sawe_tree

Format

An igraph tree with edges from child id to parent id.

Source

Zimmerman, Robert L., and John H. Nakai. 2005. "Are You Sure? Uncertainty in Mass Properties Engineering." In 64th Annual International Conference on Mass Properties Engineering, 123–60. Society of Allied Weight Engineers.

set_mass_props	<i>Set mass properties for a row in a data frame</i>
----------------	--

Description

set_mass_props() sets mass properties for a specified row in a data frame.

Usage

set_mass_props(df, id, mp)

Arguments

df	A data frame with an id column.
id	The id value of the desired row.
mp	A list with the following named elements: <ul style="list-style-type: none"> • mass Numeric mass. • center_mass Numeric 3-vector center of mass. • point Logical indicating point mass. The inertia of point masses is excluded from calculations. • poi_conv Enumeration c("+", "-") indicating sign convention for products of inertia. • inertia Numeric 3x3 matrix inertia tensor. The signs of the products of inertia are determined by POIconv. For example, Ixy is the xy element of the inertia tensor if POIconv is "-"; it is the additive inverse of that value if POIconv is "+".

Value

The updated data frame with columns `id`, `mass`, `Cx`, `Cy`, `Cz`, `Ixx`, `Iyy`, `Izz`, `Ixy`, `Ixz`, `Iyz`, `POIconv`, `Ipoint`.

Examples

```
df <- data.frame(id = c("C.1.2.2.3.1.2.3", "C.1.2.2.3.2.1.1"))
mp <- get_mass_props(mp_table, "C.1.2.2.3.2.1.1")
mp$poi_conv = "+"
set_mass_props(df, "C.1.2.2.3.2.1.1", mp)
```

set_mass_props_and_unc

Set mass properties and uncertainties for a row in a data frame

Description

`set_mass_props_and_unc()` is a convenience wrapper that combines the results of `set_mass_props()` and `set_mass_props_unc()`.

Usage

```
set_mass_props_and_unc(df, id, mpu)
```

Arguments

- | | |
|------------------|--|
| <code>df</code> | A data frame with an <code>id</code> column. |
| <code>id</code> | The <code>id</code> value of the desired row. |
| <code>mpu</code> | A list containing the following named elements: <ul style="list-style-type: none"> • <code>mass</code> Numeric mass. • <code>center_mass</code> Numeric 3-vector center of mass. • <code>point</code> Logical indicating point mass. The inertia of point masses is excluded from calculations. • <code>poi_conv</code> Enumeration c("+", "-") indicating sign convention for products of inertia. • <code>inertia</code> Numeric 3x3 matrix inertia tensor. The signs of the products of inertia are determined by <code>POIconv</code>. For example, <code>Ixy</code> is the xy element of the inertia tensor if <code>POIconv</code> is "-"; it is the additive inverse of that value if <code>POIconv</code> is "+". • <code>sigma_mass</code> Numeric mass uncertainty. • <code>sigma_center_mass</code> Numeric 3-vector center of mass uncertainties. • <code>sigma_inertia</code> Numeric 3x3 matrix inertia tensor uncertainties. |

Value

The updated data frame.

Examples

```
mpu <- c(get_mass_props_and_unc(sawe_table, "Widget"), poi_conv = "+")
set_mass_props_and_unc(sawe_table, "Combined", mpu)
```

set_mass_props_unc *Set mass properties uncertainties for a row in a data frame*

Description

set_mass_props_unc() sets mass properties and uncertainties for a selected row in a data frame with an id column.

Usage

```
set_mass_props_unc(df, id, mpu)
```

Arguments

- | | |
|-----|--|
| df | A data frame with an id column. |
| id | The id value of the desired row. |
| mpu | A list with the following named elements: <ul style="list-style-type: none">• sigma_mass Numeric mass uncertainty.• sigma_center_mass Numeric 3-vector center of mass uncertainties.• sigma_inertia Numeric 3x3 matrix inertia tensor uncertainties. |

Value

The updated data frame.

Examples

```
set_mass_props_unc(sawe_table, "Combined", get_mass_props_unc(sawe_table, "Widget"))
```

```
set_poi_conv_from_target
```

Set POI convention for mass properties list to match a target item

Description

set_poi_conv_from_target() sets the products of inertia sign convention for a mass properties list to that of a target item in a mass properties table. This convention determines how products of inertia are saved to the data frame.

The signature of set_poi_conv_from_target() is such that it can be passed as an override argument to update_mass_props() and update_mass_props_and_unc(), thus ensuring that all calculated POI values follow the negative integral convention of the target item to which they are written.

Usage

```
set_poi_conv_from_target(df, target, mp)
```

Arguments

df	A data frame with columns id and POIconv.
target	The id value of the target row.
mp	A mass properties list.

Value

The mass properties list with the named element poi_conv set to the POIconv column of the target row in the data frame.

Examples

```
set_poi_conv_from_target(mp_table, "C.1.2.2.3.2.1", get_mass_props(mp_table, "C.1.2.2.3.2.1.1"))
```

```
set_poi_conv_minus
```

Set POI sign convention for mass properties list to "-"

Description

set_poi_conv_minus() sets the products of inertia sign convention for a mass properties list to "-". This convention determines how products of inertia are saved to a data set.

The signature of set_poi_conv_minus() is such that it can be passed as an override argument to update_mass_props() and update_mass_props_and_unc(), thus ensuring that calculated POI values are saved using the negative integral convention.

Usage

```
set_poi_conv_minus(ds, target, mp)
```

Arguments

ds	Ignored.
target	Ignored.
mp	A mass properties list.

Value

The mass properties list with the named element poi_conv set to "-"

Examples

```
set_poi_conv_minus(NULL, NULL, get_mass_props(mp_table, "C.1.2.2.3.2.1.1"))
```

set_poi_conv_plus	<i>Set POI sign convention for mass properties list to "+"</i>
-------------------	--

Description

set_poi_conv_plus() sets the products of inertia sign convention for a mass properties list to "+". This convention determines how products of inertia are saved to a data set.

The signature of set_poi_conv_plus() is such that it can be passed as an override argument to update_mass_props() and update_mass_props_and_unc(), thus ensuring that calculated POI values are saved using the positive integral convention.

Usage

```
set_poi_conv_plus(ds, target, mp)
```

Arguments

ds	Ignored.
target	Ignored.
mp	A mass properties list.

Value

The input mass properties list with the named element poi_conv set to "+"

Examples

```
set_poi_conv_plus(NULL, NULL, get_mass_props(mp_table, "C.1.2.2.3.2.1.1"))
```

test_table	<i>Example Mass Properties Table</i>
------------	--------------------------------------

Description

Example Mass Properties Table

Usage

test_table

Format

A data frame with columns:

id unique key

parent parent key

mass mass

Cx x component of center of mass

Cy y component of center of mass

Cz z component of center of mass

Ixx Ixx moment of inertia

Iyy Iyy moment of inertia

Izz Izz moment of inertia

Ixy Ixy product of inertia

Ixz Ixz product of inertia

Iyz Iyz product of inertia

POIconv sign convention for products of inertia (one of c("+", "-"))

Ipoint logical indicator to consider item a point mass

test_tree	<i>Example Mass Properties Tree</i>
-----------	-------------------------------------

Description

Example Mass Properties Tree

Usage

test_tree

Format

An igraph tree with edges from child id to parent id.

update_mass_props *Update mass properties*

Description

update_mass_props() updates mass properties for a specified target row from specified source rows in a data frame.

Usage

```
update_mass_props(df, target, sources, override = set_poi_conv_from_target)
```

Arguments

df	A data frame with (at least) these columns: id, mass, Cx, Cy, Cz, Ixx, Iyy, Izz, Ixy, Ixz, Iyz, POIconv, Ipoint.
target	The id value of the target row.
sources	List of id values of the of the source rows.
override	An override function, called as override(df, target, value). The default override sets the POI sign convention of a computed aggregate to the POIconv column of the target row in the data frame.

Value

The updated data frame.

Examples

```
leaves <- names(igraph::neighbors(test_tree, "A.3", mode = "in"))
update_mass_props(test_table, "A.3", leaves)
```

update_mass_props_and_unc
 Update mass properties and uncertainties

Description

update_mass_props_and_unc() updates mass properties and uncertainties for a specified target row from specified source rows in a data frame.

Usage

```
update_mass_props_and_unc(
  df,
  target,
  sources,
  override = set_poi_conv_from_target
)
```

Arguments

df	A data frame with (at least) these columns: id, mass, Cx, Cy, Cz, Ixx, Iyy, Izz, Ixy, Ixz, Iyz, POIconv, Ipoint, sigma_mass, sigma_Cx, sigma_Cy, sigma_Cz, sigma_Ixx, sigma_Iyy, sigma_Izz, sigma_Ixy, sigma_Ixz, sigma_Iyz.
target	The id value of the target row.
sources	List of id values of the of the source rows.
override	An override function, called as override(df, target, value). The default override sets the POI sign convention of a computed aggregate to the POIconv column of the target row in the data frame.

Value

The updated data frame.

Examples

```
leaves <- list("Widget", "2nd Part")
update_mass_props_and_unc(sawe_table, "Combined", leaves)
```

update_mass_props_unc *Update mass properties uncertainties*

Description

update_mass_props_unc() updates mass properties uncertainties for a specified target row from specified source rows in a data frame with (at least) these columns: id, sigma_mass, sigma_Cx, sigma_Cy, sigma_Cz, sigma_Ixx, sigma_Iyy, sigma_Izz, sigma_Ixy, sigma_Ixz, sigma_Iyz.

Usage

```
update_mass_props_unc(df, target, sources, override = set_poi_conv_from_target)
```

Arguments

df	A data frame with (at least) these columns: id, mass, Cx, Cy, Cz, Ixx, Iyy, Izz, Ixy, Ixz, Iyz, POIconv, Ipoint, sigma_mass, sigma_Cx, sigma_Cy, sigma_Cz, sigma_Ixx, sigma_Iyy, sigma_Izz, sigma_Ixy, sigma_Ixz, sigma_Iyz.
target	The id value of the target row.
sources	List of id values of the of the source rows.
override	An override function, called as override(df, target, value). The default override sets the POI sign convention of a computed aggregate to the POIconv column of the target row in the data frame.

Value

The updated data frame.

Examples

```
leaves <- names(igraph::neighbors(sawe_tree, "Combined", mode = "in"))
update_mass_props_unc(sawe_table, "Combined", leaves)
```

validate_mass_props *Validate mass properties*

Description

validate_mass_props() ensures that a mass properties list satisfies the following constraints:

- mass is non-missing and positive
- center_mass is a 3-vector of non-missing numeric values
- point is TRUE or FALSE
- if point is FALSE:
 - inertia is positive definite
 - eigenvalues $\{\lambda_1, \lambda_2, \lambda_3\}$ of inertia satisfy the triangle inequalities:
 - * $\lambda_1 < \lambda_2 + \lambda_3$
 - * $\lambda_2 < \lambda_1 + \lambda_3$
 - * $\lambda_3 < \lambda_1 + \lambda_2$

Usage

```
validate_mass_props(mp)
```

Arguments

- `mp` Mass properties list containing the following named elements
- `mass` Numeric mass.
 - `center_mass` Numeric 3-vector center of mass.
 - `point` Logical indicating point mass. The inertia of point masses is excluded from calculations.
 - `inertia` Numeric 3x3 matrix inertia tensor.

Value

TRUE if valid, stops otherwise

Examples

```
mp <- get_mass_props(test_table, "C.1")
validate_mass_props(mp)
```

validate_mass_props_and_unc

Validate mass properties and uncertainties

Description

`validate_mass_props_and_unc()` is a convenience wrapper that calculates the logical conjunction of `validate_mass_props()` and `validate_mass_props_unc()`.

Usage

```
validate_mass_props_and_unc(mpu)
```

Arguments

- `mpu` Mass properties and uncertainties list containing the following named elements
- `mass` mass (numeric)
 - `center_mass` center of mass (3-dimensional numeric)
 - `inertia` Inertia tensor (3x3 numeric matrix)
 - `point` Logical indicating point mass, i.e., negligible inertia
 - `sigma_mass` mass uncertainty
 - `sigma_center_mass` center of mass uncertainty (3-dimensional numeric)
 - `sigma_inertia` Inertia tensor uncertainty (3x3 numeric matrix)

Value

TRUE if valid, stops otherwise

Examples

```
mpu <- get_mass_props_and_unc(sawe_table, "Widget")
validate_mass_props_and_unc(mpu)
```

```
validate_mass_props_and_unc_table
```

Validate a mass properties and uncertainties table

Description

validate_mass_props_and_unc() calls validate_mass_props_table() and further applies the checks of validate_mass_props_and_unc() to every row of the data frame corresponding to a leaf vertex of the tree.

Usage

```
validate_mass_props_and_unc_table(tree, df)
```

Arguments

tree	An 'igraph' tree whose vertices are named as the values of the id column of df and whose directed edges point from child id to parent id.
df	A data frame with (at least) these columns: id, mass, Cx, Cy, Cz, Ixx, Iyy, Izz, Ixy, Ixz, Iyz, POIconv, Ipoint, sigma_mass, sigma_Cx, sigma_Cy, sigma_Cz, sigma_Ixx, sigma_Iyy, sigma_Izz, sigma_Ixy, sigma_Ixz, sigma_Iyz.

Value

TRUE if valid, stops with an error otherwise

Examples

```
validate_mass_props_and_unc_table(mp_tree, mp_table)
```

```
validate_mass_props_table
```

Validate a mass properties table

Description

`validate_mass_props_table()` checks that the names of vertices in a tree and the id values of a data frame are identical. It further applies the checks of `validate_mass_props()` to every row of the data frame corresponding to a leaf vertex of the tree.

`validate_mass_props_table()` ensures that the id column of the table and the vertices of the tree contain the same identifiers, and that the mass properties of every leaf element of the table are valid.

Usage

```
validate_mass_props_table(tree, df)
```

Arguments

<code>tree</code>	An 'igraph' tree whose vertices are named as the values of the id column of df and whose directed edges point from child id to parent id.
<code>df</code>	A data frame with (at least) these columns: id, mass, Cx, Cy, Cz, Ixx, Iyy, Izz, Ixy, Ixz, Iyz, POIconv, Ipoint.

Value

TRUE if valid, stops with an error otherwise

Examples

```
validate_mass_props_table(mp_tree, mp_table)
```

```
validate_mass_props_unc
```

Validate mass properties uncertainties

Description

`validate_mass_props_unc()` ensures that a mass properties and uncertainties list satisfies the following constraints:

- `sigma_mass` is non-missing and non-negative
- `sigma_center_mass` is a 3-vector of non-missing non-negative values
- if `point` is FALSE, the `sigma_inertia` contains no missing or negative values

Usage

```
validate_mass_props_unc(mp)
```

Arguments

`mp` Mass properties and uncertainties list containing the following named elements

- `point` Logical indicating point mass, i.e., negligible inertia
- `sigma_mass` mass uncertainty
- `sigma_center_mass` center of mass uncertainty (3-dimensional numeric)
- `sigma_inertia` Inertia tensor uncertainty (3x3 numeric matrix)

Value

TRUE if valid, stops otherwise

Examples

```
mp <- get_mass_props_and_unc(sawe_table, "Widget")  
validate_mass_props_unc(mp)
```

Index

* datasets

- mp_table, [7](#)
- mp_tree, [8](#)
- saw_e_table, [13](#)
- saw_e_tree, [15](#)
- test_table, [20](#)
- test_tree, [20](#)

- combine_mass_props, [2](#)
- combine_mass_props_and_unc, [3](#)
- combine_mass_props_unc, [4](#)

- get_mass_props, [5](#)
- get_mass_props_and_unc, [6](#)
- get_mass_props_unc, [7](#)

- mp_table, [7](#)
- mp_tree, [8](#)

- rollup_mass_props, [9](#)
- rollup_mass_props_and_unc, [9](#)
- rollup_mass_props_and_unc_fast, [10](#)
- rollup_mass_props_fast, [11](#)
- rollup_mass_props_unc, [12](#)
- rollup_mass_props_unc_fast, [13](#)

- saw_e_table, [13](#)
- saw_e_tree, [15](#)
- set_mass_props, [15](#)
- set_mass_props_and_unc, [16](#)
- set_mass_props_unc, [17](#)
- set_poi_conv_from_target, [18](#)
- set_poi_conv_minus, [18](#)
- set_poi_conv_plus, [19](#)

- test_table, [20](#)
- test_tree, [20](#)

- update_mass_props, [21](#)
- update_mass_props_and_unc, [21](#)
- update_mass_props_unc, [22](#)

- validate_mass_props, [23](#)
- validate_mass_props_and_unc, [24](#)
- validate_mass_props_and_unc_table, [25](#)
- validate_mass_props_table, [26](#)
- validate_mass_props_unc, [26](#)